

SAFETY DATA SHEET

A1000 GLOSS BASE PURE ORANGE RAL 2004

Section 1. Identification

GHS product identifier : A1000 GLOSS BASE PURE ORANGE RAL 2004
SDS code : 12902004B

Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Paint. Professional use Industrial use
Uses advised against
All other uses

Product use : Solvent borne coating for exterior use.

Supplier's details

MAPAERO SAS
 10, Avenue de la Rijole CS30098
 09103 PAMIERS Cedex
 France

e-mail address of person responsible for this SDS : PSRA_PAMIERS@akzonobel.com


Emergency telephone number (with hours of operation) : +33 (0)5 34 01 34 01
 +33 (0)5 61 60 23 30

2. Hazards identification

GHS Classification : FLAMMABLE LIQUIDS - Category 3
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
 AQUATIC HAZARD (ACUTE) - Category 3
 AQUATIC HAZARD (LONG-TERM) - Category 3

GHS label elements

Hazard pictograms :



Signal word :

Warning

Hazard statements :

Flammable liquid and vapor.
 May cause drowsiness or dizziness.
 Harmful to aquatic life with long lasting effects.

Precautionary statements

General :

Not applicable.

2. Hazards identification

- Prevention** : Keep away from heat, sparks and hot surfaces. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid release to the environment. Avoid breathing vapor.
- Response** : IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
- Storage** : Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number	Official Gazette notice reference number	
			CSCS	ISHL
2-ethoxy-1-methylethyl acetate	≥10 - ≤25	54839-24-6	2-3159	Not available.
n-butyl acetate	≥10 - ≤25	123-86-4	2-731	2-(6)-226
bismuth vanadium tetraoxide	7.1	14059-33-7	1-1228	Not available.
Reaction mass of ethylbenzene and xylene	2.1	-	Not available.	Not available.
titanium dioxide	≤1.0	13463-67-7	1-558; 5-5225	2-(3)-509
Hydroxyphenyl-benzotriazole derivatives	<1.0	104810-48-2	Not available.	Not available.
Polymeric Benzotriazole	<1.0	104810-47-1	Not available.	Not available.
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	<1.0	41556-26-7	5-5501	8-(1)-1709
trizinc bis(orthophosphate)	≤0.90	7779-90-0	1-1181; 1-526	(1)-1181; (1)-526
Hexanoic acid, 2-ethyl-, zinc salt, basic	<1.0	85203-81-2	2-615	Not available.
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	≤0.30	82919-37-7	5-5593	8-(1)-1721
4-methylpentan-2-one	≤0.30	108-10-1	2-542	2-542

4. First aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a

Date of issue/Date of revision : 1-11-2022 **Version** : 1.02

Date of previous issue : 21-10-2022 2/11

4. First aid measures

collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Ingestion** : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

5. Fire-fighting measures

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.

- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6. Accidental release measures

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

8. Exposure controls/personal protection

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Occupational exposure limits

Date of issue/Date of revision

: 1-11-2022

Version : 1.02

Date of previous issue

: 21-10-2022

4/11

AkzoNobel

8. Exposure controls/personal protection

Ingredient name	Exposure limits
n-butyl acetate	Japan Society for Occupational Health (Japan, 5/2019). OEL-M: 475 mg/m ³ 8 hours. OEL-M: 100 ppm 8 hours. ISHL (Japan, 10/2019). TWA: 150 ppm 8 hours.
Reaction mass of ethylbenzene and xylene	ISHL (Japan, 10/2019). TWA: 50 ppm 8 hours. Japan Society for Occupational Health (Japan, 5/2019). OEL-M: 50 ppm 8 hours. OEL-M: 217 mg/m ³ 8 hours.
4-methylpentan-2-one	Japan Society for Occupational Health (Japan, 5/2019). OEL-M: 200 mg/m ³ 8 hours. OEL-M: 50 ppm 8 hours. ISHL (Japan, 10/2019). TWA: 20 ppm 8 hours.

Individual protection measures

- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Orange.
- Odor** : Characteristic.
- pH** : Not available.
- Melting point/freezing point** : Not available.
- Boiling point, initial boiling point, and boiling range** : Not available.

9. Physical and chemical properties

Flash point	: Closed cup: 35°C
Upper/lower flammability or explosive limits	: Greatest known range: Lower: 1% Upper: 9.8% (2-ethoxy-1-methylethyl acetate)
Vapor pressure	: Not available.
Vapor density	: Highest known value: 4.6 (Air = 1) (2-methoxy-1-methylethyl acetate). Weighted average: 2.75 (Air = 1)
Density	: 1.085 g/cm ³
Solubility(ies)	: Insoluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): 1.47 cm ² /s Kinematic (40°C): 1.01 cm ² /s

10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate	LC50 Inhalation Gas.	Rat	390 ppm	4 hours
	LC50 Inhalation Vapor	Mouse	6 g/m ³	2 hours
	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Intraperitoneal	Mouse	1230 mg/kg	-
	LD50 Oral	Guinea pig	4700 mg/kg	-
	LD50 Oral	Mouse	6 g/kg	-
	LD50 Oral	Rabbit	3200 mg/kg	-
	LD50 Oral	Rat	10768 mg/kg	-
	LD50 Oral	Rat	5000 ppm	4 hours
	LD50 Inhalation Gas.	Rat	5000 ppm	4 hours
Reaction mass of ethylbenzene and xylene trizinc bis(orthophosphate)	LD50 Intraperitoneal	Mouse	552 mg/kg	-
	LD50 Intraperitoneal	Rat	551 mg/kg	-
4-methylpentan-2-one	LD50 Intraperitoneal	Guinea pig	800 mg/kg	-
	LD50 Intraperitoneal	Mouse	268 mg/kg	-
	LD50 Intraperitoneal	Rat	400 mg/kg	-
	LD50 Oral	Guinea pig	1600 mg/kg	-
	LD50 Oral	Mouse	1900 mg/kg	-
	LD50 Oral	Mouse	2850 mg/kg	-
	LD50 Oral	Mouse	2850 mg/kg	-
	LD50 Oral	Rat	2080 mg/kg	-

Date of issue/Date of revision : 1-11-2022

Version : 1.02

Date of previous issue : 21-10-2022

6/11

11. Toxicological information

LD50 Oral	Rat	4600 mg/kg	-
-----------	-----	------------	---

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
2/12902004B-ORA_SBTC_A1000G-RAL2004	N/A	66504	N/A	665	N/A
Reaction mass of ethylbenzene and xylene	N/A	1100	5000	N/A	N/A
4-methylpentan-2-one	N/A	N/A	N/A	11	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
n-butyl acetate	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
Reaction mass of ethylbenzene and xylene	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
4-methylpentan-2-one	Skin - Mild irritant	Rat	-	8 hours 60 UI	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Moderate irritant	Rabbit	-	100 %	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 UI	-
	Eyes - Severe irritant	Rabbit	-	40 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-

Respiratory sensitization/Skin sensitization

Not available.

Germ Cell Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
2-ethoxy-1-methylethyl acetate	Category 3	-	Narcotic effects
n-butyl acetate	Category 3	-	Narcotic effects
Reaction mass of ethylbenzene and xylene	Category 3	-	Respiratory tract irritation
4-methylpentan-2-one	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Reaction mass of ethylbenzene and xylene	Category 2	-	-

Aspiration hazard

Name	Result
Reaction mass of ethylbenzene and xylene	ASPIRATION HAZARD - Category 1

11. Toxicological information

12. Ecological information

Ecotoxicity

Product/ingredient name	Result	Species	Exposure	
n-butyl acetate	Acute LC50 32 mg/l Marine water	Crustaceans - Artemia salina	48 hours	
	Acute LC50 100000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours	
	Acute LC50 18000 µg/l Fresh water	Fish - Pimephales promelas	96 hours	
	Acute LC50 185000 µg/l Marine water	Fish - Menidia beryllina	96 hours	
	Acute LC50 62000 µg/l Fresh water	Fish - Danio rerio	96 hours	
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours	
	Reaction mass of ethylbenzene and xylene titanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
		Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
		Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
		Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
		Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
		Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
		Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
		Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
Acute LC50 6.5 mg/l Fresh water		Daphnia - Daphnia pulex - Neonate	48 hours	
Acute LC50 13 mg/l Fresh water		Daphnia - Daphnia pulex - Neonate	48 hours	
trizinc bis(orthophosphate) 4-methylpentan-2-one	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours	
	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours	
	Acute LC50 90 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours	
	Acute LC50 505000 µg/l Fresh water	Fish - Pimephales promelas	96 hours	
	Acute LC50 540000 µg/l Fresh water	Fish - Pimephales promelas	96 hours	
	Acute LC50 537000 µg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours	
	Chronic NOEC 78 mg/l Fresh water	Daphnia - Daphnia magna	21 days	
	Chronic NOEC 168 mg/l Fresh water	Fish - Pimephales promelas - Embryo	33 days	

Persistence/degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
n-ethoxy-1-methylethyl acetate	0.76	-	low
n-butyl acetate	2.3	-	low
bismuth vanadium tetraoxide	-	<14	low
Reaction mass of ethylbenzene and xylene	3.12	8.1 to 25.9	low
trizinc bis(orthophosphate)	-	60960	high
Hexanoic acid, 2-ethyl-, zinc salt, basic	-	60960	high

Date of issue/Date of revision : 1-11-2022

Version : 1.02

Date of previous issue : 21-10-2022

8/11

12. Ecological information

4-methylpentan-2-one	1.9	-	low
----------------------	-----	---	-----

Mobility in soil : Not available.




Hazardous to the ozone layer : Not applicable.

Other adverse effects : No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

	UN	IMDG	IATA
UN number	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	3 	3 	3 
Packing group	III	III	III
Environmental hazards	No.	No.	No.

Additional information

IMDG : **Emergency schedules** F-E, _S-E_

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

15. Regulatory information

Fire Service Law

Category	Substance name/Type	Danger category	Signal word	Designated quantity
Category IV	Class II petroleums	III	Flammable - Keep Fire Away	1000 L

ISHL

Substances requiring labelling

Ingredient name	%	Status	Reference number
n-butyl acetate	≥10 - ≤25	Listed	181
Reaction mass of ethylbenzene and xylene	≤3.0	Listed	136

Chemicals requiring notification

Ingredient name	%	Status	Reference number
n-butyl acetate	≥10 - ≤25	Listed	181
Reaction mass of ethylbenzene and xylene	≤3.0	Listed	136
titanium dioxide	≤1.0	Listed	191
4-methylpentan-2-one	≤0.30	Listed	569

Guideline for Preventing Health Hazard by chemical substances (Carcinogenicity)

Ingredient name	%	Status	Reference number
ethylbenzene	<1.0	Listed	-
4-methylpentan-2-one	≤0.30	Listed	-

ISHL Appendix 1 : Flammable liquid Class 4

Organic solvents : Class 2
poisoning prevention

Chemical Substances Control Law (CSCL)

Ingredient name	%	Status	Reference number
2,6-di-tert-butyl-p-cresol	<0.10	Priority assessment	64
Reaction mass of ethylbenzene and xylene	≤3.0	Priority assessment	125
cumene	≤0.10	Priority assessment	126
4-methylpentan-2-one	≤0.30	Priority assessment	116

Poisonous and Deleterious Substances

None of the components are listed.

Pollutant Release and Transfer Registers (PRTR)

Ingredient name	%	Status	Reference number
bismuth vanadium tetraoxide	7.1	Class 1	321
Reaction mass of ethylbenzene and xylene	2.1	Class 1	80

JSOH Carcinogen : Group 2B

16. Other information

History

Date of printing	: 1 November 2022
Date of issue/ Date of revision	: 1 November 2022
Date of previous issue	: 21 October 2022
Version	: 1.02
Unique ID	:

ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 SGG = Segregation Group
 UN = United Nations

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	On basis of test data
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
AQUATIC HAZARD (ACUTE) - Category 3	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 3	Calculation method

✔ Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.