

SAFETY DATA SHEET

FRS-40 SEMI-GLOSS BASE FLAME RED RAL 3000

Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013

Section 1. Identification

GHS product identifier : FRS-40 SEMI-GLOSS BASE FLAME RED RAL 3000
SDS code : 40903000B

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Paint. Professional use Industrial use

Uses advised against

All other uses

Product use : Solvent borne coating for interior use.

Supplier's details

MAPAERO SAS
 10, Avenue de la Rijole CS30098
 09103 PAMIERS Cedex
 France

e-mail address : PSRA_PAMIERS@akzonobel.com

Emergency telephone number (with hours of operation) : +33 (0)5 34 01 34 01
 +33 (0)5 61 60 23 30

Section 2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

Emergency overview

Liquid.
 Red.
 Characteristic.
 Flammable liquid and vapor.
 Causes mild skin irritation.
 May cause drowsiness or dizziness.
 IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

See Section 12 for environmental precautions.


Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
 SKIN CORROSION/IRRITATION - Category 3
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

Date of issue/Date of revision : 21-10-2022 **Version** : 1.01
Date of previous issue : 1-10-2022 1/13

Section 2. Hazards identification

GHS label elements

Hazard pictograms :



Signal word :

Warning

Hazard statements :

H226 - Flammable liquid and vapor.
H316 - Causes mild skin irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements

Prevention :

P210 - Keep away from heat, sparks and hot surfaces. No smoking.
P241 - Use explosion-proof electrical, ventilating or lighting equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P261 - Avoid breathing vapor.

Response :

P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Storage :

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 - Keep cool.

Disposal :

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Physical and chemical hazards :

Flammable liquid and vapor.

Health hazards :

Causes mild skin irritation. May cause drowsiness or dizziness.

Environmental hazards :

No known significant effects or critical hazards.

Other hazards which do not result in classification :

None known.

Section 3. Composition/information on ingredients

Substance/mixture :

Mixture

Ingredient name	%	CAS number
n-butyl acetate	≥25 - ≤50	123-86-4
2-methoxy-1-methylethyl acetate	≤10	108-65-6
xylene	<10	1330-20-7
ethylbenzene	≤3	100-41-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. If irritation persists, get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention if adverse health effects persist or are severe. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes mild skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Section 4. First aid measures

- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
halogenated compounds
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 6. Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
n-butyl acetate	GBZ 2.1 (China, 8/2019). PC-STEL: 300 mg/m ³ 15 minutes. PC-TWA: 200 mg/m ³ 8 hours.
xylene	GBZ 2.1 (China, 8/2019). PC-STEL: 100 mg/m ³ 15 minutes. PC-TWA: 50 mg/m ³ 8 hours.
ethylbenzene	GBZ 2.1 (China, 8/2019). PC-STEL: 150 mg/m ³ 15 minutes. PC-TWA: 100 mg/m ³ 8 hours.

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Section 8. Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Red.

Odor : Characteristic.

Odor threshold : Not available.

pH : Not available.

Melting point/freezing point : Not available.

Initial boiling point and boiling range : Not available.

Flash point : Closed cup: 28°C

Evaporation rate : Not available.

Flammability (solid, gas) : Not available.

Upper/lower flammability or explosive limits : Greatest known range: Lower: 1.4% Upper: 7.6% (n-butyl acetate)

Vapor pressure : Not available.

Section 9. Physical and chemical properties

Vapor density	: Highest known value: 4.6 (Air = 1) (2-methoxy-1-methylethyl acetate). Weighted average: 4.05 (Air = 1)
Density	: 1.244 g/cm ³ *
Solubility(ies)	: Insoluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): 8.04 cm ² /s Kinematic (40°C): 1.01 cm ² /s

* typical value, figure may vary with colour, etc

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate	LC50 Inhalation Gas.	Rat	390 ppm	4 hours
	LC50 Inhalation Vapor	Mouse	6 g/m ³	2 hours
	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Intraperitoneal	Mouse	1230 mg/kg	-
	LD50 Oral	Guinea pig	4700 mg/kg	-
	LD50 Oral	Mouse	6 g/kg	-
	LD50 Oral	Rabbit	3200 mg/kg	-
	LD50 Oral	Rat	10768 mg/kg	-
	xylene	LC50 Inhalation Gas.	Rat	6700 ppm
LC50 Inhalation Gas.		Rat	5000 ppm	4 hours
LC50 Inhalation Gas.		Rat	6670 ppm	4 hours
LD50 Intraperitoneal		Mouse	1548 mg/kg	-
LD50 Intraperitoneal		Mouse	1548 mg/kg	-
LD50 Intraperitoneal		Rat	2459 mg/kg	-
LD50 Oral		Mouse	2119 mg/kg	-
LD50 Oral		Rat	4300 mg/kg	-
LD50 Oral		Rat	4300 mg/kg	-
ethylbenzene	LD50 Subcutaneous	Rat	1700 mg/kg	-
	LC50 Inhalation Gas.	Rabbit	4000 ppm	4 hours
	LC50 Inhalation Vapor	Mouse	35500 mg/m ³	2 hours
	LC50 Inhalation Vapor	Rat	55000 mg/m ³	2 hours

Date of issue/Date of revision : 21-10-2022

Version : 1.01

Date of previous issue : 1-10-2022

7/13

Section 11. Toxicological information

	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Dermal	Rabbit	17800 uL/kg	-
	LD50 Intraperitoneal	Mouse	2624 uL/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
n-butyl acetate	Eyes - Moderate irritant Skin - Moderate irritant	Rabbit Rabbit	- -	100 mg 24 hours 500	- -
xylene	Eyes - Mild irritant Eyes - Severe irritant	Rabbit Rabbit	- -	87 mg 24 hours 5	- -
	Skin - Mild irritant Skin - Moderate irritant	Rat Rabbit	- -	8 hours 60 UI 24 hours 500	- -
ethylbenzene	Skin - Moderate irritant Eyes - Severe irritant Skin - Mild irritant	Rabbit Rabbit Rabbit	- - -	100 % 500 mg 24 hours 15	- - -

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
n-butyl acetate	Category 3	-	Narcotic effects
2-methoxy-1-methylethyl acetate	Category 3	-	Narcotic effects
xylene	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs

Aspiration hazard

Name	Result
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Date of issue/Date of revision : 21-10-2022

Version : 1.01

Date of previous issue : 1-10-2022

8/13

Section 11. Toxicological information

Eye contact	: No known significant effects or critical hazards.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: Causes mild skin irritation.
Ingestion	: Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Long term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Not available.

General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
n-butyl acetate	Acute LC50 32 mg/l Marine water	Crustaceans - Artemia salina	48 hours
	Acute LC50 100000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 18000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 185000 µg/l Marine water	Fish - Menidia beryllina	96 hours
	Acute LC50 62000 µg/l Fresh water	Fish - Danio rerio	96 hours
xylene	Acute EC50 90 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute LC50 8.5 ppm Marine water	Crustaceans - Palaemonetes	48 hours

Date of issue/Date of revision : 21-10-2022

Version : 1.01

Date of previous issue : 1-10-2022

9/13

Section 12. Ecological information

ethylbenzene	Acute LC50 8500 µg/l Marine water	pugio - Adult Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 15700 µg/l Fresh water	Fish - Lepomis macrochirus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 20870 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 19000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 16940 µg/l Fresh water	Fish - Carassius auratus	96 hours
	Acute EC50 4900 µg/l Marine water	Algae - Skeletonema costatum	72 hours
	Acute EC50 7700 µg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 5400 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 6.53 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 13.3 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 2.97 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 2.93 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 8.78 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute LC50 13.3 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute LC50 40000 µg/l Marine water	Crustaceans - Cancer magister - Zoea	48 hours
	Acute LC50 18.4 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 13.9 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Acute LC50 75000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours	
Acute LC50 5100 µg/l Marine water	Fish - Menidia menidia	96 hours	
Acute LC50 9090 µg/l Fresh water	Fish - Pimephales promelas	96 hours	
Acute LC50 9100 µg/l Fresh water	Fish - Pimephales promelas	96 hours	
Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours	
Acute LC50 4.3 ul/L Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	96 hours	

Persistence/degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
n-butyl acetate	2.3	-	low
2-methoxy-1-methylethyl acetate	1.2	-	low
xylene	3.12	8.1 to 25.9	low
ethylbenzene	3.6	-	low

Mobility in soil

Date of issue/Date of revision : 21-10-2022

Version : 1.01

Date of previous issue : 1-10-2022

10/13

Section 12. Ecological information




Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	China	IMDG	IATA
UN number	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	3 	3 	3 
Packing group	III	III	III
Environmental hazards	No.	No.	No.

Additional information

China : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.

IMDG : **Emergency schedules** F-E, _S-E_
Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Incompatible materials : Reactive or incompatible with the following materials:
oxidizing materials

Section 14. Transport information

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

China inventory (IECSC) : Not determined.

List of Goods banned for Importing

None of the components are listed.

List of Goods banned for Exporting

None of the components are listed.

List of Toxic Chemicals Severely Restricted for Importing & Exporting by China

None of the components are listed.

Inventory of Highly Toxic Articles

None of the components are listed.

Catalogue of Hazardous Chemicals of Priority Management

toluene Listed

Catalogue of Occupational Disease Hazard Factors - Dust

Ingredient name	Status
titanium dioxide	Listed
Talc , not containing asbestiform fibres	Listed
diiron trioxide	Listed

Catalogue of Occupational Disease Hazard Factors - Chemical Factors

Ingredient name	Status
n-butyl acetate	Listed
Reaction mass of ethylbenzene and xylene	Listed

Section 16. Other information

History

Date of printing : 1 November 2022

Date of issue/ Date of revision : 21 October 2022

Date of previous issue : 1 October 2022

Version : 1.01

Unique ID :

Key to abbreviations : ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 SGG = Segregation Group
 UN = United Nations

Procedure used to derive the classification

Section 16. Other information

Classification	Justification
FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	On basis of test data Calculation method Calculation method

✔ Indicates information that has changed from previously issued version.

Notice to reader**FOR PROFESSIONAL USE ONLY**

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.