

SAFETY DATA SHEET

THINNER FRSL THINNER

Section 1. Identification

GHS product identifier : THINNER FRSL THINNER
SDS code : 51711000X

Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Thinner. Professional use Industrial use
Uses advised against
All other uses

Product use : Thinner

Supplier's details

MAPAERO SAS
 10, Avenue de la Rijole CS30098
 09103 PAMIERS Cedex
 France

e-mail address of person responsible for this SDS : PSRA_PAMIERS@akzonobel.com

Emergency telephone number (with hours of operation) : +33 (0)5 34 01 34 01
 +33 (0)5 61 60 23 30

2. Hazards identification

GHS Classification : FLAMMABLE LIQUIDS - Category 3
 SKIN IRRITATION - Category 2
 EYE IRRITATION - Category 2A
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
 ASPIRATION HAZARD - Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

2. Hazards identification

Hazard statements	: Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.
Precautionary statements	
General	: Not applicable.
Prevention	: Wear protective gloves. Wear eye or face protection. Keep away from heat, sparks and hot surfaces. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapor. Wash hands thoroughly after handling.
Response	: IF INHALED: Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.

3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number	Official Gazette notice reference number	
			CSCCL	ISHL
2-methoxy-1-methylethyl acetate	≥50 - ≤75	108-65-6	2-3144	(2)-3144; 5-1518
Reaction mass of ethylbenzene and xylene	30	-	Not available.	Not available.
xylene	24	1330-20-7	3-3; 3-60	(3)-3; (3)-60
ethylbenzene	5.7	100-41-4	3-28; 3-60	(3)-28; (3)-60
2-methoxypropyl acetate	<0.30	70657-70-4	Not available.	Not available.
toluene	0.15	108-88-3	3-2; 3-60	2-(8)-869

4. First aid measures

Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

4. First aid measures

Ingestion : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact : Causes skin irritation.

Eye contact : Causes serious eye irritation.

Ingestion : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Skin contact : Adverse symptoms may include the following:
irritation
redness

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Ingestion : Adverse symptoms may include the following:
nausea or vomiting

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

5. Fire-fighting measures

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7. Handling and storage

Conditions for safe storage : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

8. Exposure controls/personal protection

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Occupational exposure limits

Ingredient name	Exposure limits
Reaction mass of ethylbenzene and xylene	ISHL (Japan, 10/2019). TWA: 50 ppm 8 hours.
xylene	Japan Society for Occupational Health (Japan, 5/2019). OEL-M: 50 ppm 8 hours. OEL-M: 217 mg/m ³ 8 hours.
ethylbenzene	ISHL (Japan, 10/2019). TWA: 50 ppm 8 hours. Japan Society for Occupational Health (Japan, 5/2019). OEL-M: 50 ppm 8 hours. OEL-M: 217 mg/m ³ 8 hours.
toluene	Japan Society for Occupational Health (Japan, 5/2019). OEL-M: 217 mg/m ³ 8 hours. OEL-M: 50 ppm 8 hours. ISHL (Japan, 10/2019). TWA: 20 ppm 8 hours. Japan Society for Occupational Health (Japan, 5/2019). Absorbed through skin. OEL-M: 188 mg/m ³ 8 hours. OEL-M: 50 ppm 8 hours. ISHL (Japan, 10/2019). TWA: 20 ppm 8 hours.

Individual protection measures

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

8. Exposure controls/personal protection

- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Colorless.
- Odor** : Characteristic.
- pH** : Not available.
- Melting point/freezing point** : Not available.
- Boiling point, initial boiling point, and boiling range** : Not available.
- Flash point** : Closed cup: 29°C
- Upper/lower flammability or explosive limits** : Greatest known range: Lower: 0.8% Upper: 6.7% (xylene)
- Vapor pressure** : Not available.
- Vapor density** : Highest known value: 4.6 (Air = 1) (2-methoxy-1-methylethyl acetate).
Weighted average: 4.33 (Air = 1)
- Density** : 0.934 g/cm³
- Solubility(ies)** : Insoluble in the following materials: cold water.
- Partition coefficient: n-octanol/ water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (room temperature): 0.11 cm²/s
Kinematic (40°C): 0.06 cm²/s

10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- Incompatible materials** : Reactive or incompatible with the following materials:
oxidizing materials

10. Stability and reactivity

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethylbenzene	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LC50 Inhalation Gas.	Rat	6700 ppm	4 hours
	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LC50 Inhalation Gas.	Rat	6670 ppm	4 hours
	LD50 Intraperitoneal	Mouse	1548 mg/kg	-
	LD50 Intraperitoneal	Mouse	1548 mg/kg	-
	LD50 Intraperitoneal	Rat	2459 mg/kg	-
	LD50 Oral	Mouse	2119 mg/kg	-
	LD50 Oral	Rat	4300 mg/kg	-
	LD50 Oral	Rat	4300 mg/kg	-
	LD50 Subcutaneous	Rat	1700 mg/kg	-
	LC50 Inhalation Gas.	Rabbit	4000 ppm	4 hours
	LC50 Inhalation Vapor	Mouse	35500 mg/m ³	2 hours
	LC50 Inhalation Vapor	Rat	55000 mg/m ³	2 hours
toluene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Dermal	Rabbit	17800 uL/kg	-
	LD50 Intraperitoneal	Mouse	2624 uL/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
	LC50 Inhalation Gas.	Mouse	400 ppm	24 hours
	LC50 Inhalation Vapor	Mouse	30000 mg/m ³	2 hours
	LC50 Inhalation Vapor	Mouse	19900 mg/m ³	7 hours
	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
	LD50 Dermal	Rabbit	14100 uL/kg	-
	LD50 Intraperitoneal	Guinea pig	500 mg/kg	-
	LD50 Intraperitoneal	Mouse	59 mg/kg	-
	LD50 Intraperitoneal	Rat	1332 mg/kg	-
	LD50 Intravenous	Rat	1960 mg/kg	-
LD50 Oral	Rat	636 mg/kg	-	
LD50 Route of exposure unreported	Mouse	2 g/kg	-	
LD50 Route of exposure unreported	Rat	6900 mg/kg	-	
LD50 Subcutaneous	Mouse	2250 mg/kg	-	

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Reaction mass of ethylbenzene and xylene	N/A	4549.2	N/A	36.9	N/A
xylene	N/A	1100	5000	N/A	N/A
ethylbenzene	N/A	1100	N/A	11	N/A
	N/A	N/A	N/A	11	N/A

Irritation/Corrosion

11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Reaction mass of ethylbenzene and xylene	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
xylene	Skin - Mild irritant	Rat	-	8 hours 60 UI	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Moderate irritant	Rabbit	-	100 %	-
	Eyes - Mild irritant	Rabbit	-	87 mg	-
ethylbenzene	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 UI	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Moderate irritant	Rabbit	-	100 %	-
toluene	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 mg	-
	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 mg	-
	Eyes - Mild irritant	Rabbit	-	870 ug	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Skin - Mild irritant	Rabbit	-	435 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Skin - Moderate irritant	Rabbit	-	500 mg	-

Respiratory sensitization/Skin sensitization

Not available.

Germ Cell Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
2-methoxy-1-methylethyl acetate	Category 3	-	Narcotic effects
Reaction mass of ethylbenzene and xylene	Category 3	-	Respiratory tract irritation
xylene	Category 3	-	Respiratory tract irritation
2-methoxypropyl acetate	Category 3	-	Respiratory tract irritation
toluene	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Reaction mass of ethylbenzene and xylene	Category 2	-	-
ethylbenzene	Category 2	-	hearing organs
toluene	Category 2	-	-

Aspiration hazard

Date of issue/Date of revision : 27-10-2022

Version : 2.01

Date of previous issue : 6-10-2022

8/13

11. Toxicological information

Name	Result
Reaction mass of ethylbenzene and xylene	ASPIRATION HAZARD - Category 1
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1
toluene	ASPIRATION HAZARD - Category 1

12. Ecological information

Ecotoxicity

Product/ingredient name	Result	Species	Exposure
Reaction mass of ethylbenzene and xylene ethylbenzene	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 90 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute LC50 8.5 ppm Marine water	Crustaceans - Palaemonetes pugio - Adult	48 hours
	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 15700 µg/l Fresh water	Fish - Lepomis macrochirus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 20870 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 19000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 16940 µg/l Fresh water	Fish - Carassius auratus	96 hours
	Acute EC50 4900 µg/l Marine water	Algae - Skeletonema costatum	72 hours
	Acute EC50 7700 µg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 5400 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 6.53 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 13.3 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 2.97 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 2.93 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 8.78 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute LC50 13.3 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute LC50 40000 µg/l Marine water	Crustaceans - Cancer magister - Zoea	48 hours
	Acute LC50 18.4 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 13.9 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Acute LC50 75000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours	
Acute LC50 5100 µg/l Marine water	Fish - Menidia menidia	96 hours	
Acute LC50 9090 µg/l Fresh water	Fish - Pimephales promelas	96 hours	
Acute LC50 9100 µg/l Fresh water	Fish - Pimephales promelas	96 hours	
Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours	
Acute LC50 4.3 ul/L Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	96 hours	

12. Ecological information

toluene	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 16500 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6.88 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 6.56 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 19600 µg/l Fresh water	Daphnia - Daphnia magna - Larvae	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute EC50 6780 µg/l Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 15.5 ppm Marine water	Crustaceans - Palaemonetes pugio - Adult	48 hours
	Acute LC50 15500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 56.3 ppm Marine water	Crustaceans - Americamysis bahia	48 hours
	Acute LC50 86.3 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Acute LC50 6410 µg/l Marine water	Fish - Oncorhynchus gorbuscha - Fry	96 hours
	Acute LC50 5800 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 6780 µg/l Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 2 mg/l Fresh water	Daphnia - Daphnia magna	21 days
Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days	

Persistence/degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2-methoxy-1-methylethyl acetate	1.2	-	low
Reaction mass of ethylbenzene and xylene	3.12	8.1 to 25.9	low
xylene	3.12	8.1 to 25.9	low
ethylbenzene	3.6	-	low
toluene	2.73	90	low

Mobility in soil

: Not available.

Hazardous to the ozone layer

: Not applicable.




Other adverse effects

: No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

	UN	IMDG	IATA
UN number	UN1263	UN1263	UN1263
UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
Transport hazard class(es)	3 	3 	3 
Packing group	III	III	III
Environmental hazards	No.	No.	No.

Additional information

IMDG : **Emergency schedules** F-E, _S-E_

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

15. Regulatory information

Fire Service Law

Category	Substance name/Type	Danger category	Signal word	Designated quantity
Category IV	Class II petroleums	III	Flammable - Keep Fire Away	1000 L

ISHL

Use of specified chemical substances

15. Regulatory information

Ingredient name	%	Status	Reference number
Ethyl benzene	<10	Group-2 Substances under Supervision	3-3

Substances requiring labelling

Ingredient name	%	Status	Reference number
Reaction mass of ethylbenzene and xylene	≥25 - ≤50	Listed	136

Chemicals requiring notification

Ingredient name	%	Status	Reference number
Reaction mass of ethylbenzene and xylene	≥25 - ≤50	Listed	136

Guideline for Preventing Health Hazard by chemical substances (Carcinogenicity)

Ingredient name	%	Status	Reference number
ethylbenzene	<10	Listed	-

ISHL Appendix 1 : Flammable liquid Class 3

Organic solvents : Class 2
poisoning prevention

Chemical Substances Control Law (CSCL)

Ingredient name	%	Status	Reference number
2,6-di-tert-butyl-p-cresol	<0.10	Priority assessment	64
Reaction mass of ethylbenzene and xylene	≥25 - ≤50	Priority assessment	125

Poisonous and Deleterious Substances

None of the components are listed.

Pollutant Release and Transfer Registers (PRTR)

Ingredient name	%	Status	Reference number
Reaction mass of ethylbenzene and xylene	30	Class 1	80

JSOH Carcinogen : Group 2B

16. Other information

History

Date of printing : 27 October 2022
Date of issue/ Date of revision : 27 October 2022
Date of previous issue : 6 October 2022
Version : 2.01

Date of issue/Date of revision : 27-10-2022

Version : 2.01

Date of previous issue : 6-10-2022

12/13

16. Other information

Unique ID

:

ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 SGG = Segregation Group
 UN = United Nations

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	On basis of test data
SKIN IRRITATION - Category 2	Calculation method
EYE IRRITATION - Category 2A	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

🔹 Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.