

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET

FR18 VELVET SEMI-GLOSS BASE GREY 3605

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1	Product	identifier
-----	---------	------------

Product name SDS code : FR18 VELVET SEMI-GLOSS BASE GREY 3605 : 55900200B

1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses	
Waterborne paint. Professional use Industrial use		
Uses advised against		
All other uses		

Product use

: Waterborne coating for interior use.

1.3 Details of the supplier of the safety data sheet

MAPAERO SAS 10, Avenue de la Rijole CS30098 09103 PAMIERS Cedex France e-mail address of person : PSRA PAMIERS@akzonobel.com

responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Center		
: +33 (0)1 40 05 48 48		
: +33 (0)5 34 01 34 01		
+33 (0)5 61 60 23 30		
:		

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Date of issue/Date of revision	: 19-10-2022	Version : 1.02	
Date of previous issue	: 17-10-2022	1/15	AkzoNobel

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 FR18 VELVET SEMI-GLOSS BASE GREY 3605

FR18 VELVET SEMI-GLOSS BASE GREY 3605		
SECTION 2: Hazards identification		
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	May cause an allergic skin reaction.
Precautionary statements		
Prevention	:	Wear protective gloves. Avoid breathing vapor.
Response	:	Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	<pre> #-morpholinecarbaldehyde C(M)IT/MIT(3:1) </pre>
Supplemental label elements	:	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	<u>its</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do	:	None known.

not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture				
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
P-butoxyethanol 4-morpholinecarbaldehyde C(M)IT/MIT(3:1)	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0 CAS: 4394-85-8 REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5	<1 <1 <0.0025	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H315 Skin Sens. 1, H317 Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Skin Sens. 1A, H317	[1] [2] [1] [1]
Date of issue/Date of revision	: 19-10-2022	Version	:1.02	
Date of previous issue	: 17-10-2022	2/15	Akzo	Nobe

SECTION 3: Composition/information on ingredients	
	Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071
	See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Date of issue/Date of revision	: 19-10-2022	Version : 1.02	
Date of previous issue	: 17-10-2022	3/15	AkzoNobe

SECTION 4: First aid measures

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 4-morpholinecarbaldehyde, C(M)IT/MIT(3:1). May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

•	
5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	from the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides halogenated compounds metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

SECTION 5: Firefighting measures				
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.			

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and materials for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Date of issue/Date of revision	: 19-10-2022	Version : 1.02	
Date of previous issue	: 17-10-2022	5/15	AkzoNobel

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 FR18 VELVET SEMI-GLOSS BASE GREY 3605

SECTION 7: Handling and storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

: Not available.

Recommendations Industrial sector specific : Not available. solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
₽-butoxyethanol	Ministry of Labor (France, 3/2020). Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA: 10 ppm 8 hours. TWA: 49 mg/m ³ 8 hours. STEL: 246 mg/m ³ 15 minutes. STEL: 50 ppm 15 minutes.
	oduct contains ingredients with exposure limits, personal, workplace ere or biological monitoring may be required to determine the effectiveness

of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient na	ame Type	Exposure	Value	Population	Effects
2-butoxyethanol	DNEL	Long term Oral	6.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	26.7 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	59 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	75 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	89 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	89 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	98 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	125 mg/kg bw/day	Workers	Systemic
te of issue/Date of revision	: 19-10-2022		Version	:1.02	
te of previous issue	:17-10-2022		6/15		AkzoNobe

SECTION 8: Exposure controls/personal protection						
	DNEL	Short term	147 mg/m ³	General	Local	
		Inhalation		population		
	DNEL	Short term	246 mg/m³	Workers	Local	
		Inhalation				
	DNEL	Short term	426 mg/m³	General	Systemic	
		Inhalation		population		
	DNEL	Short term	1091 mg/	Workers	Systemic	
		Inhalation	m³			
4-morpholinecarbaldehyde	DNEL	Long term Oral	8 mg/kg	General	Systemic	
			bw/day	population		
	DNEL	Long term Dermal	8 mg/kg	General	Systemic	
			bw/day	population		
	DNEL	Long term Dermal	14 mg/kg	Workers	Systemic	
			bw/day			
	DNEL	Long term	29 mg/m³	General	Systemic	
		Inhalation		population		
	DNEL	Long term	98 mg/m³	Workers	Systemic	
		Inhalation				

PNECs

No PNECs available.

Individual protection measures : Wash hands, forearms and face thoroughly after handling chemical product before eating, smoking and using the lavatory and at the end of the working Appropriate techniques should be used to remove potentially contaminated Contaminated work clothing should not be allowed out of the workplace. We contaminated clothing before reusing. Ensure that eyewash stations and showers are close to the workstation location. Eye/face protection : Safety eyewear complying with an approved standard should be used where assessment indicates this is necessary to avoid exposure to liquid splashere gases or dusts. If contact is possible, the following protection should be work unless the assessment indicates a higher degree of protection: safety glass side-shields. Skin protection : Chemical-resistant, impervious gloves complying with an approved standard be worn at all times when handling chemical products if a risk assessment this is necessary. Considering the parameters specified by the glove manu, check during use that the gloves are still retaining their protective properties should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consist several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374 recommended. Recommended gloves: Nitnle, thickness ≥ 0.38 When only brief contact is expected, a glove with protection class of 2 or hi (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitnle, thickness ≥ 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to t	airborne
before eating, smoking and using the lavatory and at the end of the working Appropriate techniques should be used to remove potentially contaminated Contaminated clothing behould not be allowed out of the workplace. We contaminated clothing before reusing. Ensure that eyewash stations and s showers are close to the workstation location.Eye/face protection: Safety eyewear complying with an approved standard should be used wher assessment indicates this is necessary to avoid exposure to liquid splashe gases or dusts. If contact is possible, the following protection should be w unless the assessment indicates a higher degree of protection: safety glas side-shields.Hand protection: Chemical-resistant, impervious gloves complying with an approved standard be worn at all times when handling chemical products if a risk assessment this is necessary. Considering the parameters specified by the glove many check during use that the gloves are still retaining their protective propertie should be noted that the time to breakthrough for any glove material may b different for different glove manufacturers. In the case of mixtures, consist several substances, the protection time of the gloves cannot be accurately estimated.When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) te commended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 When only brief contact is expected, a glove with protection class of 2 or hi (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to t material. The performance or effectiveness of the glove may be reduced by physical	
 assessment indicates this is necessary to avoid exposure to liquid splashed gases or dusts. If contact is possible, the following protection should be we unless the assessment indicates a higher degree of protection: safety glas side-shields. Skin protection Hand protection Chemical-resistant, impervious gloves complying with an approved standard be worn at all times when handling chemical products if a risk assessment this is necessary. Considering the parameters specified by the glove manu check during use that the gloves are still retaining their protective propertie should be noted that the time to breakthrough for any glove material may b different for different glove manufacturers. In the case of mixtures, consist several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374 recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 When only brief contact is expected, a glove with protection class of 2 or hi (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the material. 	g period. I clothing Vash
 Hand protection Chemical-resistant, impervious gloves complying with an approved standard be worn at all times when handling chemical products if a risk assessment this is necessary. Considering the parameters specified by the glove many check during use that the gloves are still retaining their protective properties should be noted that the time to breakthrough for any glove material may b different for different glove manufacturers. In the case of mixtures, consist several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374 recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 When only brief contact is expected, a glove with protection class of 2 or hi (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the material. 	s, mists, orn,
be worn at all times when handling chemical products if a risk assessment this is necessary. Considering the parameters specified by the glove manu check during use that the gloves are still retaining their protective propertie should be noted that the time to breakthrough for any glove material may b different for different glove manufacturers. In the case of mixtures, consist several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374 recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 When only brief contact is expected, a glove with protection class of 2 or hi (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the material.	
protection class of 6 (breakthrough time >480 minutes according to EN374 recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 When only brief contact is expected, a glove with protection class of 2 or hi (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the material. The performance or effectiveness of the glove may be reduced by physical	indicate ufacture s. It e ing of
	´mm. igher
	/
Date of issue/Date of revision : 19-10-2022 Version : 1.02	
Date of previous issue : 17-10-2022 7/15 Akzo	Nobe

SECTION 8: Exposure controls/personal protection

		The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Gray.
Odor	: Characteristic.
Odor threshold	: Not available.
рН	: 8
Melting point/freezing point	: Not available.
Initial boiling point and	: Not available.
boiling range	
Flash point	: Closed cup: 105°C
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Upper/lower flammability or explosive limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Highest known value: (Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether).
Density	: 1.055 g/cm³
Solubility(ies)	: Easily soluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): 10.43 cm ² /s Kinematic (40°C): 2.01 cm ² /s



SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingred	dients.
10.2 Chemical stability	The product is stable.	
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occ	cur.
10.4 Conditions to avoid	No specific data.	
10.5 Incompatible materials	No specific data.	
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition prodused.	ucts

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethanol	LC50 Inhalation Gas.	Mouse	700 ppm	7 hours
-	LC50 Inhalation Gas.	Rat	450 ppm	4 hours
	LC50 Inhalation Vapor	Mouse	3380 mg/m ³	7 hours
	LC50 Inhalation Vapor	Rat	2900 mg/m ³	7 hours
	LD50 Dermal	Guinea pig	230 uL/kg	-
	LD50 Dermal	Rabbit	220 mg/kg	-
	LD50 Intraperitoneal	Mouse	536 mg/kg	-
	LD50 Intraperitoneal	Rabbit	220 mg/kg	-
	LD50 Intraperitoneal	Rat	220 mg/kg	-
	LD50 Intravenous	Mouse	1130 mg/kg	-
	LD50 Intravenous	Rabbit	252 mg/kg	-
	LD50 Intravenous	Rat	307 mg/kg	-
	LD50 Oral	Guinea pig	1200 mg/kg	-
	LD50 Oral	Mouse	1230 mg/kg	-
	LD50 Oral	Mouse	1167 mg/kg	-
	LD50 Oral	Rabbit	300 mg/kg	-
	LD50 Oral	Rabbit	320 mg/kg	-
	LD50 Oral	Rat	917 mg/kg	-
	LD50 Oral	Rat	250 mg/kg	-
	LD50 Route of exposure	Mouse	1050 mg/kg	-
	unreported .			
	LD50 Route of exposure	Rat	917 mg/kg	-
	unreported			
4-morpholinecarbaldehyde	LD50 Oral	Rat	6500 uL/kg	-

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
				mg	
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
4-morpholinecarbaldehyde	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
Conclusion/Summary	: Not available.				
ate of issue/Date of revision	: 19-10-2022	Vers	sion : 1.02	2	
ate of previous issue	:17-10-2022	9/15	i		AkzoNobel

SECTION 11: Toxicological information

	eg.ea		
Sensitization			
Conclusion/Summary	: Not available.		
<u>Mutagenicity</u>			
Conclusion/Summary	: Not available.		
<u>Carcinogenicity</u>			
Conclusion/Summary	: Not available.		
Reproductive toxicity			
Conclusion/Summary	: Not available.		
<u>Teratogenicity</u>			
Conclusion/Summary	: Not available.		
<u>Specific target organ toxici</u>	<u>ty (single exposure)</u>		
Not available.			
Specific target organ toxici	ty (repeated exposure)		
Not available.			
Aspiration hazard			
Not available.			
Information on the likely	: Not available.		
routes of exposure	. Not available.		
Potential acute health effect	<u>s</u>		
Eye contact	 No known significant e 	ffects or critical hazards.	
Inhalation	: No known significant e		
Skin contact	: May cause an allergic		
Ingestion	: No known significant e		
-	-		
Symptoms related to the phy	ysical, chemical and toxic	ological characteristics	
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: Adverse symptoms ma	ay include the following:	
	irritation redness		
Ingestion	: No specific data.		
ingeetion			
Delayed and immediate effe	cts and also chronic effec	ts from short and long term exposit	ire
Short term exposure			
Potential immediate	: Not available.		
effects			
Potential delayed effects	: Not available.		
Long term exposure			
Potential immediate	: Not available.		
effects			
Potential delayed effects	: Not available.		
Potential chronic health eff	ects		
Not available.			
Conclusion/Summary	: Not available.		
General		ere allergic reaction may occur when	subsequently exposed
	to very low levels.		
Date of issue/Date of revision	: 19-10-2022	Version : 1.02	
Date of previous issue	: 17-10-2022	10/15	AkzoNobel
1			

SECTION 11: Toxicological information	
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

Product/ingredient name	Result	Species	Exposure
2-butoxyethanol	Acute LC50 800000 µg/l Marine water	Fish - Lepomis macrochirus	48 hours 48 hours 96 hours 96 hours

Conclusion/Summary

: Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-butoxyethanol	0.81	-	low
4-morpholinecarbaldehyde	-	<1.9	low

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product



SECTION 13: Disposal considerations

Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
Disposal considerations	: Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11
Packaging	
Methods of disposal	The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	 Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 FR18 VELVET SEMI-GLOSS BASE GREY 3605

	FR18 VELVET SEMI-GLOSS BASE GREY 3605	
SECTION 14: Transp	ort information	
14.7 Transport in bulk according to IMO instruments	: Not applicable.	
SECTION 15: Regula	tory information	
15.1 Safety, health and enviro	onmental regulations/legislation specific for t	the substance or mixture
EU Regulation (EC) No. 190	<u>7/2006 (REACH)</u>	
Annex XIV - List of substar	nces subject to authorization	
Annex XIV		
None of the components ar		
Substances of very high (
None of the components ar		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.	
Other EU regulations		
VOC	: The provisions of Directive 2004/42/EC on V product label and/or technical data sheet for	
VOC for Ready-for-Use Mixture	: Not applicable.	
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed	
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed	
Ozone depleting substance	<u>es (1005/2009/EU)</u>	
Not listed.		
Prior Informed Consent (P Not listed.	IC) (649/2012/EU)	
Seveso Directive		
This product is not controlled	d under the Seveso Directive.	
National regulations		
Industrial use	: The information contained in this safety data own assessment of workplace risks, as requ legislation. The provisions of the national her to the use of this product at work.	ired by other health and safety
Social Security Code, Articles L 461-1 to L 461-7	: Z-butoxyethanol	RG 84
Reinforced medical surveillance	: Decree n ° 2012-135 of January 30, 2012 re occupational medicine: not applicable	lating to the organization of
International regulations		
<u>Chemical Weapon Conventi</u>	ion List Schedules I, II & III Chemicals	
Not listed.		
Montreal Protocol		

Date of issue/Date of revision	: 19-10-2022	Version	:1.02
Date of previous issue	: 17-10-2022	13/15	



SECTION 15: Regulatory information

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Europe

: Not determined.

15.2 Chemical Safety : No Chemical Safety Assessment has been carried out.

Assessment

SECTION 16: Other information

\checkmark	Indicates information	that has changed fro	om previously issued version.	

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method

Full text of abbreviated H statements

H 301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Date of issue/Date of revision	: 19-10-2022	Version : 1.02	
Date of previous issue	: 17-10-2022	14/15	AkzoNobel

SECTION 16: Other information				
Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Eye Irrit. 2 Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A		ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 1C SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A		
Date of printing	: 31 October 2022			
Date of issue/ Date of revision	: 19 October 2022			
Date of previous issue	: 17 October 2022			
Version	: 1.02			
Unique ID	:			

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

