

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET

FR2-55 SEMI-GLOSS BASE BROWN L2/8253

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name SDS code : FR2-55 SEMI-GLOSS BASE BROWN L2/8253 : 55928253B

1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified uses | | |
|---|--|--|
| Waterborne paint. Professional use Industrial use | | |
| Uses advised against | | |
| All other uses | | |
| | | |

Product use

: Waterborne coating for interior use.

1.3 Details of the supplier of the safety data sheet

MAPAERO SAS 10, Avenue de la Rijole CS30098 09103 PAMIERS Cedex France e-mail address of person : PSRA PAMIERS@akzonobel.com

responsible for this SDS

1.4 Emergency telephone number <u>National advisory body/Poison Center</u> Telephone number

| Telephone number | : +33 (0)1 40 05 48 48 |
|--------------------|------------------------|
| <u>Supplier</u> | |
| Telephone number | : +33 (0)5 34 01 34 01 |
| | +33 (0)5 61 60 23 30 |
| Hours of operation | : |

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

| Date of issue/Date of revision | : 21-10-2022 | Version : 1.01 | |
|--------------------------------|--------------|----------------|-----------|
| Date of previous issue | : 5-10-2022 | 1/15 | AkzoNobel |

| | | FR2-55 SEMI-GLOSS BASE BROWN L2/8253 |
|---|-----|---|
| SECTION 2: Hazards | ic | dentification |
| Hazard pictograms | : | |
| Signal word | : | Warning |
| Hazard statements | : | May cause an allergic skin reaction. |
| Precautionary statements | | |
| Prevention | : | Wear protective gloves. Avoid breathing vapor. |
| Response | : | Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. |
| Storage | : | Not applicable. |
| Disposal | : | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Hazardous ingredients | : | C(M)IT/MIT(3:1) |
| Supplemental label elements | : | Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : | Not applicable. |
| Special packaging requirem | ner | <u>its</u> |
| Containers to be fitted with child-resistant fastenings | : | Not applicable. |
| Tactile warning of danger | : | Not applicable. |
| 2.3 Other hazards | | |
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : | This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do | : | None known. |

not result in classification

SECTION 3: Composition/information on ingredients

| 3.2 Mixtures : Mixture | | | | |
|------------------------------------|---|----------|---|---------|
| Product/ingredient name | Identifiers | % | Regulation (EC) No. 1272/2008 [CLP] | Туре |
| Z-butoxyethanol C(M)IT/MIT(3:1) | REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0 REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5 | <1 | Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) | [1] [2] |
| Date of issue/Date of revision | : 21-10-2022 | Version | : 1.01 | 1 |
| Date of previous issue : 5-10-2022 | | 2/15 Akz | | Nobe |

| SECTION 3: Composition/information on ingredients | | |
|---|---|--|
| | Aquatic Chronic 1, H410 (M=100) EUH071 | |
| | See Section 16 for the full text of the H statements declared above. | |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

| Eye contact | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs. |
|----------------------------|--|
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Skin contact | : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Ingestion | : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

4.2 Most important symptoms and effects, both acute and delayed

SECTION 4: First aid measures

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains C(M)IT/MIT(3:1). May produce an allergic reaction.

Over-exposure signs/symptoms

| Eye contact | : No specific data. |
|--------------|--|
| Inhalation | : No specific data. |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : No specific data. |

4.3 Indication of any immediate medical attention and special treatment needed

| Notes to physician | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
|---------------------|---|
| Specific treatments | : No specific treatment. |

SECTION 5: Firefighting measures

| 5.1 Extinguishing media | | | | |
|--|---|--|--|-----------------|
| Suitable extinguishing media | : | Use an extinguishing agent su | itable for the surrounding fire. | |
| Unsuitable extinguishing media | : | None known. | | |
| 5.2 Special hazards arising fi | ron | n the substance or mixture | | |
| Hazards from the substance or mixture | : | In a fire or if heated, a pressu | re increase will occur and the conta | iner may burst. |
| Hazardous combustion products | : | Decomposition products may carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides | include the following materials: | |
| 5.3 Advice for firefighters | | | | |
| Special protective actions for fire-fighters | : | | removing all persons from the vicir be taken involving any personal ris | |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. | | | |
| Date of issue/Date of revision | | : 21-10-2022 | Version : 1.01 | |
| Date of previous issue | | : 5-10-2022 | 4/15 | AkzoNobel |
| N | | | | |

SECTION 6: Accidental release measures

| 6.1 Personal precautions, pro | tective equipment and emergency procedures |
|---------------------------------|---|
| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders | : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| 6.2 Environmental precautions | : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |
| 6.3 Methods and materials for | containment and cleaning up |
| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Large spill | : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. |
| 6.4 Reference to other sections | : See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information. |

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

| Protective measures | : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|--|---|
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

| Date of issue/Date of revision | : 21-10-2022 | Version : 1.01 | |
|--------------------------------|--------------|----------------|-----------|
| Date of previous issue | : 5-10-2022 | 5/15 | AkzoNobel |

SECTION 7: Handling and storage

| 7.3 Specific end use(s) | |
|----------------------------|------------------|
| Recommendations | : Not available. |
| Industrial sector specific | : Not available. |
| solutions | |

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| | | Exposure limit values | |
|-----------------------------------|---|---|--|
| | | Ministry of Labor (France, 3/2020). Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA: 10 ppm 8 hours. TWA: 49 mg/m ³ 8 hours. STEL: 246 mg/m ³ 15 minutes. STEL: 50 ppm 15 minutes. | |
| Recommended monitoring procedures | atmosphere of the ventila protective eq | et contains ingredients with exposure limits, personal, workplace or biological monitoring may be required to determine the effectiveness tion or other control measures and/or the necessity to use respiratory upment. Reference should be made to monitoring standards, such as : European Standard EN 689 (Workplace atmospheres - Guidance for | |

protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | е Туре | Exposure | Value | Population | Effects |
|-----------------------------|--------------|-------------------|-----------------------|------------|----------|
| 2-butoxyethanol | DNEL | Long term Oral | 6.3 mg/kg | General | Systemic |
| | | Ŭ | bw/day | population | , |
| | DNEL | Short term Oral | 26.7 mg/ | General | Systemic |
| | | | kg bw/day | population | , |
| | DNEL | Long term | 59 mg/m ³ | General | Systemic |
| | | Inhalation | U U | population | |
| | DNEL | Long term Dermal | 75 mg/kg | General | Systemic |
| | | | bw/day | population | - |
| | DNEL | Short term Dermal | 89 mg/kg | General | Systemic |
| | | | bw/day | population | - |
| | DNEL | Short term Dermal | 89 mg/kg | Workers | Systemic |
| | | | bw/day | | - |
| | DNEL | Long term | 98 mg/m ³ | Workers | Systemic |
| | | Inhalation | - | | |
| | DNEL | Long term Dermal | 125 mg/kg | Workers | Systemic |
| | | | bw/day | | |
| | DNEL | Short term | 147 mg/m ³ | General | Local |
| | | Inhalation | _ | population | |
| | DNEL | Short term | 246 mg/m ³ | Workers | Local |
| | | Inhalation | | | |
| | DNEL | Short term | 426 mg/m ³ | General | Systemic |
| | | Inhalation | | population | |
| e of issue/Date of revision | : 21-10-2022 | <u> </u> | Version | : 1.01 | 1 |
| te of previous issue | : 5-10-2022 | | 6/15 | | AkzoNob |

| | | | EMI-GLOSS BASE BRO | | | |
|-------------------------------------|--|---|--|--|---|---|
| SECTION 8: Exposu | re con | - | - | | | |
| | | DNEL | Short term Inhalation | 1091 mg/ m³ | Workers | Systemic |
| PNECs | | | | | | |
| No PNECs available. | | | | | | |
| 8.2 Exposure controls | 0 | | | <i></i> | | |
| Appropriate engineering controls | | d genera aminants | | e sufficient to | o control worker | exposure to airborne |
| Individual protection meas | ures | | | | | |
| Hygiene measures | befc App Con cont | re eating ropriate t taminate aminated | | the lavatory used to rem ld not be allo sing. Ensure | and at the end ove potentially wed out of the v | of the working period. contaminated clothing. workplace. Wash |
| Eye/face protection | asse gase unle | essment i es or dus | ndicates this is nece ts. If contact is poss | ssary to avoi ible, the follo | id exposure to li wing protection | be used when a risk quid splashes, mists, should be worn, n: safety glasses with |
| Skin protection | | | | | | |
| Hand protection | be v this chea shou diffe seve estin | vorn at al is necess ck during uld be no rent for d eral subst mated. | I times when handlin sary. Considering the use that the gloves a ted that the time to b lifferent glove manuf ances, the protection | g chemical p e parameters are still retair reakthrough acturers. In n time of the | roducts if a risk s specified by th ning their protec for any glove m the case of mixi gloves cannot b | aterial may be tures, consisting of be accurately |
| | prot recc Whe (bre Rec Glov | ection cla ommende en only br akthroug ommend | ged or frequently rep iss of 6 (breakthroug d. Recommended g ief contact is expect h time >30 minutes a ed gloves: Nitrile, thi d be replaced regula | h time >480 loves: Viton ed, a glove w according to I ckness ≥ 0.1. | minutes accord ® or Nitrile, thic vith protection cl EN374) is recor 2 mm. | ing to EN374) is kness ≥ 0.38 mm. lass of 2 or higher |
| | | • | ance or effectiveness nage and poor maint | • | may be reduce | d by physical/ |
| | proc | luct is the | | nd takes into | account the pa | ected for handling this rticular conditions of |
| Body protection | bein | g perforn | tective equipment for ned and the risks inv ng this product. | | | |
| Other skin protection | sele | cted base | ootwear and any add ed on the task being a specialist before ha | performed a | nd the risks invo | |
| Respiratory protection | app resp | ropriate s | tandard or certification of the termination of terminatio of t | on. Respirate | ors must be use | irator that meets the ed according to a g, and other important |



SECTION 8: Exposure controls/personal protection

| Environmental exposure | : Emissions from ventilation or work process equipment should be checked to |
|------------------------|--|
| controls | ensure they comply with the requirements of environmental protection legislation. |
| | In some cases, fume scrubbers, filters or engineering modifications to the process |
| | equipment will be necessary to reduce emissions to acceptable levels. |

SECTION 9: Physical and chemical properties

| 9.1 Information on basic physica | l a | nd chemical properties |
|---|-----|---|
| <u>Appearance</u> | | |
| Physical state | : | Liquid. |
| Color | : | Brown. |
| Odor | : | Characteristic. |
| Odor threshold | : | Not available. |
| рН | : | 8 |
| Melting point/freezing point | : | Not available. |
| Initial boiling point and boiling range | : | Not available. |
| Flash point | : | Closed cup: 105°C |
| Evaporation rate | : | Not available. |
| Flammability (solid, gas) | : | Not available. |
| Upper/lower flammability or explosive limits | : | Not available. |
| Vapor pressure | : | Not available. |
| Vapor density | : | Highest known value: (Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether). |
| Density | : | 1.314 g/cm ³ |
| Solubility(ies) | : | Easily soluble in the following materials: cold water. |
| Partition coefficient: n-octanol/ water | : | Not available. |
| Auto-ignition temperature | : | Not available. |
| Decomposition temperature | : | Not available. |
| Viscosity | : | Kinematic (room temperature): 4.41 cm²/s Kinematic (40°C): 2.01 cm²/s |
| | | |

| SECTION 10: Stability and reactivity | | | | |
|--|--|--|--|--|
| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. | | | |
| 10.2 Chemical stability | : The product is stable. | | | |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. | | | |
| 10.4 Conditions to avoid | : No specific data. | | | |
| 10.5 Incompatible materials | : No specific data. | | | |
| 10.6 Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. | | | |

| Date of issue/Date of revision | : 21-10-2022 | Version : 1.01 | |
|--------------------------------|--------------|----------------|-----------|
| Date of previous issue | : 5-10-2022 | 8/15 | AkzoNobel |

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|------------------------|------------|------------------------|----------|
| 2-butoxyethanol | LC50 Inhalation Gas. | Mouse | 700 ppm | 7 hours |
| - | LC50 Inhalation Gas. | Rat | 450 ppm | 4 hours |
| | LC50 Inhalation Vapor | Mouse | 3380 mg/m ³ | 7 hours |
| | LC50 Inhalation Vapor | Rat | 2900 mg/m ³ | 7 hours |
| | LD50 Dermal | Guinea pig | 230 uL/kg | - |
| | LD50 Dermal | Rabbit | 220 mg/kg | - |
| | LD50 Intraperitoneal | Mouse | 536 mg/kg | - |
| | LD50 Intraperitoneal | Rabbit | 220 mg/kg | - |
| | LD50 Intraperitoneal | Rat | 220 mg/kg | - |
| | LD50 Intravenous | Mouse | 1130 mg/kg | - |
| | LD50 Intravenous | Rabbit | 252 mg/kg | - |
| | LD50 Intravenous | Rat | 307 mg/kg | - |
| | LD50 Oral | Guinea pig | 1200 mg/kg | - |
| | LD50 Oral | Mouse | 1230 mg/kg | - |
| | LD50 Oral | Mouse | 1167 mg/kg | - |
| | LD50 Oral | Rabbit | 300 mg/kg | - |
| | LD50 Oral | Rabbit | 320 mg/kg | - |
| | LD50 Oral | Rat | 917 mg/kg | - |
| | LD50 Oral | Rat | 250 mg/kg | - |
| | LD50 Route of exposure | Mouse | 1050 mg/kg | - |
| | unreported | | 0.0 | |
| | LD50 Route of exposure | Rat | 917 mg/kg | - |
| | unreported | | 5 5 | |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------------|----------------------------|---------|-------|--------------|-------------|
| 2-butoxyethanol | Eyes - Moderate irritant | Rabbit | - | 24 hours 100 | - |
| | | | | mg | |
| | Eyes - Severe irritant | Rabbit | - | 100 mg | - |
| | Skin - Mild irritant | Rabbit | - | 500 mg | - |
| Conclusion/Summary | : Not available. | | | | |
| <u>Sensitization</u> | | | | | |
| Conclusion/Summary | : Not available. | | | | |
| Mutagenicity | | | | | |
| Conclusion/Summary | : Not available. | | | | |
| Carcinogenicity | | | | | |
| Conclusion/Summary | : Not available. | | | | |
| Reproductive toxicity | | | | | |
| Conclusion/Summary | : Not available. | | | | |
| Teratogenicity | | | | | |
| Conclusion/Summary | : Not available. | | | | |
| Specific target organ toxicit | <u>y (single exposure)</u> | | | | |
| Not available. | | | | | |
| | | | | | |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

| | FR2-55 SEMI-GLOSS BASE BROWN L2/8253 | |
|--|--|---------|
| SECTION 11: Toxico | al information | |
| Information on the likely routes of exposure | t available. | |
| Potential acute health effects | | |
| Eye contact | known significant effects or critical hazards. | |
| Inhalation | known significant effects or critical hazards. | |
| Skin contact | y cause an allergic skin reaction. | |
| Ingestion | known significant effects or critical hazards. | |
| Symptoms related to the phy | chemical and toxicological characteristics | |
| Eye contact | specific data. | |
| Inhalation | specific data. | |
| Skin contact | verse symptoms may include the following: tation Iness | |
| Ingestion | specific data. | |
| Delayed and immediate effect | also chronic effects from short and long term exposure | |
| <u>Short term exposure</u> | | |
| Potential immediate effects | t available. | |
| Potential delayed effects | t available. | |
| <u>Long term exposure</u> | | |
| Potential immediate effects | t available. | |
| Potential delayed effects | t available. | |
| Potential chronic health eff | | |
| Not available. | | |
| Conclusion/Summary | t available. | |
| General | ce sensitized, a severe allergic reaction may occur when subsequently very low levels. | exposed |
| Carcinogenicity | known significant effects or critical hazards. | |
| Mutagenicity | known significant effects or critical hazards. | |
| Reproductive toxicity | known significant effects or critical hazards. | |
| | | |

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

| Product/ingredient name | Result | Species | Exposure |
|--------------------------------|---|---|--|
| ₽-butoxyethanol | Acute EC50 >1000 mg/l Fresh water Acute LC50 800000 μg/l Marine water Acute LC50 1490000 μg/l Fresh water Acute LC50 1250000 μg/l Marine water | Daphnia - Daphnia magna Crustaceans - Crangon crango Fish - Lepomis macrochirus Fish - Menidia beryllina | 48 hours n 48 hours 96 hours 96 hours |
| Conclusion/Summary | : Not available. | | |
| Date of issue/Date of revision | : 21-10-2022 | Version : 1.01 | |
| Date of previous issue | : 5-10-2022 | 10/15 | AkzoNobel |

SECTION 12: Ecological information

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| 2-butoxyethanol | 0.81 | - | low |

12.4 Mobility in soil

| Soil/water partition coefficient (K _{oc}) | : Not available. |
|---|------------------|
| Mobility | : Not available. |

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

| <u>Product</u> | |
|-------------------------|--|
| Methods of disposal | : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. |
| Hazardous waste | : The classification of the product may meet the criteria for a hazardous waste. |
| Disposal considerations | : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority. |

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

| Waste code | Waste designation | |
|-------------------------|---|--|
| EWC 08 01 12 | waste paint and varnish other than those mentioned in 08 01 11 | |
| Packaging | | |
| Methods of disposal | The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. | |
| Disposal considerations | Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions. | |

| Date of issue/Date of revision | : 21-10-2022 | Version : 1.01 | |
|--------------------------------|--------------|----------------|-----------|
| Date of previous issue | : 5-10-2022 | 11/15 | AkzoNobel |

SECTION 13: Disposal considerations

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | IMDG | ΙΑΤΑ |
|------------------------------------|----------------|----------------|----------------|
| 14.1 UN number | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - | - |
| 14.3 Transport hazard class(es) | - | - | - |
| 14.4 Packing group | - | - | - |
| 14.5 Environmental hazards | No. | No. | No. |

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk: Not applicable.according to IMOinstruments

SECTION 15: Regulatory information

| 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixt | ure |
|--|-----|
| EU Regulation (EC) No. 1907/2006 (REACH) | |

Annex XIV - List of substances subject to authorization

None of the components are listed. Substances of very high concern None of the components are listed. Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles **Other EU regulations** VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information. VOC for Ready-for-Use : Not applicable. Mixture

Annex XIV



| SECTION 15: Regulat | ory information | |
|---|--|-----------------------|
| Industrial emissions (integrated pollution prevention and control) - Air | : Not listed | |
| Industrial emissions (integrated pollution prevention and control) - Water | : Not listed | |
| Ozone depleting substance Not listed. | es (1005/2009/EU) | |
| Prior Informed Consent (Ple Not listed. | <u>C) (649/2012/EU)</u> | |
| Seveso Directive | | |
| This product is not controlled | under the Seveso Directive. | |
| National regulations | | |
| Industrial use | : The information contained in this safety data sheet doe own assessment of workplace risks, as required by oth legislation. The provisions of the national health and sa to the use of this product at work. | ner health and safety |
| Social Security Code, Articles L 461-1 to L 461-7 | : Z-butoxyethanol | RG 84 |
| Reinforced medical surveillance | : Decree n ° 2012-135 of January 30, 2012 relating to th occupational medicine: not applicable | e organization of |
| International regulations | | |
| Chemical Weapon Convention Not listed. | on List Schedules I, II & III Chemicals | |
| Montreal Protocol Not listed. | | |
| Stockholm Convention on P Not listed. | ersistent Organic Pollutants | |
| Rotterdam Convention on P | rior Informed Consent (PIC) | |
| Not listed. | | |
| UNECE Aarhus Protocol on Not listed. | POPs and Heavy Metals | |
| <u>Inventory list</u> Europe | : Not determined. | |
| 15.2 Chemical Safety Assessment | : No Chemical Safety Assessment has been carried out | |
| SECTION 16: Other in | formation | |

Indicates information that has changed from previously issued version.



| Abbreviations and | : ATE = Acute Toxicity Estimate |
|-------------------|--|
| acronyms | CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] |
| | DMEL = Derived Minimal Effect Level |
| | DNEL = Derived No Effect Level |
| | EUH statement = CLP-specific Hazard statement |
| | N/A = Not available |
| | PBT = Persistent, Bioaccumulative and Toxic |
| | PNEC = Predicted No Effect Concentration |
| | RRN = REACH Registration Number |
| | SGG = Segregation Group |
| | vPvB = Very Persistent and Very Bioaccumulative |

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|--------------------|--------------------|
| Skin Sens. 1, H317 | Calculation method |

Full text of abbreviated H statements

| F 301 | Toxic if swallowed. |
|--------------|---|
| H302 | Harmful if swallowed. |
| H310 | Fatal in contact with skin. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H330 | Fatal if inhaled. |
| H332 | Harmful if inhaled. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract. |

Full text of classifications [CLP/GHS]

| Kcute Tox. 2 | ACUTE TOXICITY - Category 2 |
|-------------------|---|
| Acute Tox. 3 | ACUTE TOXICITY - Category 3 |
| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
| Aquatic Acute 1 | AQUATIC HAZARD (ACUTE) - Category 1 |
| Aquatic Chronic 1 | AQUATIC HAZARD (LONG-TERM) - Category 1 |
| Eye Irrit. 2 | SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 |
| Skin Corr. 1C | SKIN CORROSION/IRRITATION - Category 1C |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| Skin Sens. 1 | SKIN SENSITIZATION - Category 1 |
| Skin Sens. 1A | SKIN SENSITIZATION - Category 1A |

| Date of printing | : 31 October 2022 |
|------------------------|-------------------|
| Date of issue/ Date of | : 21 October 2022 |
| revision | |
| Date of previous issue | : 5 October 2022 |
| Version | : 1.01 |
| Unique ID | : |
| | |

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality

| Date of issue/Date of revision | : 21-10-2022 | Version : 1.01 | |
|--------------------------------|--------------|----------------|-----------|
| Date of previous issue | : 5-10-2022 | 14/15 | AkzoNobel |

SECTION 16: Other information

or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

