

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET

FR2-55 SEMI-GLOSS BASE BLACK KANSAS 2002 V2/9679

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name SDS code

: FR2-55 SEMI-GLOSS BASE BLACK KANSAS 2002 V2/9679 : 55929679B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses			
Waterborne paint. Professional use Industrial use			
	Uses advised against		
All other uses			
Product use	: Waterborne coating for interior use.		

: Waterborne coating for interior use.

1.3 Details of the supplier of the safety data sheet

MAPAERO SAS 10, Avenue de la Rijole CS30098 09103 PAMIERS Cedex France e-mail address of person : PSRA PAMIERS@akzonobel.com

responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Center		
: +33 (0)1 40 05 48 48		
: +33 (0)5 34 01 34 01		
+33 (0)5 61 60 23 30		
:		

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Date of issue/Date of revision	: 21-10-2022	Version : 1.02	
Date of previous issue	: 5-10-2022	1/15	AkzoNobel

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 FR2-55 SEMI-GLOSS BASE BLACK KANSAS 2002 V2/9679

		FR2-55 SEMI-GLOSS BASE BLACK KANSAS 2002 V2/9679		
SECTION 2: Hazards identification				
Hazard pictograms	:			
Signal word	:	Warning		
Hazard statements	:	May cause an allergic skin reaction.		
Precautionary statements				
Prevention	:	Wear protective gloves. Avoid breathing vapor.		
Response	:	Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.		
Storage	:	Not applicable.		
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.		
Hazardous ingredients	:	C(M)IT/MIT(3:1)		
Supplemental label elements	:	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.		
Special packaging requirem	nen	uts		
Containers to be fitted with child-resistant fastenings	:	Not applicable.		
Tactile warning of danger	:	Not applicable.		
2.3 Other hazards				
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.		
Other hazards which do not result in classification	:	None known.		

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Z-butoxyethanol C(M)IT/MIT(3:1)	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0 REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5	<1	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100)	[1] [2]
Date of issue/Date of revision	: 21-10-2022	Version	:1.02	
Date of previous issue : 5-10-2022		2/15	Akzo	Nobe

SECTION 3: Composition/information on ingredients		
	Aquatic Chronic 1, H410 (M=100) EUH071	
	See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact		Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	;	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact		Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion		Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	1	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed



SECTION 4: First aid measures

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains C(M)IT/MIT(3:1). May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

		-		
5.1 Extinguishing media				
Suitable extinguishing media	:	Use an extinguishing agent suitable	for the surrounding fire.	
Unsuitable extinguishing media	:	None known.		
5.2 Special hazards arising fr	on	n the substance or mixture		
Hazards from the substance or mixture	:	In a fire or if heated, a pressure incr	ease will occur and the contai	ner may burst.
Hazardous combustion products	:	Decomposition products may includ carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides	e the following materials:	
5.3 Advice for firefighters				
Special protective actions for fire-fighters	:	Promptly isolate the scene by remove there is a fire. No action shall be tall suitable training.		
Special protective equipment for fire-fighters	:	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.		
Date of issue/Date of revision		: 21-10-2022	Version : 1.02	
Date of previous issue		: 5-10-2022	4/15	AkzoNobel

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and materials for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of issue/Date of revision	: 21-10-2022	Version : 1.02	
Date of previous issue	: 5-10-2022	5/15	AkzoNobel

SECTION 7: Handling and storage

7.3 Specific end use(s)		
Recommendations	: Not available	
Industrial sector specific	: Not available	
solutions		

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name		Exposure limit values		
P-butoxyethanol Recommended monitoring procedures : If this product atmosphere of the ventilation protective equities the following:		Ministry of Labor (France, 3/2020). Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA: 10 ppm 8 hours. TWA: 49 mg/m ³ 8 hours. STEL: 246 mg/m ³ 15 minutes. STEL: 50 ppm 15 minutes.		
		contains ingredients with exposure limits, personal, workplace r biological monitoring may be required to determine the effectiveness on or other control measures and/or the necessity to use respiratory ipment. Reference should be made to monitoring standards, such as European Standard EN 689 (Workplace atmospheres - Guidance for nt of exposure by inhalation to chemical agents for comparison with		

the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
2-butoxyethanol	DNEL	Long term Oral	6.3 mg/kg	General	Systemic
		5	bw/day	population	5
	DNEL	Short term Oral	26.7 mg/	General	Systemic
			kg bw/day	population	,
	DNEL	Long term	59 mg/m³	General	Systemic
		Inhalation	Ũ	population	,
	DNEL	Long term Dermal	75 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Short term Dermal	89 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Short term Dermal	89 mg/kg	Workers	Systemic
			bw/day		
	DNEL	Long term	98 mg/m³	Workers	Systemic
		Inhalation			
	DNEL	Long term Dermal	125 mg/kg	Workers	Systemic
			bw/day		
	DNEL	Short term	147 mg/m ³	General	Local
		Inhalation		population	
	DNEL	Short term	246 mg/m ³	Workers	Local
		Inhalation			
	DNEL	Short term	426 mg/m ³	General	Systemic
		Inhalation		population	
e of issue/Date of revision	: 21-10-2022	1	Version	:1.02	•
e of previous issue	: 5-10-2022		6/15		AkzoNob

		DNEL	Short term Inhalation	1091 mg/ m³	Workers	Systemic
<u>PNECs</u>			Innalation			
No PNECs available.						
2 Exposure controls						
Appropriate engineering controls		od genera Itaminants	l ventilation should l s.	pe sufficient to	o control worker	exposure to airborr
Individual protection meas						
Hygiene measures	bet Ap Co cor	ore eating propriate t ntaminate ntaminateo		g the lavatory e used to rem uld not be allo ising. Ensure	and at the end o ove potentially o wed out of the v	of the working period contaminated clothir vorkplace. Wash
Eye/face protection	ass gas unl	essment i ses or dus	indicates this is nece ts. If contact is pose	essary to avoi sible, the follo	d exposure to li wing protection	be used when a risk quid splashes, mists should be worn, n: safety glasses wit
Skin protection						
Hand protection	be this che she diff sev est	worn at al is necess eck during ould be no erent for c veral subst imated.	I times when handlin sary. Considering th use that the gloves ted that the time to b lifferent glove manu tances, the protection	ng chemical p ne parameters are still retain preakthrough facturers. In on time of the	roducts if a risk specified by th ing their protect for any glove m the case of mixt gloves cannot b	aterial may be ures, consisting of be accurately
	pro rec Wł (br Re Glo	tection cla ommende ien only bi eakthroug commend	ged or frequently re ass of 6 (breakthroug d. Recommended rief contact is expec h time >30 minutes ed gloves: Nitrile, th d be replaced regula	gh time >480 gloves: Viton ted, a glove w according to I ickness ≥ 0.1.	minutes accord ® or Nitrile, thic ith protection cl EN374) is recon 2 mm.	ing to EN374) is kness ≥ 0.38 mm. ass of 2 or higher nmended.
		•	ance or effectivenes nage and poor main	•	may be reduce	d by physical/
	pro	duct is the	st check that the fina e most appropriate a ded in the user's risk	and takes into	account the par	
Body protection	bei	ng perforn	tective equipment fo ned and the risks inv ng this product.			
Other skin protection	sel	ected base	ootwear and any ad ed on the task being a specialist before h	performed a	nd the risks invo	ures should be blved and should be
Respiratory protection	ap res	propriate s	hazard and potenti tandard or certificat otection program to e.	ion. Respirate	ors must be use	ed according to a



SECTION 8: Exposure controls/personal protection

Environmental exposure	: Emissions from ventilation or work process equipment should be checked to
controls	ensure they comply with the requirements of environmental protection legislation.
	In some cases, fume scrubbers, filters or engineering modifications to the process
	equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

	hh
9.1 Information on basic physical	and chemical properties
<u>Appearance</u>	
Physical state	: Liquid.
Color	: Black.
Odor	: Characteristic.
Odor threshold	: Not available.
рН	: 8
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: Not available.
Flash point	: Closed cup: 105°C
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Upper/lower flammability or explosive limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Highest known value: (Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether).
Density	: 1.256 g/cm ³
Solubility(ies)	: Easily soluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): 4.62 cm ² /s Kinematic (40°C): 2.01 cm ² /s

SECTION 10: Stability and reactivity			
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	: The product is stable.		
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.		
10.4 Conditions to avoid	: No specific data.		
10.5 Incompatible materials	: No specific data.		
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.		

Date of issue/Date of revision	: 21-10-2022	Version : 1.02	
Date of previous issue	: 5-10-2022	8/15	AkzoNobel

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethanol	LC50 Inhalation Gas.	Mouse	700 ppm	7 hours
2	LC50 Inhalation Gas.	Rat	450 ppm	4 hours
	LC50 Inhalation Vapor	Mouse	3380 mg/m ³	7 hours
	LC50 Inhalation Vapor	Rat	2900 mg/m ³	7 hours
	LD50 Dermal	Guinea pig	230 uL/kg	-
	LD50 Dermal	Rabbit	220 mg/kg	-
	LD50 Intraperitoneal	Mouse	536 mg/kg	-
	LD50 Intraperitoneal	Rabbit	220 mg/kg	-
	LD50 Intraperitoneal	Rat	220 mg/kg	-
	LD50 Intravenous	Mouse	1130 mg/kg	-
	LD50 Intravenous	Rabbit	252 mg/kg	-
	LD50 Intravenous	Rat	307 mg/kg	-
	LD50 Oral	Guinea pig	1200 mg/kg	-
	LD50 Oral	Mouse	1230 mg/kg	-
	LD50 Oral	Mouse	1167 mg/kg	-
	LD50 Oral	Rabbit	300 mg/kg	-
	LD50 Oral	Rabbit	320 mg/kg	-
	LD50 Oral	Rat	917 mg/kg	-
	LD50 Oral	Rat	250 mg/kg	-
	LD50 Route of exposure	Mouse	1050 mg/kg	-
	unreported			
	LD50 Route of exposure	Rat	917 mg/kg	-
	unreported			

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
				mg	
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
Conclusion/Summary	: Not available.				
Sensitization					
Conclusion/Summary	: Not available.				
<u>Mutagenicity</u>					
Conclusion/Summary	: Not available.				
Carcinogenicity					
Conclusion/Summary	: Not available.				
Reproductive toxicity					
Conclusion/Summary	: Not available.				
<u>Teratogenicity</u>					
Conclusion/Summary	: Not available.				
Specific target organ toxicit	<u>y (single exposure)</u>				
Not available.					

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

		FR2-55 SEMI-GLOSS BASE BLACK KANSAS 2002 V2/9679
SECTION 11: Toxico	lo	gical information
Information on the likely routes of exposure	:	Not available.
Potential acute health effects	<u>s</u>	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the phy	<u>/sic</u>	cal, chemical and toxicological characteristics
Eye contact	:	No specific data.
Inhalation		No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Delayed and immediate effect	<u>cts</u>	and also chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
<u>Long term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health eff	ect	<u>s</u>
Not available.		
Conclusion/Summary	:	Not available.
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

Product/ingredient name	Result	Species	Exposure
₽-butoxyethanol	Acute EC50 >1000 mg/l Fresh water Acute LC50 800000 μg/l Marine water Acute LC50 1490000 μg/l Fresh water Acute LC50 1250000 μg/l Marine water	Daphnia - Daphnia magna Crustaceans - Crangon crango Fish - Lepomis macrochirus Fish - Menidia beryllina	48 hours n 48 hours 96 hours 96 hours
Conclusion/Summary	: Not available.		
Date of issue/Date of revision	: 21-10-2022	Version : 1.02	
Date of previous issue	: 5-10-2022	10/15	kzoNobel

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 FR2-55 SEMI-GLOSS BASE BLACK KANSAS 2002 V2/9679

SECTION 12: Ecological information

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-butoxyethanol	0.81	-	low

12.4 Mobility in soil

Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
Disposal considerations	: Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation	
EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11	
Packaging		
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	
Disposal considerations	 Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions. 	

Date of issue/Date of revision	: 21-10-2022	Version : 1.02	
Date of previous issue	: 5-10-2022	11/15	AkzoNobel

SECTION 13: Disposal considerations

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk: Not applicable.according to IMOinstruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixtu	ıre
EU Regulation (EC) No. 1907/2006 (REACH)	

Annex XIV - List of substances subject to authorization

None of the components are listed. Substances of very high concern None of the components are listed. Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles **Other EU regulations** VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information. VOC for Ready-for-Use : Not applicable. Mixture

Annex XIV



	1112 00 CEMI CECCO B/ CE	BLACK KANSAS 2002 V2/9079
SECTION 15: Regulat	tory information	
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed	
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed	
Ozone depleting substance	<u>es (1005/2009/EU)</u>	
Not listed.		
Prior Informed Consent (PI Not listed.	<u>C) (649/2012/EU)</u>	
<u>Seveso Directive</u>		
This product is not controlled	I under the Seveso Directiv	2 .
National regulations		
Industrial use	own assessment of wor	ed in this safety data sheet does not constitute the user's kplace risks, as required by other health and safety ns of the national health and safety at work regulations apply ct at work.
Social Security Code, Articles L 461-1 to L 461-7	: 2 -butoxyethanol	RG 84
Reinforced medical surveillance	: Decree n ° 2012-135 of occupational medicine:	January 30, 2012 relating to the organization of not applicable
International regulations		
Chemical Weapon Convention	on List Schedules I, II & I	I Chemicals
Not listed.		
Montreal Protocol Not listed.		
Stockholm Convention on P Not listed.	Persistent Organic Polluta	<u>nts</u>
Rotterdam Convention on P Not listed.	rior Informed Consent (P	<u>C)</u>
UNECE Aarhus Protocol on Not listed.	POPs and Heavy Metals	
<u>Inventory list</u> Europe	: Not determined.	
15.2 Chemical Safety Assessment	: No Chemical Safety As	sessment has been carried out.
SECTION 16: Other in	nformation	

Indicates information that has changed from previously issued version.



Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method

Full text of abbreviated H statements

F 301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Kcute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1A	SKIN SENSITIZATION - Category 1A

Date of printing	: 31 October 2022
Date of issue/ Date of revision	: 21 October 2022
Date of previous issue	: 5 October 2022
Version	: 1.02
Unique ID	:

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality

Date of issue/Date of revision	: 21-10-2022	Version : 1.02	
Date of previous issue	: 5-10-2022	14/15	AkzoNobel

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 FR2-55 SEMI-GLOSS BASE BLACK KANSAS 2002 V2/9679

SECTION 16: Other information

or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

