

# **SAFETY DATA SHEET**

FR2-55 SEMI-GLOSS TUK SMOKE WHITE AIC 12.5

# **Section 1. Identification**

GHS product identifier SDS code

: FR2-55 SEMI-GLOSS TUK SMOKE WHITE AIC 12.5 : 55981205K

. 0000120

#### Recommended use of the chemical and restrictions on use

	Identified uses
Paint. Professional use	Industrial use
	Restrictions on use
All other uses	
Product use	: Waterborne coating for interior use.
Supplier's details	
MAPAERO SA	S

10, Avenue de la Rijol 09103 PAMIERS Ced France		
e-mail address of person responsible for this SDS	:	PSRA_PAMIERS@akzonobel.com
Emergency telephone number	:	+33 (0)5 34 01 34 01 +33 (0)5 61 60 23 30

# Section 2. Hazard identification

Classification of the	: FLAMMABLE LIQUIDS - Category 3
substance or mixture	SKIN SENSITIZATION - Category 1

**GHS label elements** 

Hazard pictograms



Signal word	: Warning
Hazard statements	: Flammable liquid and vapor. May cause an allergic skin reaction.
Precautionary statements	
Prevention	: Wear protective gloves. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapor.
Response	: Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	: Store in a well-ventilated place. Keep cool.

## Section 2. Hazard identification

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not : None known. result in classification

## Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	%	CAS number
1,3,5-Triazine-2,4,6(1H,3H,5H)-trione, 1,3,5-tris(6-isocyanatohexyl)-, reaction products with polyethylene glycol monomethyl ether	≤10	129217-88-5
2-ethoxy-1-methylethyl acetate	≤10	54839-24-6
Polyisocyanate, aliphatic	≤3	-
C(M)IT/MIT(3:1)	≤0.001	55965-84-9

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

: No known significant effects or critical hazards.
: May cause an allergic skin reaction.
: No known significant effects or critical hazards.

Date of issue/Date of revision	: 6-10-2022	Version : 1.01	
Date of previous issue	: 30-9-2022	2/10	AkzoNobel

## Section 4. First aid measures

<u>Over-exposure signs/symptoms</u>			
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: Adverse symptoms may include the following: irritation redness		
Ingestion	: No specific data.		

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### See toxicological information (Section 11)

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

## Section 6. Accidental release measures

: 30-9-2022

Date of previous issue

Personal precautions, protective equipment and emergency procedures : No action shall be taken involving any personal risk or without suitable training. For non-emergency Evacuate surrounding areas. Keep unnecessary and unprotected personnel from personnel entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. **For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". Date of issue/Date of revision : 6-10-2022 Version : 1.01 **AkzoNobel** 

3/10

## Section 6. Accidental release measures

Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways,
-	drains and sewers. Inform the relevant authorities if the product has caused
	environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-

combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits None.



# Section 8. Exposure controls/personal protection

Appropriate engineering controls	e only with adequate ventilation. Use process enclosures, local exhant ntilation or other engineering controls to keep worker exposure to air ntaminants below any recommended or statutory limits. The engineer o need to keep gas, vapor or dust concentrations below any lower ex- its. Use explosion-proof ventilation equipment.	borne ering controls
Environmental exposure controls	nissions from ventilation or work process equipment should be check by comply with the requirements of environmental protection legislation ses, fume scrubbers, filters or engineering modifications to the proce uipment will be necessary to reduce emissions to acceptable levels.	on. In some
Individual protection measur		
Hygiene measures	ash hands, forearms and face thoroughly after handling chemical pro- ting, smoking and using the lavatory and at the end of the working per- propriate techniques should be used to remove potentially contamina ntaminated work clothing should not be allowed out of the workplace ntaminated clothing before reusing. Ensure that eyewash stations ar powers are close to the workstation location.	eriod. ated clothing. e. Wash
Eye/face protection	fety eyewear complying with an approved standard should be used v sessment indicates this is necessary to avoid exposure to liquid splay ses or dusts. If contact is possible, the following protection should be less the assessment indicates a higher degree of protection: safety e-shields.	shes, mists, e worn,
Skin protection		
Hand protection	emical-resistant, impervious gloves complying with an approved star worn at all times when handling chemical products if a risk assessm is is necessary. Considering the parameters specified by the glove m eck during use that the gloves are still retaining their protective proper- build be noted that the time to breakthrough for any glove material ma ferent for different glove manufacturers. In the case of mixtures, con- veral substances, the protection time of the gloves cannot be accura- timated.	ent indicates nanufacturer, erties. It ay be isisting of
Body protection	rsonal protective equipment for the body should be selected based or ng performed and the risks involved and should be approved by a sp fore handling this product. When there is a risk of ignition from static ar anti-static protective clothing. For the greatest protection from static charges, clothing should include anti-static overalls, boots and glove	pecialist c electricity, atic
Other skin protection	propriate footwear and any additional skin protection measures shou ected based on the task being performed and the risks involved and proved by a specialist before handling this product.	
Respiratory protection	sed on the hazard and potential for exposure, select a respirator that propriate standard or certification. Respirators must be used accord piratory protection program to ensure proper fitting, training, and oth pects of use.	ing to a

# Section 9. Physical and chemical properties and safety characteristics

: Liquid.
: White.
: Characteristic.
: Not available.

Date of issue/Date of revision	: 6-10-2022	Version : 1.01	
Date of previous issue	: 30-9-2022	5/10	AkzoNobel

# Section 9. Physical and chemical properties and safety characteristics

Evaporation rate: Not available.Flammability: Not available.Lower and upper explosion limit/flammability limit: Greatest known range: Lower: 1% Upper: 9.8% (2-ethoxy-1-methylethyl acetate)Vapor pressure: Not available.Relative vapor density: Highest known value: >1 (Air = 1) (Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether). Weighted average: 1.17 (Air = 1)Density: 1.344 g/cm³Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/ water: Not available.Auto-ignition temperature vater: Not available.Viscosity: Kinematic (room temperature): 0.67 cm²/s Kinematic (40°C): 1.01 cm²/sExplosive properties Oxidizing properties: Not available.			
Flammability: Not available.Lower and upper explosion limit/flammability limit: Greatest known range: Lower: 1% Upper: 9.8% (2-ethoxy-1-methylethyl acetate)Vapor pressure: Not available.Relative vapor density: Highest known value: >1 (Air = 1) (Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether). Weighted average: 1.17 (Air = 1)Density: 1.344 g/cm³Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/ water: Not available.Auto-ignition temperature Decomposition temperature: Not available.Viscosity: Kinematic (room temperature): 0.67 cm²/s Kinematic (40°C): 1.01 cm²/sExplosive properties Oxidizing properties: Not available.	Flash point	:	Closed cup: 59°C
Lower and upper explosion limit/flammability limit: Greatest known range: Lower: 1% Upper: 9.8% (2-ethoxy-1-methylethyl acetate)Vapor pressure: Not available.Relative vapor density: Highest known value: >1 (Air = 1) (Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether). Weighted average: 1.17 (Air = 1)Density: 1.344 g/cm³Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/ water: Not available.Auto-ignition temperature: Not available.Viscosity: Kinematic (room temperature): 0.67 cm²/s Kinematic (40°C): 1.01 cm²/sExplosive properties: Not available.Oxidizing properties: Not available.	Evaporation rate	:	Not available.
limit/flammability limitNot available.Vapor pressure: Not available.Relative vapor density: Highest known value: >1 (Air = 1) (Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether). Weighted average: 1.17 (Air = 1)Density: 1.344 g/cm³Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/ water: Not available.Auto-ignition temperature: Not available.Decomposition temperature: Not available.Viscosity: Kinematic (room temperature): 0.67 cm²/s Kinematic (40°C): 1.01 cm²/sExplosive properties: Not available.Oxidizing properties: Not available.	Flammability	:	Not available.
Relative vapor density: Highest known value: >1 (Air = 1) (Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether). Weighted average: 1.17 (Air = 1)Density: 1.344 g/cm³Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/ water: Not available.Auto-ignition temperature: Not available.Decomposition temperature: Not available.Viscosity: Kinematic (room temperature): 0.67 cm²/s Kinematic (40°C): 1.01 cm²/sExplosive properties: Not available.Oxidizing properties: Not available.	Lower and upper explosion limit/flammability limit	:	Greatest known range: Lower: 1% Upper: 9.8% (2-ethoxy-1-methylethyl acetate)
monobutyl ether). Weighted average: 1.17 (Air = 1)Density: 1.344 g/cm³Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/ water: Not available.Auto-ignition temperature Decomposition temperature Viscosity: Not available.Viscosity: Kinematic (room temperature): 0.67 cm²/s 	Vapor pressure	:	Not available.
Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/ water: Not available.Auto-ignition temperature: Not available.Decomposition temperature: Not available.Viscosity: Kinematic (room temperature): 0.67 cm²/s Kinematic (40°C): 1.01 cm²/sExplosive properties: Not available.Oxidizing properties: Not available.	Relative vapor density	:	
Partition coefficient: n-octanol/ water: Not available.Auto-ignition temperature: Not available.Decomposition temperature: Not available.Viscosity: Kinematic (room temperature): 0.67 cm²/s Kinematic (40°C): 1.01 cm²/sExplosive properties: Not available.Oxidizing properties: Not available.	Density	:	1.344 g/cm <sup>3</sup>
waterAuto-ignition temperature: Not available.Decomposition temperature: Not available.Viscosity: Kinematic (room temperature): 0.67 cm²/s Kinematic (40°C): 1.01 cm²/sExplosive properties: Not available.Oxidizing properties: Not available.	Solubility(ies)	:	Insoluble in the following materials: cold water.
Decomposition temperature: Not available.Viscosity: Kinematic (room temperature): 0.67 cm²/s Kinematic (40°C): 1.01 cm²/sExplosive properties: Not available.Oxidizing properties: Not available.	Partition coefficient: n-octanol/ water	:	Not available.
Viscosity: Kinematic (room temperature): 0.67 cm²/s Kinematic (40°C): 1.01 cm²/sExplosive properties: Not available.Oxidizing properties: Not available.	Auto-ignition temperature	:	Not available.
Kinematic (40°C): 1.01 cm²/s         Explosive properties       : Not available.         Oxidizing properties       : Not available.	Decomposition temperature	:	Not available.
<b>Oxidizing properties</b> : Not available.	Viscosity	:	
	Explosive properties	:	Not available.
Solubility in water : Not available.	Oxidizing properties	:	Not available.
	Solubility in water	:	Not available.

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Not available.

#### Irritation/Corrosion

Not available.

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

Date of issue/Date of revision	: 6-10-2022	Version : 1.01	
Date of previous issue	: 30-9-2022	6/10	AkzoNobel

# Section 11. Toxicological information

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
2-ethoxy-1-methylethyl acetate	Category 3	-	Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely routes of exposure	: Not available.
Potential acute health effect	ts
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Eye contact Inhalation	nysical, chemical and toxicological characteristics : No specific data. : No specific data.
•	•
Skin contact	irritation redness
Ingestion	: No specific data.
	ects and also chronic effects from short and long term e
<u>Short term exposure</u>	

#### exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.

Date of issue/Date of revision	: 6-10-2022	Version : 1.01	
Date of previous issue	: 30-9-2022	7/10	AkzoNobel

# Section 11. Toxicological information

**Reproductive toxicity** 

: No known significant effects or critical hazards.

# Section 12. Ecological information

#### **Toxicity**

Not available.

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2-ethoxy-1-methylethyl acetate	0.76	-	low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

1				
	UN	IMDG	ΙΑΙ	A
UN number	UN1263	UN1263	UN1263	
UN proper shipping name	PAINT	PAINT	PAINT	
Transport hazard class(es)	3	3	3	
Date of issue/Date of revi Date of previous issue	ision : 6-10-2022 : 30-9-2022	Version 8/10	. : 1.01 A	kzoNobel

# Section 14. Transport information

Packing group			
Environmental hazards	No.	No.	No.
hazards			

#### Additional information

#### IMDG : <u>Emergency schedules</u> F-E, \_S-E\_

# **Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

# Transport in bulk according : Not available. to IMO instruments

## Section 15. Regulatory information

Inventory list	
Australia	: Not determined.
Canada	: At least one component is not listed.
China	: Not determined.
Europe	: Not determined.
Japan	: Japan inventory (ENCS): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: Not determined.
Viet Nam	: Not determined.

## Section 16. Other information

<u>History</u>	
Date of printing	: 31 October 2022
Date of issue/ Date of revision	: 6 October 2022
Date of previous issue	: 30 September 2022
Version	: 1.01
Unique ID	:
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

#### Procedure used to derive the classification

Date of issue/Date of revision	: 6-10-2022	Version : 1.01	
Date of previous issue	: 30-9-2022	9/10	AkzoNobel

# Section 16. Other information

#### Classification

FLAMMABLE LIQUIDS - Category 3 SKIN SENSITIZATION - Category 1 Justification

On basis of test data Calculation method

#### References

#### : Not available.

#### ✓ Indicates information that has changed from previously issued version.

#### Notice to reader

#### FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

