

# SAFETY DATA SHEET

FR2-55 SEMI-GLOSS TUK WHITE 7362 AIC 12.16

### **Section 1. Identification**

GHS product identifier : FR2-55 SEMI-GLOSS TUK WHITE 7362 AIC 12.16

**SDS code** : 55981216K

### Recommended use of the chemical and restrictions on use

Identified uses

Paint. Professional use Industrial use

Restrictions on use

All other uses

**Product use** : Waterborne coating for interior use.

Supplier's details

MAPAERO SAS

10, Avenue de la Rijole CS30098

09103 PAMIERS Cedex

France

e-mail address of person

responsible for this SDS

: PSRA\_PAMIERS@akzonobel.com

**Emergency telephone** 

number

: +33 (0)5 34 01 34 01 +33 (0)5 61 60 23 30

### Section 2. Hazard identification

Classification of the substance or mixture

: FLAMMABLE LIQUIDS - Category 3 SKIN SENSITIZATION - Category 1

**GHS label elements** 

Hazard pictograms





Signal word : Warning

**Hazard statements** : Flammable liquid and vapor.

May cause an allergic skin reaction.

**Precautionary statements** 

**Prevention**: Wear protective gloves. Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. Avoid breathing vapor.

**Response** : Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with

plenty of water. If skin irritation or rash occurs: Get medical advice or attention.

**Storage** : Store in a well-ventilated place. Keep cool.

Date of issue/Date of revision : 12-10-2022 Version : 1

Date of previous issue : No previous validation 1/10 AkzoNobel

### Section 2. Hazard identification

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not : None known.

result in classification

### Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
1,3,5-Triazine-2,4,6(1H,3H,5H)-trione, 1,3,5-tris(6-isocyanatohexyl)-, reaction products with polyethylene glycol monomethyl ether	≤10	129217-88-5
2-ethoxy-1-methylethyl acetate	≤10	54839-24-6
Polyisocyanate, aliphatic	≤3	-
C(M)IT/MIT(3:1)	≤0.001	55965-84-9

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

### Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards.

Skin contact : May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Date of issue/Date of revision : 12-10-2022 Version: 1

**AkzoNobel** Date of previous issue : No previous validation 2/10

### Section 4. First aid measures

### Over-exposure signs/symptoms

Eye contact : No specific data. Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

> irritation redness

Ingestion : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear

gloves.

### See toxicological information (Section 11)

# **Section 5. Fire-fighting measures**

### **Extinguishing media**

Suitable extinguishing

media

: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

Specific hazards arising

from the chemical

: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with

the risk of a subsequent explosion.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides

Special protective actions

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk.

Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources.

No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any

information in Section 8 on suitable and unsuitable materials. See also the

information in "For non-emergency personnel".

: 12-10-2022 Date of issue/Date of revision Version : 1

**AkzoNobel** Date of previous issue : No previous validation 3/10

### Section 6. Accidental release measures

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

#### Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

#### Precautions for safe handling

#### Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and wellventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### Control parameters

Occupational exposure limits

None.

: 12-10-2022 Date of issue/Date of revision Version : 1 **AkzoNobel** Date of previous issue : No previous validation 4/10

## Section 8. Exposure controls/personal protection

# Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

**Hygiene measures**: Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing.

Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists,

gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with

side-shields.

### **Skin protection**

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should

be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

estimated.

**Body protection**: Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static

discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

**Respiratory protection**: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a

respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

# Section 9. Physical and chemical properties and safety characteristics

#### **Appearance**

Physical state : Liquid.

Color : White.

Odor : Characteristic.
Odor threshold : Not available.
pH : Not available.
Melting point/freezing point : Not available.
Initial boiling point and : Not available.

boiling range

Date of issue/Date of revision : 12-10-2022 Version : 1

Date of previous issue : No previous validation 5/10 AkzoNobel

### Section 9. Physical and chemical properties and safety characteristics

Flash point : Closed cup: 59°C **Evaporation rate** : Not available. **Flammability** : Not available.

Lower and upper explosion limit/flammability limit

: Greatest known range: Lower: 1% Upper: 9.8% (2-ethoxy-1-methylethyl acetate)

Vapor pressure : Not available.

: Highest known value: >1 (Air = 1) (Oxirane, 2-methyl-, polymer with oxirane, Relative vapor density

monobutyl ether). Weighted average: 1.17 (Air = 1)

: 1.345 g/cm<sup>3</sup> Density

Solubility(ies) : Insoluble in the following materials: cold water.

Partition coefficient: n-octanol/ : Not available.

water

**Auto-ignition temperature** : Not available. **Decomposition temperature** : Not available.

**Viscosity** : Kinematic (room temperature): 0.67 cm<sup>2</sup>/s

Kinematic (40°C): 1.01 cm<sup>2</sup>/s

**Explosive properties** : Not available. Oxidizing properties : Not available. Solubility in water : Not available.

### Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials : Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

### **Section 11. Toxicological information**

### Information on toxicological effects

### **Acute toxicity**

Not available.

### Irritation/Corrosion

Not available.

#### **Sensitization**

Not available.

### **Mutagenicity**

Not available.

Date of issue/Date of revision : 12-10-2022 Version

**AkzoNobel** Date of previous issue : No previous validation 6/10

# **Section 11. Toxicological information**

### **Carcinogenicity**

Not available.

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
2-ethoxy-1-methylethyl acetate	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Not available.

### **Aspiration hazard**

Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Short term exposure**

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

### Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.Mutagenicity : No known significant effects or critical hazards.

Date of issue/Date of revision : 12-10-2022 Version : 1

Date of previous issue : No previous validation 7/10 AkzoNobel

### **Section 11. Toxicological information**

Reproductive toxicity

: No known significant effects or critical hazards.

### **Section 12. Ecological information**

#### **Toxicity**

Not available.

### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2-ethoxy-1-methylethyl acetate	0.76	-	low

### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

### Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	UN	IMDG	IATA
UN number	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	3	3	3

Date of issue/Date of revision

Date of previous issue

: No previous validation

: 12-10-2022

Version : 1

8/10

AkzoNobel

### **Section 14. Transport information**

Packing group	III	III	III
Environmental hazards	No.	No.	No.

**Additional information** 

**IMDG** : Emergency schedules F-E, \_S-E\_

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

### Section 15. Regulatory information

Inventory list

**Australia** : Not determined.

Canada : At least one component is not listed.

China : Not determined. **Europe** : Not determined.

: Japan inventory (ENCS): Not determined. Japan

Japan inventory (ISHL): Not determined.

**New Zealand** : Not determined. **Philippines** : Not determined. Republic of Korea : Not determined. **Taiwan** : Not determined. **Thailand** : Not determined. **Turkey** : Not determined. **United States** : Not determined. **Viet Nam** : Not determined.

### Section 16. Other information

**History** 

: 31 October 2022 Date of printing Date of issue/ Date of : 12 October 2022

revision

Date of previous issue : No previous validation

Version : 1 **Unique ID** 

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group **UN = United Nations** 

Procedure used to derive the classification

Date of issue/Date of revision : 12-10-2022 Version : 1

**AkzoNobel** Date of previous issue : No previous validation 9/10

### Section 16. Other information

Classification	Justification
<b>5</b> ,	On basis of test data Calculation method

References Not available.

▼ Indicates information that has changed from previously issued version.

#### Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision : 12-10-2022 Version : 1 10/10

Date of previous issue : No previous validation **AkzoNobel**