

# SAFETY DATA SHEET

FR2-55-SG-TINT SEMI-GLOSS BASE YELLOW SF3123

## Section 1. Identification

GHS product identifier : FR2-55-SG-TINT SEMI-GLOSS BASE YELLOW SF3123

**SDS code** : 55993123B

### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** 

Waterborne paint. Professional use Industrial use

Uses advised against

All other uses

**Product use** : Waterborne coating for interior use.

Supplier's details

MAPAERO SAS

10, Avenue de la Rijole CS30098

09103 PAMIERS Cedex

France

Emergency telephone number (with hours of

operation)

: +33 (0)5 34 01 34 01 +33 (0)5 61 60 23 30

# Section 2. Hazards identification

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available

for employees and other users of this product.

Classification of the substance or mixture

: Not classified.

**GHS label elements** 

Signal word : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

**Precautionary statements** 

**Prevention**: Do not get in eyes, on skin, or on clothing.

Response : Not applicable.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Hazards not otherwise

classified

: None known.

Date of issue/Date of revision: 10/19/2022Version: 1.02Date of previous issue: 10/6/20221/10AkzoNobel

## Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
silicon dioxide	≤3	7631-86-9
Talc , not containing asbestiform fibres	≤3	14807-96-6
Chlorite-group minerals	≤3	1318-59-8
Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether	≤3	9038-95-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

**Inhalation**: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get

medical attention if symptoms occur.

**Skin contact**: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

**Ingestion**: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position

comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

#### Most important symptoms/effects, acute and delayed

## Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

## Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Date of issue/Date of revision : 10/19/2022 Version : 1.02

Date of previous issue : 10/6/2022 2/10 AkzoNobel

## Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Date of issue/Date of revision : 10/19/2022 Version : 1.02

Date of previous issue : 10/6/2022 3/10 AkzoNobel

## Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
silicon dioxide	None.
Talc , not containing asbestiform fibres	None.
Chlorite-group minerals	None.
Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether	None.

### Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

### Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Date of issue/Date of revision : 10/19/2022 Version: 1.02

**AkzoNobel** Date of previous issue : 10/6/2022 4/10

## Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid. Color : Yellow.

Odor : Characteristic. **Odor threshold** : Not available.

На : 8

: Not available. **Melting point Boiling point** : Not available.

Flash point : Closed cup: 105°C (221°F)

: Not available. **Evaporation rate** Flammability (solid, gas) : Not available. Upper/lower flammability or : Not available.

explosive limits

: Not available. Vapor pressure

Vapor density : Highest known value: (Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether).

: 1.321 g/cm<sup>3</sup> **Density** 

Solubility(ies) : Easily soluble in the following materials: cold water.

Partition coefficient: n-

octanol/water

: Not available.

# Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

## **Section 11. Toxicological information**

## Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether	LC50 Inhalation Vapor	Guinea pig	293 mg/m³	4 hours
,	LC50 Inhalation Vapor	Mouse	174 mg/m <sup>3</sup>	4 hours
	LC50 Inhalation Vapor	Rat	4770 mg/m <sup>3</sup>	4 hours
	LC50 Inhalation Vapor	Rat	4670 mg/m <sup>3</sup>	4 hours
	LC50 Inhalation Vapor	Rat	147 mg/m <sup>3</sup>	4 hours
	LC50 Inhalation Vapor	Rat	330 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	>20 g/kg	-
	LD50 Dermal	Rabbit	20 mL/kg	-
	LD50 Dermal	Rabbit	14100 uL/kg	-
	LD50 Intraperitoneal	Rat	2600 mg/kg	-

Date of issue/Date of revision : 10/19/2022 Version: 1.02

**AkzoNobel** Date of previous issue : 10/6/2022 5/10

# **Section 11. Toxicological information**

LD50 Oral	Mouse	49 g/kg	-
LD50 Oral	Mouse	7460 mg/kg	-
LD50 Oral	Rabbit	16 g/kg	-
LD50 Oral	Rabbit	1770 mg/kg	-
LD50 Oral	Rat	5 g/kg	-
LD50 Oral	Rat	45 g/kg	-
LD50 Oral	Rat	4 mL/kg	-
LD50 Oral	Rat	6130 mg/kg	-
LD50 Oral	Rat	5370 mg/kg	-
LD50 Oral	Rat	9610 mg/kg	-
LD50 Oral	Rat	12300 uL/kg	-
LD50 Oral	Rat	9170 uL/kg	-
LD50 Oral	Rat	38400 uL/kg	-
LD50 Oral	Rat	8530 uL/kg	-
LD50 Oral	Rat	18300 uL/kg	-
LD50 Oral	Rat	20600 uL/kg	_

### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
silicon dioxide	Eyes - Mild irritant	Rabbit	-	24 hours 25	-
				mg	
Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether	Eyes - Severe irritant	Rabbit	-	50 mg	-
,	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

### **Sensitization**

Not available.

### **Mutagenicity**

Not available.

### **Carcinogenicity**

Not available.

### **Classification**

Product/ingredient name	OSHA	IARC	NTP
silicon dioxide Talc , not containing asbestiform fibres	-	3	-

## **Reproductive toxicity**

Not available.

### **Teratogenicity**

Not available.

## Specific target organ toxicity (single exposure)

Not available.

## Specific target organ toxicity (repeated exposure)

Not available.

Date of issue/Date of revision: 10/19/2022Version: 1.02Date of previous issue: 10/6/20226/10AkzoNobel

## **Section 11. Toxicological information**

### **Aspiration hazard**

Not available.

Information on the likely

: Not available.

routes of exposure

Potential acute health effects

Eye contact
 Inhalation
 Skin contact
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate :

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

## Section 12. Ecological information

### **Toxicity**

Not available.

### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Not available.

#### **Mobility in soil**

Date of issue/Date of revision: 10/19/2022Version: 1.02

Date of previous issue : 10/6/2022 7/10 AkzoNobel

FR2-55-SG-TINT SEMI-GLOSS BASE YELLOW SF3123

## Section 12. Ecological information

Soil/water partition coefficient (Koc)

Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

#### Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **Section 14. Transport information**

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	DOT Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

## Section 15. Regulatory information

U.S. Federal regulations

: United States inventory (TSCA 8b):

Not determined.

### State regulations

Date of issue/Date of revision : 10/19/2022 Version: 1.02

**AkzoNobel** Date of previous issue : 10/6/2022 8/10

FR2-55-SG-TINT SEMI-GLOSS BASE YELLOW SF3123

## **Section 15. Regulatory information**

Massachusetts : The following components are listed: TALC; SOAPSTONE; DIATOMACEOUS EARTH;

**AMORPHOUS SILICA** 

**New York** : None of the components are listed.

New Jersey : The following components are listed: SOAPSTONE

Pennsylvania : The following components are listed: TALC; SOAPSTONE DUST; SILICA

California Prop. 65

⚠ WARNING: Cancer - www.P65Warnings.ca.gov.

Ingredient name		Maximum acceptable dosage level
rystalline silica, respirable powder	-	-

### **Inventory list**

**Canada** : At least one component is not listed.

## Section 16. Other information

## Procedure used to derive the classification

Classification	Justification
Not classified.	

#### **History**

Date of printing : 26 October 2022

Date of issue/ Date of : 19 October 2022

revision

Date of previous issue : 6 October 2022

Version : 1.02 Unique ID :

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group

UN = United Nations

### Indicates information that has changed from previously issued version.

#### Notice to reader

### FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in

Date of issue/Date of revision :10/19/2022 Version :1.02

Date of previous issue : 10/6/2022 9/10 AkzoNobel

FR2-55-SG-TINT SEMI-GLOSS BASE YELLOW SF3123

## **Section 16. Other information**

this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision: 10/19/2022Version: 1.02

Date of previous issue : 10/6/2022 10/10 AkzoNobel