

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET

FR6-55 SEMI-GLOSS BASE GREY S-1000-N/7541

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name SDS code : FR6-55 SEMI-GLOSS BASE GREY S-1000-N/7541 : 66927541B

1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses	
Waterborne paint. Professional use Industrial use		
Uses advised against		
All other uses		

Product use

: Waterborne coating for interior use.

1.3 Details of the supplier of the safety data sheet

MAPAERO SAS 10, Avenue de la Rijole CS30098 09103 PAMIERS Cedex France e-mail address of person : PSRA PAMIERS@akzonobel.com

responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Center		
Telephone number	: +43 1 406 43 43	
<u>Supplier</u>		
Telephone number	: +33 (0)5 34 01 34 01 +33 (0)5 61 60 23 30	
Hours of operation	:	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Date of issue/Date of revision	: 20-10-2022	Version : 1.02	
Date of previous issue	: 3-10-2022	1/14	AkzoNobel

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 FR6-55 SEMI-GLOSS BASE GREY S-1000-N/7541

FR6-55 SEMI-GLOSS BASE GREY S-1000-N/7541 SECTION 2: Hazards identification			
Signal word	Warning		
Hazard statements	May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.		
Precautionary statements			
Prevention	Wear protective gloves. Avoid release to the environment. Avoid breathing vap	oor.	
Response	Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash was plenty of water. If skin irritation or rash occurs: Get medical advice or attention.		
Storage	Not applicable.		
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.	l	
Hazardous ingredients	C(M)IT/MIT(3:1)		
Supplemental label elements	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.		
Special packaging requirem	<u>S</u>		
Containers to be fitted with child-resistant fastenings	Not applicable.		
Tactile warning of danger	Not applicable.		
2.3 Other hazards			
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture does not contain any substances that are assessed to be a PBT or vPvB.	а	
Other hazards which do	None known.		

not result in classification

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
propylidynetrimethanol	EC: 201-074-9 CAS: 77-99-6	≤0.3	Repr. 2, H361	[1]
C(M)IT/MIT(3:1)	REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5	<0.025	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	[1]
Date of issue/Date of revision	: 20-10-2022	Version		12
Date of previous issue	: 3-10-2022	2/14	Akzo	Nobe

SECTION 3: Composition/information on ingredients		
	EUH071	
	See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Туре</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed



SECTION 4: First aid measures

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains C(M)IT/MIT(3:1). May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

	<u> </u>		
5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing	g agent suitable for the surrounding t	fire.
Unsuitable extinguishing media	: None known.		
5.2 Special hazards arising f	from the substance or m	nixture	
Hazards from the substance or mixture	This material is harm contaminated with th	a pressure increase will occur and t nful to aquatic life with long lasting e is material must be contained and p aterway, sewer or drain.	ffects. Fire water
Hazardous combustion products	: Decomposition producarbon dioxide carbon monoxide nitrogen oxides halogenated compou metal oxide/oxides	ucts may include the following mater unds	ials:
5.3 Advice for firefighters			
Special protective actions for fire-fighters		scene by removing all persons from tion shall be taken involving any per	
Date of issue/Date of revision	: 20-10-2022	Version : 1.02	
Date of previous issue	: 3-10-2022	4/14	AkzoNobel

SECTION 5: Firefight	ing measures
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and materials for	r c	ontainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 FR6-55 SEMI-GLOSS BASE GREY S-1000-N/7541

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : N Industrial sector specific : N

: Not available.

Industrial sector specific : Not available. solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name		Exposure limit values	
procedures	atmosphere or to of the ventilation protective equip the following: E the assessment limit values and atmospheres - (of exposure to co (Workplace atm for the measure	ontains ingredients with exposure limits, personal, workplace biological monitoring may be required to determine the effectiveness on or other control measures and/or the necessity to use respiratory oment. Reference should be made to monitoring standards, such as suropean Standard EN 689 (Workplace atmospheres - Guidance for t of exposure by inhalation to chemical agents for comparison with measurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 nospheres - General requirements for the performance of procedure ement of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be	

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
propylidynetrimethanol	DNEL	Long term Oral	1.68 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.68 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2.79 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	5.03 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	19.54 mg/ m³	Workers	Systemic
	DNEL	Short term Oral	50 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	83.3 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Dermal	138.8 mg/ kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	925 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	3037.3 mg/ m³	Workers	Systemic

Date of issue/Date of revision	: 20-10-2022	Version : 1.02	
Date of previous issue	: 3-10-2022	6/14	AkzoNobe

SECTION 8: Exposure controls/personal protection

PNECs

No PNECs available.

Date of previous issue

8.2 Exposure controls					
Appropriate engineering controls	:	Good general ventila contaminants.	ation should be suff	icient to cont	trol worker exposure to airborne
Individual protection measu	ures				
Hygiene measures	:	before eating, smoki Appropriate techniqu Contaminated work	ing and using the la ues should be used clothing should not ng before reusing.	avatory and a I to remove p : be allowed o Ensure that e	ndling chemical products, it the end of the working period. otentially contaminated clothing. but of the workplace. Wash eyewash stations and safety
Eye/face protection	:	assessment indicate gases or dusts. If co	es this is necessary ontact is possible, t	to avoid exp he following	rd should be used when a risk osure to liquid splashes, mists, protection should be worn, protection: safety glasses with
Skin protection					
Hand protection	:	be worn at all times this is necessary. C check during use that should be noted that different for different	when handling che onsidering the para at the gloves are st t the time to breakt glove manufacture	mical produc ameters spec ill retaining th hrough for an ers. In the ca	th an approved standard should its if a risk assessment indicates ified by the glove manufacturer, neir protective properties. It ny glove material may be ase of mixtures, consisting of s cannot be accurately
		protection class of 6 recommended. Rec When only brief cont (breakthrough time > Recommended glow	(breakthrough time commended gloves tact is expected, a >30 minutes accord es: Nitrile, thicknes	e >480 minut :: Viton ® or N glove with pr ding to EN374 ss ≥ 0.12 mm	
		The performance or chemical damage ar			be reduced by physical/
			appropriate and tak	kes into acco	glove selected for handling this unt the particular conditions of
Body protection	:		d the risks involved		be selected based on the task be approved by a specialist
Other skin protection	:		ne task being perfo	rmed and the	tion measures should be e risks involved and should be st.
Respiratory protection	:	appropriate standard	d or certification. R	lespirators m	ect a respirator that meets the ust be used according to a ng, training, and other important
Environmental exposure controls	:	ensure they comply	with the requireme e scrubbers, filters	nts of enviror or engineerir	ent should be checked to nmental protection legislation. ng modifications to the process acceptable levels.
Date of issue/Date of revision		: 20-10-2022		Version : 1.0	² AkzoNobel
Date of previous issue		: 3-10-2022		7/14	ANZUNUDCI

7/14

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	:	Liquid.
Color	:	Gray.
Odor	:	Characteristic.
Odor threshold	:	Not available.
рН	:	8
Melting point/freezing point	:	Not available.
Initial boiling point and boiling range	:	Not available.
Flash point	:	Closed cup: 105°C
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Upper/lower flammability or explosive limits	:	Not available.
Vapor pressure	:	Not available.
Vapor density	:	Highest known value: (acrylated polyol).
Density	:	1.453 g/cm³
Solubility(ies)	:	Easily soluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (room temperature): 7.57 cm²/s Kinematic (40°C): 2.01 cm²/s

SECTION 10: Stability and reactivity			
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	: The product is stable.		
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.		
10.4 Conditions to avoid	: No specific data.		
10.5 Incompatible materials	: No specific data.		
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.		



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
propylidynetrimethanol	LD50 Oral	Mouse	13700 mg/kg	-
	LD50 Oral LD50 Oral	Mouse Rat	14000 mg/kg 14100 mg/kg	-
	LD50 Oral	Rat	14000 mg/kg	-
Conclusion/Summary	: Not available.		0.0	
Irritation/Corrosion				
Conclusion/Summary	: Not available.			
Sensitization				
Conclusion/Summary	: Not available.			
Mutagenicity				
Conclusion/Summary	: Not available.			
Carcinogenicity				
Conclusion/Summary	: Not available.			
Reproductive toxicity				
Conclusion/Summary	: Not available.			
<u>Teratogenicity</u>				
Conclusion/Summary	: Not available.			
Specific target organ toxicity	<u>y (single exposure)</u>			
Not available.				
Specific target organ toxicity Not available.	<u>y (repeated exposure)</u>			
Aspiration hazard Not available.				
Information on the likely routes of exposure	: Not available.			
Potential acute health effects				
Eye contact	: No known significant effects of	or critical hazards		
Inhalation	: No known significant effects of	or critical hazards.		
Skin contact	May cause an allergic skin reaction.			
Ingestion	: No known significant effects of	or critical hazards		
	sical, chemical and toxicologic	al characteristic	<u>s</u>	
Eye contact	: No specific data.			
Inhalation	: No specific data.			
Skin contact	: Adverse symptoms may inclu irritation redness	de the following:		
Ingestion	: No specific data.			
Delayed and immediate effect	ts and also chronic effects from	n short and long	term exposure	
Short term exposure				
Potential immediate effects	: Not available.			
Date of issue/Date of revision	: 20-10-2022	Version	: 1.02	
Date of previous issue	: 3-10-2022	9/14		AkzoNobe

SECTION 11: Toxicological information

Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
Other information	: Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
propylidynetrimethanol	Acute EC50 13000000 μg/l Fresh water Acute LC50 14400000 μg/l Marine water	Daphnia - Daphnia magna Fish - Cyprinodon variegatus	48 hours 96 hours
Conclusion/Summary	· Not available		

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
propylidynetrimethanol	-0.47	<1	low

12.4 Mobility in soil

Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

Date of issue/Date of revision	: 20-10-2022	Version : 1.02	
Date of previous issue	: 3-10-2022	10/14	AkzoNobel

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
Disposal considerations	 Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation		
EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11		
Packaging			
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.		
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.		
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.		

SECTION 14: Transport information

		INDO	
	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

Date of issue/Date of revision	: 20-10-2022	Version : 1.02	
Date of previous issue	: 3-10-2022	11/14	AkzoNobel

	FR6-55 SEMI-GLOSS BASE GREY S-1000-N/7541
SECTION 14: Transp	ort information
14.6 Special precautions for user	 Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport in bulk according to IMO instruments	: Not applicable.
SECTION 15: Regula	itory information
5.1 Safety, health and envir	onmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 190	
Annex XIV - List of substa Annex XIV	nces subject to authorization
None of the components a	re listed
Substances of very high	
None of the components a	
Annex XVII - Restrictions	: Not applicable.
on the manufacture, placing on the market and use of certain dangerous substances,	
mixtures and articles	
Other EU regulations	
VOC	The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.
VOC for Ready-for-Use Mixture	: Not applicable.
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed
Ozone depleting substance Not listed.	<u>es (1005/2009/EU)</u>
Prior Informed Consent (P Not listed.	<u>PIC) (649/2012/EU)</u>
Seveso Directive	
This product is not controlle	d under the Seveso Directive.
National regulations	
Industrial use	: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.
VbF class	: Not regulated.
Limitation of the use of	: Permitted.
organic solvents	

Chemical Weapon Convention List Schedules I, II & III Chemicals

Date of issue/Date of revision	: 20-10-2022	Version : 1.02	
Date of previous issue	: 3-10-2022	12/14	AkzoNobel

SECTION 15: Regulatory information

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

: Not determined. Europe

15.2 Chemical Safety

: No Chemical Safety Assessment has been carried out.

Assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.		
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group 	
	vPvB = Very Persistent and Very Bioaccumulative	

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
, -	Calculation method Calculation method

Full text of abbreviated H statements

H 301	Toxic if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H330	Fatal if inhaled.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]



SECTION 16: Other information		
Cute Tox. 2 Acute Tox. 3 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 3 Repr. 2 Skin Corr. 1C Skin Sens. 1 Skin Sens. 1		ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 3 TOXIC TO REPRODUCTION - Category 2 SKIN CORROSION/IRRITATION - Category 1C SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A
Date of printing	: 31 October 202	2
Date of issue/ Date of revision	: 20 October 202	2
Date of previous issue	: 3 October 2022	

Version

: 1.02

Unique ID Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

