

# SAFETY DATA SHEET

03-49 BASE FOG GREY

## **Section 1. Identification**

GHS product identifier : 03-49 BASE FOG GREY

**SDS code** : 21049002B

#### Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Paint. Professional use Industrial use

Uses advised against

All other uses

**Product use** : Filler for exterior use

Supplier's details

MAPAERO SAS

10, Avenue de la Rijole CS30098

09103 PAMIERS Cedex

France

e-mail address : PSRA PAMIERS@akzonobel.com

Emergency telephone number (with hours of

indiffice (with flours of

operation)

: +33 (0)5 34 01 34 01 +33 (0)5 61 60 23 30

### Section 2. Hazards identification

Classification of the substance or mixture

: SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SKIN SENSITIZATION - Category 1

GERM CELL MUTAGENICITY - Category 2

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

#### GHS label elements, including precautionary statements

Hazard pictograms :







Signal word : Danger

**Hazard statements**: H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage.

H341 - Suspected of causing genetic defects.

H373 - May cause damage to organs through prolonged or repeated exposure.

#### **Precautionary statements**

Date of issue/Date of revision : 30-9-2022 Version : 1

Date of previous issue : No previous validation 1/11 AkzoNobel

### Section 2. Hazards identification

Prevention : P201 - Obtain special instructions before use.

P280 - Wear protective gloves, protective clothing and eye or face protection.

P260 - Do not breathe vapor.

P264 - Wash hands thoroughly after handling.

Response : P308 + P313 - IF exposed or concerned: Get medical advice or attention.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

Storage : Not applicable.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Other hazards which do not : None known.

result in classification

# Section 3. Composition/information on ingredients

Substance/mixture

Ingredient name	%	CAS number
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin	≥10 - ≤15	25068-38-6
2,3-epoxypropyl neodecanoate	≤5	26761-45-5
benzyl alcohol	≤5	100-51-6
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	≤5	2530-83-8
Naphtha (petroleum), hydrodesulfurized heavy	≤2.5	64742-82-1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Chemical formula : Not applicable.

#### Section 4. First aid measures

#### **Description of necessary first aid measures**

: Get medical attention immediately. Call a poison center or physician. Immediately Eye contact

> flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes.

Chemical burns must be treated promptly by a physician.

Inhalation Get medical attention immediately. Call a poison center or physician. Remove

victim to fresh air and keep at rest in a position comfortable for breathing. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

It may be dangerous to the person providing aid to give mouth-to-mouth

resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie,

belt or waistband.

Skin contact : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash

contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure.

Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date of revision : 30-9-2022 Version : 1

**AkzoNobel** Date of previous issue : No previous validation 2/11

### Section 4. First aid measures

#### Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : No specific data.

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion**: Adverse symptoms may include the following:

stomach pains

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

#### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### Extinguishing media

Suitable extinguishing

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

media

: None known.

Specific hazards arising

from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Date of issue/Date of revision : 30-9-2022 Version : 1

Date of previous issue : No previous validation 3/11 AkzoNobel

# Section 5. Fire-fighting measures

#### **Hazardous thermal** decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide sulfur oxides

halogenated compounds metal oxide/oxides

#### Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Date of issue/Date of revision : 30-9-2022 Version : 1

**AkzoNobel** Date of previous issue : No previous validation 4/11

# Section 7. Handling and storage

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

None.

# Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

# Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

#### Skin protection

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date of revision : 30-9-2022 Version : 1

Date of previous issue : No previous validation

5/11

AkzoNobel

# Section 8. Exposure controls/personal protection

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

<u>Appearance</u>

Physical state : Liquid. Color : Gray.

Odor : Characteristic. : Not available. Odor threshold : Not available. Melting point/freezing point : Not available. Initial boiling point and : Not available.

boiling range

Flash point Closed cup: 100°C

**Evaporation rate** : Not available. Flammability (solid, gas) : Not available.

Upper/lower flammability or

explosive limits

: Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcohol)

Vapor pressure : Not available.

Vapor density : Highest known value: 3.7 (Air = 1) (benzyl alcohol).

: 2.216 g/cm<sup>3</sup> Density

: Insoluble in the following materials: cold water. Solubility(ies)

Partition coefficient: n-octanol/ : Not available.

water

: Not available. **Auto-ignition temperature Decomposition temperature** : Not available.

**Viscosity** : Kinematic (room temperature): 9.03 cm<sup>2</sup>/s

Kinematic (40°C): 2.01 cm<sup>2</sup>/s

# Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

**SADT** : Not available.

Date of issue/Date of revision : 30-9-2022 Version

**AkzoNobel** Date of previous issue : No previous validation 6/11

# **Section 11. Toxicological information**

### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
2,3-epoxypropyl	LD50 Oral	Rat	>10 g/kg	-
neodecanoate				
benzyl alcohol	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Intra-arterial	Rat	441 mg/kg	-
	LD50 Intraperitoneal	Mouse	650 mg/kg	-
	LD50 Intraperitoneal	Rat	400 mg/kg	-
	LD50 Intravenous	Mouse	324 mg/kg	-
	LD50 Intravenous	Rat	53 mg/kg	-
	LD50 Oral	Guinea pig	2500 mg/kg	-
	LD50 Oral	Guinea pig	2500 mg/kg	-
	LD50 Oral	Mouse	1360 mg/kg	-
	LD50 Oral	Mouse	1360 mg/kg	-
	LD50 Oral	Rabbit	1040 mg/kg	-
	LD50 Oral	Rabbit	1040 mg/kg	-
	LD50 Oral	Rat	1.5 mL/kg	-
	LD50 Oral	Rat	1230 mg/kg	-
	LD50 Oral	Rat	1660 mg/kg	-
[3-(2,3-epoxypropoxy)propyl]	LD50 Dermal	Rabbit	3970 uL/kg	-
trimethoxysilane				
	LD50 Oral	Rat	7.01 g/kg	-
	LD50 Oral	Rat	22600 uL/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction product: bisphenol- A-(epichlorhydrin); epoxy resin	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 UI	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 mg	-
2,3-epoxypropyl neodecanoate	Skin - Moderate irritant	Rabbit	-	0.5 MI	-
benzyl alcohol	Skin - Moderate irritant	Rabbit	-	24 hours 100 mg	-
[3-(2,3-epoxypropoxy)propyl] trimethoxysilane	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

 Date of issue/Date of revision
 : 30-9-2022
 Version
 : 1

 Date of previous issue
 : No previous validation
 7/11
 AkzoNobel

# **Section 11. Toxicological information**

Name	Category	Route of exposure	Target organs
Naphtha (petroleum), hydrodesulfurized heavy	Category 3	-	Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Naphtha (petroleum), hydrodesulfurized heavy	Category 1	inhalation	-

#### **Aspiration hazard**

Name	Result
Naphtha (petroleum), hydrodesulfurized heavy	ASPIRATION HAZARD - Category 1

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : No specific data.

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion**: Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General: May cause damage to organs through prolonged or repeated exposure. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to very

low levels.

**Carcinogenicity**: No known significant effects or critical hazards.

**Mutagenicity**: Suspected of causing genetic defects.

Date of issue/Date of revision : 30-9-2022 Version : 1

 Date of previous issue
 : No previous validation
 8/11

 AkzoNobel

03-49 BASE FOG GREY

# **Section 11. Toxicological information**

Reproductive toxicity

: No known significant effects or critical hazards.

# **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
benzyl alcohol	Acute LC50 10000 μg/l Fresh water Acute LC50 460000 μg/l Fresh water	Fish - Lepomis macrochirus Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours 96 hours
	Acute LC50 15000 μg/l Marine water	Fish - Menidia beryllina	96 hours

#### Persistence/degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
reaction product: bisphenol-A-(epichlorhydrin); epoxy	2.64 to 3.78	31	low
resin			
2,3-epoxypropyl	4.4	-	high
neodecanoate			
benzyl alcohol	0.87	-	low
Naphtha (petroleum),	-	10 to 2500	high
hydrodesulfurized heavy			

#### **Mobility in soil**

Soil/water partition coefficient (K<sub>oc</sub>)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision: 30-9-2022Version: 1Date of previous issue: No previous validation9/11AkzoNobel

03-49 BASE FOG GREY

# **Section 14. Transport information**

	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

### Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

: SS586: Specification for hazard communication for hazardous chemicals and dangerous goods.

Singapore - hazardous chemicals under government control

None.

# Section 16. Other information

**History** 

Date of printing : 1 November 2022 Date of issue/ Date of : 30 September 2022

revision

Date of previous issue : No previous validation

Version : 1 **Unique ID** 

: ATE = Acute Toxicity Estimate Key to abbreviations

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group **UN = United Nations** 

Procedure used to derive the classification

Date of issue/Date of revision : 30-9-2022 Version : 1 **AkzoNobel** Date of previous issue : No previous validation 10/11

03-49 BASE FOG GREY

## Section 16. Other information

Classification	Justification
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
GERM CELL MUTAGENICITY - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method

Indicates information that has changed from previously issued version.

#### **Notice to reader**

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision : 30-9-2022 Version : 1 11/11

Date of previous issue : No previous validation

