

SAFETY DATA SHEET

DI-TEX 50 MATT BASE META GREY 9006 PPAXALTA/B428

Section 1. Identification

GHS product identifier SDS code

: DI-TEX 50 MATT BASE META GREY 9006 PPAXALTA/B428 : 8422B428B

Relevant identified uses of the substance or mixture and uses advised against

Identified uses Waterborne paint. Professional use Industrial use			
All other uses			
Product use	: Waterborne coating for interior use.		
Supplier's details			
MAPAERO SAS			
10, Avenue de la l			
09103 PAMIERS France	Cedex		
e-mail address	: PSRA_PAMIERS@akzonobel.com		
Emergency telephone	: +33 (0)5 34 01 34 01		
number (with hours of	+33 (0)5 61 60 23 30		

Section 2. Hazards identification

2

Classification of the	:	SKIN CORROSION/IRRITATION - Category 3
substance or mixture		SKIN SENSITIZATION - Category 1

GHS label elements

operation)

Hazard pictograms



Signal word Hazard statements	: Warning : H316 - Causes mild skin irritation.			
Precautionary statements	H317 - May cause an a	llergic skin reaction.		
Prevention	: P280 - Wear protective P261 - Avoid breathing			
Response	P302 + P352 - IF ON S	[:] contaminated clothing and wash it be KIN: Wash with plenty of water. ritation or rash occurs: Get medical ad		
Storage	: Not applicable.			
Date of issue/Date of revision	: 20-10-2022	Version : 1.03		
Date of previous issue	: 4-10-2022	1/10	AkzoNobel	

Section 2. Hazards identification

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not : None known. result in classification

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Chinese name (Traditional)	Concentration	CAS number	Туре
2-butoxyethanol	≤3	111-76-2	[1], [2]
C(M)IT/MIT(3:1)	<0.01	55965-84-9	[1]
Nombre del producto	Concentración	Número CAS	Тіро
2-butoxietanol	≤3	111-76-2	[1], [2]
C(M)IT/MIT(3:1)	<0.01	55965-84-9	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Toxic chemical substance

[4] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	eyelids. Check for an		onally lifting the upper and lower Continue to rinse for at least 10	
Inhalation	If not breathing, if bre artificial respiration or person providing aid adverse health effect position and get med tight clothing such as decomposition produc	athing is irregular or if respirat oxygen by trained personnel. o give mouth-to-mouth resusc s persist or are severe. If unc cal attention immediately. Ma a collar, tie, belt or waistband	It may be dangerous to the citation. Get medical attention if onscious, place in recovery intain an open airway. Loosen . In case of inhalation of e delayed. The exposed person	
Skin contact	Wash contaminated or gloves. Continue to r event of any complair	oap and water. Remove cont clothing thoroughly with water inse for at least 10 minutes. (its or symptoms, avoid further shoes thoroughly before reuse	Get medical attention. In the exposure. Wash clothing	
Ingestion	and keep at rest in a swallowed and the ex drink. Stop if the exp induce vomiting unles the head should be ke attention if adverse he mouth to an unconsc medical attention imm	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.		
Date of issue/Date of revision	: 20-10-2022	Version : 1.		
Date of previous issue	: 4-10-2022	2/10	AkzoNobel	

Section 4. First aid measures

Most important symptoms/effects, acute and delayed

Potential acute health effect	
Eye contact	No known significant effects or critical hazards.
Inhalation	No known significant effects or critical hazards.
Skin contact	Causes mild skin irritation. May cause an allergic skin reaction.
Ingestion	No known significant effects or critical hazards.
<u>Over-exposure signs/symp</u>	ns
Eye contact	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	No specific data.
Skin contact	Adverse symptoms may include the following: irritation redness
Ingestion	No specific data.
Indication of immediate med	al attention and special treatment needed, if necessary
Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delaye The exposed person may need to be kept under medical surveillance for 48 hours
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Section 5. Fire-fighting measures			
Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.		
Unsuitable extinguishing media	: None known.		
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.		
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides halogenated compounds metal oxide/oxides		
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.		
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.		

See toxicological information (Section 11)

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ontainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

<u>Control parameters</u> <u>Occupational exposure limits</u>



Section 8. Exposure controls/personal protection

Ingredient name			Exposure limits
2-butoxyethanol			TW Minstry of Labor, labor permissible workplace exposure standards, allowable concentration (Taiwan, 3/2018). Absorbed through skin. STEL: 37.5 ppm 15 minutes. STEL: 181.5 mg/m ³ 15 minutes. TWA: 25 ppm 8 hours. TWA: 121 mg/m ³ 8 hours.
Appropriate engineering controls	:	Good general ventilation should be su contaminants.	fficient to control worker exposure to airborne
Individual protection measu	res		
Respiratory protection	:	appropriate standard or certification.	exposure, select a respirator that meets the Respirators must be used according to a are proper fitting, training, and other important
Hand protection	:	be worn at all times when handling ch this is necessary. Considering the par check during use that the gloves are s should be noted that the time to break	s complying with an approved standard should emical products if a risk assessment indicates rameters specified by the glove manufacturer, still retaining their protective properties. It through for any glove material may be rers. In the case of mixtures, consisting of the gloves cannot be accurately
Eye protection	:	assessment indicates this is necessar gases or dusts. If contact is possible,	proved standard should be used when a risk y to avoid exposure to liquid splashes, mists, the following protection should be worn, gher degree of protection: chemical splash
Body protection	:		body should be selected based on the task d and should be approved by a specialist
Other skin protection	:		al skin protection measures should be ormed and the risks involved and should be ng this product.
Hygiene measures	:	eating, smoking and using the lavatory Appropriate techniques should be use Contaminated work clothing should no	bughly after handling chemical products, before y and at the end of the working period. d to remove potentially contaminated clothing. bt be allowed out of the workplace. Wash Ensure that eyewash stations and safety occation.

Section 9. Physical and chemical properties

<u>Appearance</u>			
Physical state	: Liquid.		
Color	: Silver.		
	: Characteristic.		
Odor threshold	: Not available.		
рН	: 8		
Melting point/freezing point	: Not available.		
Initial boiling point and boiling range	: Not available.		
Flash point	: Closed cup: 105°C		
Date of issue/Date of revision	: 20-10-2022	Version : 1.03	
Date of previous issue	: 4-10-2022	5/10	AkzoNobel

Section 9. Physical and chemical properties

-		
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Upper/lower flammability or explosive limits	:	Not available.
Vapor pressure	:	Not available.
Vapor density	:	Highest known value: 4.1 (Air = 1) (2-butoxyethanol). Weighted average: 2.56 (Air = 1)
Density	:	1.182 g/cm³
Solubility(ies)	:	Easily soluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (room temperature): 10.15 cm²/s Kinematic (40°C): 2.01 cm²/s

Section 10. Stability and reactivity

Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Incompatible materials	: No specific data.
Conditions to avoid	: No specific data.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	: The product is stable.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethanol	LC50 Inhalation Gas.	Mouse	700 ppm	7 hours
-	LC50 Inhalation Gas.	Rat	450 ppm	4 hours
	LC50 Inhalation Vapor	Mouse	3380 mg/m ³	7 hours
	LC50 Inhalation Vapor	Rat	2900 mg/m ³	7 hours
	LD50 Dermal	Guinea pig	230 uL/kg	-
	LD50 Dermal	Rabbit	220 mg/kg	-
	LD50 Intraperitoneal	Mouse	536 mg/kg	-
	LD50 Intraperitoneal	Rabbit	220 mg/kg	-
	LD50 Intraperitoneal	Rat	220 mg/kg	-
	LD50 Intravenous	Mouse	1130 mg/kg	-
	LD50 Intravenous	Rabbit	252 mg/kg	-
	LD50 Intravenous	Rat	307 mg/kg	-
	LD50 Oral	Guinea pig	1200 mg/kg	-
	LD50 Oral	Mouse	1230 mg/kg	-
	LD50 Oral	Mouse	1167 mg/kg	-
	LD50 Oral	Rabbit	300 mg/kg	-
	LD50 Oral	Rabbit	320 mg/kg	-
	LD50 Oral	Rat	917 mg/kg	-
	LD50 Oral	Rat	250 mg/kg	-
	LD50 Route of exposure	Mouse	1050 mg/kg	-
ate of issue/Date of revision	: 20-10-2022	Versio	on : 1.03	
ate of previous issue	: 4-10-2022	6/10		AkzoNobel

Section 11. Toxicological information

unreported LD50 Route of exposure unreported	Rat	917 mg/kg	-
--	-----	-----------	---

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Severe irritant Skin - Mild irritant	Rabbit Rabbit	-	100 mg 500 mg	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes mild skin irritation. May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the phys	sic	al, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure

Date of issue/Date of revision	: 20-10-2022	Version : 1.03	
Date of previous issue	: 4-10-2022	7/10	AkzoNobel

Section 11. Toxicological information

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Section 12. Ecological information

<u>Toxicity</u>				
Product/ingredient name	Result	Species	Exposure	
2-butoxyethanol	Acute EC50 >1000 mg/l Fresh water Acute LC50 800000 μg/l Marine water Acute LC50 1490000 μg/l Fresh water Acute LC50 1250000 μg/l Marine water	Daphnia - Daphnia magna Crustaceans - Crangon crangon Fish - Lepomis macrochirus Fish - Menidia beryllina	48 hours 48 hours 96 hours 96 hours	

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-butoxyethanol	0.81	-	low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled		
Date of issue/Date of revision	: 20-10-2022	Version : 1.03	
Date of previous issue	: 4-10-2022	8/10	AkzoNobel

DI-TEX 50 MATT BASE META GREY 9006 PPAXALTA/B428

Section 13. Disposal considerations

material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ	
UN number	Not regulated.	Not regulated.	Not regulated.	
UN proper shipping name	-	-	-	
Transport hazard class(es)	-	-	-	
Packing group	-	-	-	
Environmental hazards	No.	No.	No.	

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Section 15. Regulatory information

List of chemicals for which annufacturing or handling is defined as "work specially hazardous to health": 2-butoxyethanol. hazardous to

Section 16. Other information

Procedure used to derive the classification

112 - 4 - ---

Classification	Justification
······································	Calculation method Calculation method

Date of issue/Date of revision Date of previous issue	: 20-10-2022 : 4-10-2022	Version : 1.03 9/10	AkzoNobel
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available 		
Unique ID	:		
Version	: 1.03		
Date of issue/ Date of revision	: 20 October 2022		
Date of printing	: 1 November 2022		
<u>History</u>			

Section 16. Other information

SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

