

SAFETY DATA SHEET

FR4-45 BASE CREAM

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: FR4-45 BASE CREAM
SDS code	: 64000300B

1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses		
Waterborne paint. Professio	Waterborne paint. Professional use Industrial use		
	Uses advised against		
All other uses			
Product use	: Filler for interior use		
1.3 Details of the supplier o	of the safety data sheet		
MAPAERO SAS 10, Avenue de la Ri 09103 PAMIERS Co France			
e-mail address of person responsible for this SDS	: PSRA_PAMIERS@akzonobel.com		
1.4 Emergency telephone n	umber		
National advisory body/Po	vison Center		
Telephone number	: 112		
<u>Supplier</u>			
Telephone number	: +33 (0)5 34 01 34 01 +33 (0)5 61 60 23 30		
Hours of operation			

SECTION 2: Hazards identification

.1 Classification of the s	ubstance or mixture	
Product definition	: Mixture	
Classification according	to Regulation (EC) No. 1272/2008 [CLP/GHS]	
Skin Sens. 1, H317 Aquatic Chronic 3, H412		
The product is classified a	s hazardous according to Regulation (EC) 1272/2008 as amended	l.
See Section 16 for the full	text of the H statements declared above.	
See Section 11 for more d	letailed information on health effects and symptoms.	

Date of issue/Date of revision	: 9-12-2022	Version : 2	
Date of previous issue	: 7-12-2022	1/15	AkzoNobel

FR4-45 BASE CREAM

SECTION 2: Hazards identification		
2.2 Label elements		
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Wear protective gloves. Avoid release to the environment. Avoid breathing vapor.
Response	:	Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	7,2-benzisothiazol-3(2H)-one C(M)IT/MIT(3:1)
Supplemental label elements	:	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	nen	ts
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture					
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
√2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5	≤0.1	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
Date of issue/Date of revision	: 9-12-2022		Version : 2		
Date of previous issue	: 7-12-2022		2/15	Akzol	Nobe

	FR4-45 BASE CREAM				
SECTION 3: Col	mposition/informat	ion on	ingredients		
C(M)IT/MIT(3:1)	REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5	≤0.1	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Corr. 1C, H314: C $\geq 0.6\%$ Skin Irrit. 2, H315: $0.06\% \leq C < 0.6\%$ Skin Sens. 1, H317: C $\geq 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures : Immediately flush eves with plenty of water, occasionally lifting the upper and lower Eve contact evelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs. Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Skin contact Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. : Wash out mouth with water. Remove dentures if any. If material has been Ingestion swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Version : 2 Date of issue/Date of revision :9-12-2022

FR4-45 BASE CREAM

SECTION 4: First aid measures

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, C(M)IT/MIT(3:1). May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

	0
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising fr	om the substance or mixture
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Date of issue/Date of revision	: 9-12-2022	Version : 2	
Date of previous issue	: 7-12-2022	4/15	AkzoNobe

SECTION 5: Firefighting measures

Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
---	---

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Eva ente mis	action shall be taken involving any personal risk or without suitable training. acuate surrounding areas. Keep unnecessary and unprotected personnel from ering. Do not touch or walk through spilled material. Avoid breathing vapor or it. Provide adequate ventilation. Wear appropriate respirator when ventilation is dequate. Put on appropriate personal protective equipment.
For emergency responders	info	pecialized clothing is required to deal with the spillage, take note of any prmation in Section 8 on suitable and unsuitable materials. See also the prmation in "For non-emergency personnel".
6.2 Environmental precautions	dra env	bid dispersal of spilled material and runoff and contact with soil, waterways, ins and sewers. Inform the relevant authorities if the product has caused vironmental pollution (sewers, waterways, soil or air). Water polluting material. y be harmful to the environment if released in large quantities.
6.3 Methods and materials for	conta	ainment and cleaning up
Small spill	up i ma	p leak if without risk. Move containers from spill area. Dilute with water and mop if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry terial and place in an appropriate waste disposal container. Dispose of via a nsed waste disposal contractor.
Large spill	upv	p leak if without risk. Move containers from spill area. Approach release from vind. Prevent entry into sewers, water courses, basements or confined areas. sh spillages into an effluent treatment plant or proceed as follows. Contain and

collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
 6.4 Reference to other : See Section 1 for emergency contact information.

See Section 13 for additional waste treatment information.

See Section 8 for information on appropriate personal protective equipment.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

sections

Protective measures	history of skin sensitiz which this product is u Avoid breathing vapor original container or ar	rsonal protective equipment (see Section 8). Persons with a ation problems should not be employed in any process in used. Do not get in eyes or on skin or clothing. Do not inges or mist. Avoid release to the environment. Keep in the n approved alternative made from a compatible material, ke t in use. Empty containers retain product residue and can b use container.	st. pt
Advice on general occupational hygiene	handled, stored and p eating, drinking and sr	moking should be prohibited in areas where this material is rocessed. Workers should wash hands and face before moking. Remove contaminated clothing and protective ering eating areas. See also Section 8 for additional e measures.	
Date of issue/Date of revision	· 9-12-2022	Version : 2	



FR4-45 BASE CREAM

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient na	ame Type	Exposure	Value	Population	Effects
2-benzisothiazol-3(2H)-on	e DNEL	Long term Dermal	0.345 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.966 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m³	Workers	Systemic
C(M)IT/MIT(3:1)	DNEL	Long term Inhalation	0.02 mg/m ³	General population	Local
	DNEL	Long term Inhalation	0.02 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	0.04 mg/m ³	General population	Local
	DNEL	Short term Inhalation	0.04 mg/m ³		Local
	DNEL	Long term Oral	0.09 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.11 mg/ kg bw/day	General population	Systemic
e of issue/Date of revision	: 9-12-2022		Version	:2	
e of previous issue	: 7-12-2022		6/15		AkzoNob

SECTION 8: Exposure controls/personal protection

PNECs

No PNECs available.

8.2 Exposure controls	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	ures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

eristic.

Date of issue/Date of revision	: 9-12-2022	Version : 2	
Date of previous issue	: 7-12-2022	7/15	AkzoNobel

	al and che		•			
Ddor threshold		vailable. vailable.				
Melting point/freezing poir nitial boiling point and		vailable. vailable.				
boiling range	. Nota	valiable.				
Flammability	: Not a	vailable.				
Lower and upper explosio imit	n : Nota	vailable.				
Flash point	: Close	d cup: 105°0	C (221°F) [Pensky	/-Martens1		
Auto-ignition temperature	:	1		, 1		
Ingredient name		°C	°F		Method	
24 butoxyethanol		230	446		DIN 51794	
Paraffin waxes and Hydrocarbon	waxes	244.85	472.7			
Ethene, homopolymer		330 to 410	626 to 77	D		
dodecamethylcyclohexasiloxane		368 to 371	694.4 to 6	99.8		
decamethylcyclopentasiloxane		372	701.6		ASTM E 659-78	
N,N'-ethylenedi(stearamide)		380	716		DIN 51794	
octamethylcyclotetrasiloxane		384 to 387	723.2 to 7	28.6	ASTM E 659	
ammonia, anhydrous		651	1203.8			
Solubility(ies) Media Sold water	: Res		201 mm²/s [DIN	EN ISO 32	N EN ISO 321 19]	
Media Fold water Partition coefficient: n-octa water	: Res	ult		EN ISO 32	19]	
Media Fold water Partition coefficient: n-octa	: Res Solu anol/ : Not a :	ult uble [OESO ((TG 105)]	EN ISO 32	19] Vapor press	
Media Fold water Partition coefficient: n-octa	: Res Solu anol/ : Not a :	ult uble [OESO (pplicable.	(TG 105)]	EN ISO 32	19] Vapor press	
Media Fold water Partition coefficient: n-oct vater /apor pressure	: Res Solu anol/ : Not a : Va	ult uble [OESO (pplicable. por Pressure	(TG 105)] e at 20°C		19] Vapor press	ure at 50°C
Media Fold water Partition coefficient: n-oct vater /apor pressure	: Res Solu anol/ : Not a : Vaj mm Hg	ult uble [OESO (pplicable. por Pressure kPa	(TG 105)] e at 20°C		19] Vapor press	ure at 50°C
Media Fold water Partition coefficient: n-octavater /apor pressure Ingredient name Frimonia, anhydrous	: Res Solu anol/ : Not a : Vaj mm Hg 72.31	uble [OESO (pplicable. por Pressure kPa 9.6	(TG 105)] e at 20°C		19] Vapor press	ure at 50°C
Media Fold water Partition coefficient: n-octavater /apor pressure Ingredient name mmonia, anhydrous octamethylcyclotetrasiloxane	: Res Solu anol/ : Not a : Vaj 72.31 0.99	pplicable.	(TG 105)] e at 20°C		19] Vapor press	ure at 50°C
Media Fold water Partition coefficient: n-octa water /apor pressure Ingredient name mmonia, anhydrous octamethylcyclotetrasiloxane 2-butoxyethanol	: Res Solut anol/ : Not a : Vaj 72.31 0.99 0.75	sult uble [OESO (pplicable. oor Pressure kPa 9.6 0.13 0.1	(TG 105)] e at 20°C		19] Vapor press	ure at 50°C
Media Cold water Partition coefficient: n-octa water /apor pressure Ingredient name minonia, anhydrous octamethylcyclotetrasiloxane 2-butoxyethanol Polyether modified siloxane	: Res Solu anol/ : Not a : Va 72.31 0.99 0.75 0.75	sult uble [OESO (pplicable. bor Pressure kPa 9.6 0.13 0.1 0.1	(TG 105)] e at 20°C		19] Vapor press	ure at 50°C
Media Cold water Partition coefficient: n-oct water /apor pressure Ingredient name mmonia, anhydrous octamethylcyclotetrasiloxane 2-butoxyethanol Polyether modified siloxane decamethylcyclopentasiloxane	: Res Solut anol/ : Not a : Val 72.31 0.99 0.75 0.75 0.25	sult uble [OESO (pplicable. bor Pressure kPa 9.6 0.13 0.1 0.1 0.1 0.1	(TG 105)] e at 20°C		19] Vapor press	ure at 50°C
Media Cold water Partition coefficient: n-octavater /apor pressure Ingredient name mmonia, anhydrous octamethylcyclotetrasiloxane 2-butoxyethanol Polyether modified siloxane decamethylcyclopentasiloxane aluminium hydroxide	: Res Solu anol/ : Not a : Val mm Hg 72.31 0.99 0.75 0.75 0.25 <0.075	Sult Juble [OESO (pplicable. bor Pressure kPa 9.6 0.13 0.1 0.1 0.1 0.033 <0.01	(TG 105)] e at 20°C		19] Vapor press	ure at 50°C
Media Cold water Partition coefficient: n-octavater Apor pressure Ingredient name Ingredient n	: Res Solut anol/ : Not a : Val 72.31 0.99 0.75 0.75 0.75 0.25 <0.075 0.00087	sult uble [OESO (pplicable. oor Pressure kPa 9.6 0.13 0.1 0.13 0.1 0.13 0.1 0.033 <0.01	(TG 105)] e at 20°C Method		19] Vapor press	ure at 50°C
Media Cold water Partition coefficient: n-octavater /apor pressure Ingredient name mmonia, anhydrous octamethylcyclotetrasiloxane 2-butoxyethanol Polyether modified siloxane decamethylcyclopentasiloxane aluminium hydroxide N,N'-ethylenedi(stearamide) 1,1'-(ethane-1,2-diyl)bis [pentabromobenzene] propylidynetrimethanol	: Res Solut anol/ : Not a : Va 72.31 0.99 0.75 0.75 0.75 0.25 <0.075 0.00087 <0.0000075 0	sult uble [OESO (pplicable. oor Pressure kPa 9.6 0.13 0.1 0.13 0.1 0.13 0.1 0.033 <0.01	(TG 105)] e at 20°C Method		19] Vapor press	ure at 50°C
Media Cold water Partition coefficient: n-octavater Vapor pressure Ingredient name mmonia, anhydrous octamethylcyclotetrasiloxane 2-butoxyethanol Polyether modified siloxane decamethylcyclopentasiloxane aluminium hydroxide N,N'-ethylenedi(stearamide) 1,1'-(ethane-1,2-diyl)bis [pentabromobenzene] propylidynetrimethanol Density	: Res Solu anol/ : Not a : Va mm Hg 72.31 0.99 0.75 0.75 0.25 <0.075 0.00087 <0.0000075 0 0 : .508	sult uble [OESO (pplicable. oor Pressure kPa 9.6 0.13 0.1 0.13 0.1 0.13 0.1 0.033 <0.01	(TG 105)] e at 20°C Method OECD 104		19] Vapor press	ure at 50°C
Media Cold water Partition coefficient: n-octavater /apor pressure Ingredient name mmonia, anhydrous octamethylcyclotetrasiloxane 2-butoxyethanol Polyether modified siloxane decamethylcyclopentasiloxane aluminium hydroxide N,N'-ethylenedi(stearamide) 1,1'-(ethane-1,2-diyl)bis [pentabromobenzene] propylidynetrimethanol Density /apor density	: Res Solu anol/ : Not a : Va mm Hg 72.31 0.99 0.75 0.75 0.25 <0.075 0.00087 <0.0000075 0 0 : .508	sult uble [OESO (pplicable. oor Pressure kPa 9.6 0.13 0.1 0.13 0.1 0.033 <0.01	(TG 105)] e at 20°C Method OECD 104		19] Vapor press	ure at 50°C
Partition coefficient: n-oct. water Vapor pressure Ingredient name Immonia, anhydrous octamethylcyclotetrasiloxane 2-butoxyethanol Polyether modified siloxane decamethylcyclopentasiloxane aluminium hydroxide N,N'-ethylenedi(stearamide) 1,1'-(ethane-1,2-diyl)bis [pentabromobenzene]	: Res Solu anol/ : Not a : Va mm Hg 72.31 0.99 0.75 0.75 0.25 <0.075 0.00087 <0.0000075 0 0 : .508	sult uble [OESO (pplicable. por Pressure kPa 9.6 0.13 0.1 0.13 0.1 0.033 <0.01	(TG 105)] e at 20°C Method OECD 104		19] Vapor press kPa	ure at 50°C

FR4-45 BASE CREAM

SECTION 9: Physical and chemical properties				
Median particle size	: Not applicable.			
SECTION 10: Stabilit	SECTION 10: Stability and reactivity			
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: No specific data.			
10.5 Incompatible materials	: No specific data.			

10.6 Hazardous : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
7,2-benzisothiazol-3(2H)-	LD50 Oral	Mouse	1150 mg/kg	-
one	LD50 Oral	Rat	1020 mg/kg	-
Conclusion/Summary	: Not available.			
Irritation/Corrosion				
Conclusion/Summary	: Not available.			
<u>Sensitization</u>				
Conclusion/Summary	: Not available.			
<u>Mutagenicity</u>				
Conclusion/Summary	: Not available.			
Carcinogenicity				
Conclusion/Summary	: Not available.			
Reproductive toxicity				
Conclusion/Summary	: Not available.			
<u>Teratogenicity</u>				
Conclusion/Summary	: Not available.			
Specific target organ toxicity	<u>r (single exposure)</u>			
Not available.				
Specific target organ toxicity	(repeated exposure)			
Not available.				

Aspiration hazard

Not available.

Date of issue/Date of revision	: 9-12-2022	Version : 2	
Date of previous issue	: 7-12-2022	9/15	AkzoNobel

FR4-45 BASE CREAM

SECTION 11: Toxico	ological information
Information on the likely routes of exposure	: Not available.
Potential acute health effect	<u>s</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph	vsical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Delayed and immediate effe Short term exposure Potential immediate effects	cts and also chronic effects from short and long term exposure : Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	fects
Not available.	
Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting propertiesNot available.11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Date of issue/Date of revision	: 9-12-2022	Version : 2	
Date of previous issue	: 7-12-2022	10/15	AkzoNobel

SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
,2-benzisothiazol-3(2H)-one	Acute EC50 97 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2.24 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 3.7 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 1.1 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 10 to 20 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 540 ppb Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 167 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 0.75 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.6 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.

Date of issue/Date of revision	: 9-12-2022	Version : 2	
Date of previous issue	: 7-12-2022	11/15	AkzoNobel

SECTION 13: Disposal considerations

Disposal considerations	: Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations.
	If this product is mixed with other wastes, the original waste product code may no
	longer apply and the appropriate code should be assigned.
	For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation	
EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11	
Packaging		
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.	
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.	

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information IMDG : MDG Code Segregation group Not applicable			
14.6 Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.			

14.7 Maritime transport in : Not applicable. **bulk according to IMO instruments**



SECTION 15: Regula	tory information
15.1 Safety, health and enviro EU Regulation (EC) No. 190	onmental regulations/legislation specific for the substance or mixture 7/2006 (REACH)
Annex XIV - List of substan	nces subject to authorization
Annex XIV	
None of the components a	
Substances of very high	
None of the components a	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Other EU regulations	
VOC	: The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.
VOC for Ready-for-Use Mixture	: Not available.
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed
Ozone depleting substanc Not listed.	<u>es (1005/2009/EU)</u>
Prior Informed Consent (P	IC) (649/2012/EU)
Not listed.	
Persistent Organic Polluta Not listed.	<u>nts</u>
Seveso Directive	
This product is not controlled	d under the Seveso Directive.
National regulations	
Industrial use	: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.
International regulations	
	ion List Schedules I, II & III Chemicals
Not listed.	
Montreal Protocol	
Not listed.	
Stockholm Convention on F Not listed.	Persistent Organic Pollutants
Data of issue (Data of revision	



FR4-45 BASE CREAM

SECTION 15: Regulatory information

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

15.2 Chemical Safety	: No Chemical Safety Assessment has been carried out.
----------------------	---

Assessment

SECTION 16: Other information

Indicates information that had a second s	s changed from previously issued version.
---	---

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

F 301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Date of issue/Date of revision	: 9-12-2022	Version : 2 14/15	AkzoNobel
Eye Dam. 1 Skin Corr. 1C Skin Irrit. 2		SERIOUS EYE DAMAGE/ EYE IRRITATION - C SKIN CORROSION/IRRITATION - Category 1C SKIN CORROSION/IRRITATION - Category 2	ategory 1
Aquatic Chronic 3		AQUATIC HAZARD (LONG-TERM) - Category 3	
Aquatic Chronic 2		AQUATIC HAZARD (LONG-TERM) - Category 2	
Aquatic Chronic 1		AQUATIC HAZARD (LONG-TERM) - Category 1	
Aquatic Acute 1		AQUATIC HAZARD (ACUTE) - Category 1	
Acute Tox. 4		ACUTE TOXICITY - Category 4	
Acute Tox. 3		ACUTE TOXICITY - Category 3	
Acute Tox. 2		ACUTE TOXICITY - Category 2	

SECTION 16: Other information				
Skin Sens. 1 Skin Sens. 1A	SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A			
Date of printing	: 9 December 2022			
Date of issue/ Date of revision	: 9 December 2022			
Date of previous issue	: 7 December 2022			
Version	: 2			
Unique ID	:			

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

