

SAFETY DATA SHEET

THINNER 713 THINNER

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: THINNER 713 THINNER
SDS code	: 51713000X

1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses
Thinner. Professional use I	ndustrial use
	Uses advised against
All other uses	
Product use	: Thinner
I.3 Details of the supplier o	f the safety data sheet
MAPAERO SAS 10, Avenue de la R 09103 PAMIERS C France	
e-mail address of person responsible for this SDS	: PSRA_PAMIERS@akzonobel.com
I.4 Emergency telephone n	umber
National advisory body/Po	<u>vison Center</u>
<u>Supplier</u>	
Telephone number	: +33 (0)5 34 01 34 01 +33 (0)5 61 60 23 30
Hours of operation	:

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Mam. Liq. 3, H226 STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Date of issue/Date of revision	: 9-12-2022	Version : 3	
Date of previous issue	: 5-10-2022	1/15	AkzoNobel

THINNER 713 THINNER

		THINNER TIS THINNER
SECTION 2: Hazards	ic	lentification
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	Flammable liquid and vapor. May cause drowsiness or dizziness.
Precautionary statements		
Prevention	:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapor.
Response	:	IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
Storage	:	Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	p-butyl acetate
Supplemental label elements	:	Repeated exposure may cause skin dryness or cracking.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≥90	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

Date of issue/Date of revision	: 9-12-2022	Version : 3	
Date of previous issue	: 5-10-2022	2/15	AkzoNobel

THINNER 713 THINNER

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures		
4.1 Description of first aid r	neasures	
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.	
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	
Skin contact	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.	
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.	

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Over-exposure signs/symptoms

Date of issue/Date of revision	: 9-12-2022	Version : 3	
Date of previous issue	: 5-10-2022	3/15	AkzoNobel

SECTION 4: First aid measures

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
	qualities have been ingested of innaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

•	
Hazards from the substance or mixture	: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
	inadequate. Fut on appropriate personal protective equipment.

Date of issue/Date of revision	: 9-12-2022	Version : 3	
Date of previous issue	: 5-10-2022	4/15	AkzoNobel

SECTION 6: Accident	ta	release measures
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and materials for	r c	ontainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Date of issue/Date of revision	: 9-12-2022	Version : 3	
Date of previous issue	: 5-10-2022	5/15	AkzoNobel

SECTION 7: Handling and storage

Danger criteria		
	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonne	50000 tonne

7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
P-butyl acetate	Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021). STEL: 150 ppm 15 minutes. STEL: 723 mg/m ³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 241 mg/m ³ 8 hours.
procedures atmos of the protect	product contains ingredients with exposure limits, personal, workplace phere or biological monitoring may be required to determine the effectiveness ventilation or other control measures and/or the necessity to use respiratory tive equipment. Reference should be made to monitoring standards, such as lowing: European Standard EN 680 (Workplace atmospheres - Cuidance for

protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient na	me Type	Exposure	Value	Population	Effects
p-butyl acetate	DNEL	Short term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3.4 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	7 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	11 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	12 mg/m³	General population	Systemic
	DNEL	Long term	35.7 mg/m³	General	Local
e of issue/Date of revision	: 9-12-2022		Version	:3	AkzoNob
te of previous issue	: 5-10-2022	5-10-2022		6/15	

THINNER 713 THINNER						
SECTION 8: Exposure controls/personal protection						
DNE	Inhalation L Long term Inhalation	48 mg/m ³	population Workers	Systemic		
DNE		300 mg/m³	General population	Local		
DNE	L Short term Inhalation	300 mg/m ³		Systemic		
DNE	L Long term Inhalation	300 mg/m ³	Workers	Local		
DNE	L Short term Inhalation	600 mg/m ³	Workers	Local		
DNE	L Short term Inhalation	600 mg/m ³	Workers	Systemic		

PNECs

No PNECs available.

8.2 Exposure controls					
Appropriate engineering controls	ventila contai contro	ation or other engi minants below an ols also need to ke	e ventilation. Use pro ineering controls to k y recommended or s eep gas, vapor or du xplosion-proof ventila	teep worker exposu statutory limits. The st concentrations b	re to airborne engineering
Individual protection meas	<u>sures</u>				
Hygiene measures	before Appro Wash	e eating, smoking priate techniques contaminated clo	and face thoroughly and using the lavato should be used to re othing before reusing se to the workstation	ory and at the end o emove potentially c . Ensure that eyew	f the working period. ontaminated clothing.
Eye/face protection	asses gases unless	sment indicates to or dusts. If conta	ing with an approved his is necessary to a act is possible, the fo indicates a higher d	void exposure to liq	uid splashes, mists,
Skin protection					
Hand protection	be wo this is check should differe	rn at all times who necessary. Cons during use that the d be noted that the ent for different glo al substances, the	en handling chemica	Il products if a risk a ers specified by the aining their protecti gh for any glove ma In the case of mixtu	iterial may be ires, consisting of
	produ	ct is the most app	nat the final choice of propriate and takes ir user's risk assessme	nto account the part	
Body protection	being before wear discha Europ	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer t European Standard EN 1149 for further information on material and design requirements and test methods.			d by a specialist om static electricity, from static nd gloves. Refer to
Other skin protection	: Appro select	priate footwear a ed based on the t	nd any additional ski ask being performed t before handling thi	and the risks invol	
Date of issue/Date of revision	: 9-12-2	2022	Vers	ion :3	
Date of previous issue	: 5-10-2	2022	7/15		AkzoNobel

SECTION 8: Exposure controls/personal protection

Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Ingredient name		ാ °		°F	Method	
Auto-ignition temperature	:					
Flash point	: 🕻	Nosed cup: 24°C	(75.2°F)	[Pensky-Martens]	
Lower and upper explosion limit	: N	lot available.				
Flammability	: N	lot available.				
Initial boiling point and boiling range	: N	lot available.				
Melting point/freezing point	: N	lot available.				
Odor threshold	: N	lot available.				
Odor	: 0	Characteristic.				
Color	: (Colorless.				
Physical state	: L	iquid.				
<u>Appearance</u>						

	Ingredient name		<i>ч</i> с	- -	Method	
	p-butyl acetate		415	779	EU A.15	
D	ecomposition temperature	: Not ava	ilable.			
р	н	: Not app	licable. [DIN EN 12	262]		
V	iscosity		tic (room temperat tic (40°C): 6 mm²/s			

Solubility(ies)

Media	Result
cold water	Not soluble [OESO (TG 105)]

Partition coefficient: n-octanol/ : Not applicable. water

2

2

Vapor pressure

	V	Vapor Pressure at 20°C			/apor pres	ssure at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
p≁butyl acetate	11.25	1.5	DIN EN 13016-2			
Density	: 0.88	31 g/cm³ [[DIN EN ISO 2811-1]			
Vapor density	: Not	available.				
Particle characteristics Median particle size	: Not	applicable				

Date of issue/Date of revision	: 9-12-2022	Version : 3	
Date of previous issue	: 5-10-2022	8/15	AkzoNobel

SECTION 10: Stabilit	y and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
p-butyl acetate	LC50 Inhalation Gas. LC50 Inhalation Vapor LD50 Dermal LD50 Intraperitoneal LD50 Oral LD50 Oral LD50 Oral LD50 Oral LD50 Oral	Rat Mouse Rabbit Mouse Guinea pig Mouse Rabbit Rat	390 ppm 6 g/m ³ >17600 mg/kg 1230 mg/kg 4700 mg/kg 6 g/kg 3200 mg/kg 10768 mg/kg	4 hours 2 hours - - - - -

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
-butyl acetate	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500	-
				mg	
Conclusion/Summary	: Not available.				
<u>Sensitization</u>					
Conclusion/Summary	: Not available.				
<u>Mutagenicity</u>					
Conclusion/Summary	: Not available.				
Carcinogenicity					
Conclusion/Summary	: Not available.				
Reproductive toxicity					
Conclusion/Summary	: Not available.				
Teratogenicity					
Conclusion/Summary	: Not available.				
Specific target organ toxicit	<u>y (single exposure)</u>				

THINNER 713 THINNER

SECTION 11: Toxicological information

Product/in	grea	lient name	Category	Route of exposure	Target organs
n-butyl acetate			Category 3	-	Narcotic effects
Specific target organ toxic	;ity ((repeated exposure)			
Not available.	-				
Aspiration hazard Not available.					
Information on the likely routes of exposure	:	Not available.			
Potential acute health effec	<u>ts</u>				
Eye contact	:	No known significant effe	cts or critical hazar	ds.	
Inhalation	:	Can cause central nervou dizziness.	ıs system (CNS) de	pression. May ca	ause drowsiness or
Skin contact	:	Defatting to the skin. May	y cause skin drynes	s and irritation.	
Ingestion	:	Can cause central nervou	ıs system (CNS) de	pression.	
Symptoms related to the ph	vsi	cal, chemical and toxicolo	ogical characterist	tics	
Eye contact	-	No specific data.			
Inhalation		Adverse symptoms may i nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness	nclude the following	j:	
Skin contact	:	Adverse symptoms may i irritation dryness cracking	nclude the followinູ	j :	
Ingestion	:	No specific data.			
Delayed and immediate effe	ects	and also chronic effects	from short and lo	na term exposur	P
Short term exposure					<u> </u>
Potential immediate effects	:	Not available.			
Potential delayed effects	:	Not available.			
Long term exposure					
Potential immediate effects	:	Not available.			
Potential delayed effects	:	Not available.			
Potential chronic health ef	fect	<u>s</u>			
Not available.					
Conclusion/Summary		Not available.			
General	-	Prolonged or repeated co or dermatitis.	ntact can defat the	skin and lead to i	rritation, cracking and/
Carcinogenicity	:	No known significant effe	cts or critical hazar	ds.	
Mutagenicity		No known significant effe			
Reproductive toxicity		No known significant effe			
Date of issue/Date of revision		: 9-12-2022	Versi	on :3	

SECTION 11: Toxicological information

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

Product/ingredient name	Result	Species	Exposure
-butyl acetate	Acute LC50 32 mg/l Marine water	Crustaceans - Artemia salina	48 hours
	Acute LC50 62000 µg/l Fresh water	Fish - Danio rerio	96 hours
	Acute LC50 100000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 185000 µg/l Marine water	Fish - Menidia beryllina	96 hours
	Acute LC50 18000 µg/l Fresh water	Fish - Pimephales promelas	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
p-butyl acetate	2.3	-	low

12.4 Mobility in soil

Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

Date of issue/Date of revision	: 9-12-2022	Version : 3	
Date of previous issue	: 5-10-2022	11/15	AkzoNobel

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>			
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.		
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.		
Disposal considerations	 Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority. 		

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 99	wastes not otherwise specified
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	 Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group			
Date of issue/Date of revi Date of previous issue	ision : 9-12-2022 : 5-10-2022	Version : 3 12/15	AkzoNobel

SECTION 14: Transp					
	SECTION 14: Transport information				
14.5 No. Environmental hazards		No.	No.		
Additional information					
ADR/RID	: <u>Tunnel</u>	<u>code</u> (D/E)			
IMDG		ncy schedules F-E, _S-E_ ode Segregation group Not	applicable		
14.6 Special precautions fo user	upright a		always transport in closed containers that are ons transporting the product know what to do ir		
14.7 Maritime transport in bulk according to IMO instruments	: Not appl	icable.			
SECTION 15: Regula	atory info	rmation			
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>					
Annex XIV - List of substa	<u>ances subject</u>	to authorization			
<u>Annex XIV</u> None of the components are listed.					
<u>Substances of very high concern</u> None of the components are listed.					
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not appli	cable.			
Other EU regulations					
VOC		isions of Directive 2004/42/E0 abel and/or technical data she	C on VOC apply to this product. Refer to the eet for further information.		
	: Not avail	able.			
VOC for Ready-for-Use Mixture	- <i>v</i>				
-	: Not listed				

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants Not listed.

Date of issue/Date of revision	: 9-12-2022	Version : 3	
Date of previous issue	: 5-10-2022	13/15	AkzoNobel

SECTION 15: Regulatory information

Seveso Directive

This product is controlled under the Seveso Directive. <u>Danger criteria</u>			
Category			
P5c			
National regulations			
Industrial use	: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.		
International regulation	—		
-	vention List Schedules I, II & III Chemicals		
Not listed.			
Montreal Protocol Not listed.			
	on Persistent Organic Pollutants		
Rotterdam Convention Not listed.	on Prior Informed Consent (PIC)		
UNECE Aarhus Protoco Not listed.	ol on POPs and Heavy Metals		
<u>Inventory list</u> Eurasian Economic U	nion : Russian Federation inventory: All components are listed or exempted.		
15.2 Chemical Safety Assessment	: No Chemical Safety Assessment has been carried out.		
SECTION 16: Oth	er information		
Indicates information t	hat has changed from previously issued version.		
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available 		

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
	On basis of test data Calculation method

Full text of abbreviated H statements

Date of issue/Date of revision	:9-12-2022	Version : 3	
Date of previous issue	: 5-10-2022	14/15	AkzoNobel

SECTION 16: Other information		
H226 H336 EUH066		Flammable liquid and vapor. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.
Full text of classifications	[CLP/GHS]	
Flam. Liq. 3 STOT SE 3	:	FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3
Date of printing	: 9 December 202	2
Date of issue/ Date of revision	: 9 December 2022	
Date of previous issue	: 5 October 2022	
Version	: 3	
Unique ID	:	
Notice to useday		

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

