

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET

A1500-M MATT BASE GREEN 383 FS 34094

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : A1500-M MATT BASE GREEN 383 FS 34094
SDS code : 13744094B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Paint. Professional use Industrial use
Uses advised against
All other uses

Product use : Solvent borne coating for exterior use.

1.3 Details of the supplier of the safety data sheet

MAPAERO SAS
10, Avenue de la Rijole CS30098
09103 PAMIERS Cedex
France

e-mail address of person responsible for this SDS : PSRA_PAMIERS@akzonobel.com

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : +33 (0)1 40 05 48 48

Supplier

Telephone number : +33 (0)5 34 01 34 01
+33 (0)5 61 60 23 30

Hours of operation :

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226
Skin Sens. 1, H317
STOT SE 3, H336
Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision : 1-10-2022 **Version** : 1
Date of previous issue : No previous validation 1/20

SECTION 2: Hazards identification

2.2 Label elements

Hazard pictograms



Signal word

: Warning

Hazard statements

: Flammable liquid and vapor.
 May cause an allergic skin reaction.
 May cause drowsiness or dizziness.
 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Wear protective gloves. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Avoid breathing vapor.

Response

: IF INHALED: Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.

Storage

: Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients

: 2-ethoxy-1-methylethyl acetate
 n-butyl acetate
 Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
 Hydroxyphenyl-benzotriazole derivatives
 Polymeric Benzotriazole

Supplemental label elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger

: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
2-ethoxy-1-methylethyl acetate	EC: 259-370-9 CAS: 54839-24-6 Index: 603-177-00-8	≥10 - ≤25	Flam. Liq. 3, H226 STOT SE 3, H336	[1]
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≥10 - ≤15	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	[1] [2]
2-methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6	≤10	Flam. Liq. 3, H226 STOT SE 3, H336	[1] [2]
Reaction mass of ethylbenzene and xylene	REACH #: 01-2119488216-32 EC: 905-588-0	≤3	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	[1] [2]
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≤1	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
Hydroxyphenyl-benzotriazole derivatives	REACH #: 01-0000015075-76 EC: 400-830-7 CAS: 104810-48-2	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
4-methylpentan-2-one	EC: 203-550-1 CAS: 108-10-1 Index: 606-004-00-4	≤0.6	Flam. Liq. 2, H225 Acute Tox. 4, H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336 EUH066	[1] [2]
Polymeric Benzotriazole	CAS: 104810-47-1	<1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	REACH #: 01-2119457273-39 EC: 918-481-9	≤0.2	Asp. Tox. 1, H304 EUH066	[1]
Hexanoic acid, 2-ethyl-, zinc salt, basic	REACH #: 01-2119979093-30 EC: 286-272-3 CAS: 85203-81-2	≤0.3	Eye Irrit. 2, H319 Repr. 2, H361d (oral) Aquatic Chronic 3, H412	[1]
cumene	REACH #: 01-2119473983-24 EC: 202-704-5 CAS: 98-82-8 Index: 601-024-00-X	≤0.1	Flam. Liq. 3, H226 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above.	[1] [2]

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption

Date of issue/Date of revision : 1-10-2022 Version : 1

Date of previous issue : No previous validation 4/20

SECTION 4: First aid measures

through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate, Hydroxyphenyl-benzotriazole derivatives, Polymeric Benzotriazole. May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonne	50000 tonne

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
n-butyl acetate	Ministry of Labor (France, 3/2020). Notes: Indicative limit values (circular) STEL: 940 mg/m ³ 15 minutes. Form: Risk for sensitisation STEL: 200 ppm 15 minutes. Form: Risk for sensitisation TWA: 710 mg/m ³ 8 hours. Form: Risk for sensitisation TWA: 150 ppm 8 hours. Form: Risk for sensitisation
2-methoxy-1-methylethyl acetate	Ministry of Labor (France, 10/2016). Absorbed through skin. Notes: Labour Act , Art 4412-149 (Regulatory binding exposure limits) STEL: 550 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 275 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.
Reaction mass of ethylbenzene and xylene	Ministry of Labor (France, 3/2020). Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL: 442 mg/m ³ 15 minutes. Form: Risk for sensitisation STEL: 100 ppm 15 minutes. Form: Risk for sensitisation TWA: 221 mg/m ³ 8 hours. Form: Risk for sensitisation TWA: 50 ppm 8 hours. Form: Risk for sensitisation
4-methylpentan-2-one	Ministry of Labor (France, 3/2020). Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL: 208 mg/m ³ 15 minutes. Form: Risk for sensitisation STEL: 50 ppm 15 minutes. Form: Risk for sensitisation TWA: 83 mg/m ³ 8 hours. Form: Risk for sensitisation TWA: 20 ppm 8 hours. Form: Risk for sensitisation
cumene	Ministry of Labor (France, 3/2020). Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

Date of issue/Date of revision : 1-10-2022

Version : 1

Date of previous issue : No previous validation

7/20

SECTION 8: Exposure controls/personal protection

STEL: 250 mg/m³ 15 minutes. Form: Risk for sensitisation
 STEL: 50 ppm 15 minutes. Form: Risk for sensitisation
 TWA: 100 mg/m³ 8 hours. Form: Risk for sensitisation
 TWA: 20 ppm 8 hours. Form: Risk for sensitisation

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
2-ethoxy-1-methylethyl acetate	DNEL	Long term Oral	13.1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	62 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	103 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	181 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	302 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	365 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	608 mg/m ³	Workers	Systemic
n-butyl acetate	DNEL	Long term Oral	3.4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3.4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	7 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	12 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	48 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	102.34 mg/m ³	General population	Local
	DNEL	Long term Inhalation	480 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	859.7 mg/m ³	General population	Local
	DNEL	Short term Inhalation	859.7 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	960 mg/m ³	Workers	Local
Reaction mass of ethylbenzene and xylene	DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	14.8 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	77 mg/m ³	Workers	Systemic

SECTION 8: Exposure controls/personal protection

4-methylpentan-2-one	DNEL	Inhalation Long term Dermal	108 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	289 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	289 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	4.2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	4.2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	11.8 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	14.7 mg/m ³	General population	Local
	DNEL	Long term Inhalation	14.7 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	83 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	83 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	155.2 mg/ m ³	General population	Local
	DNEL	Short term Inhalation	155.2 mg/ m ³	General population	Systemic
	DNEL	Short term Inhalation	208 mg/m ³	Workers	Local
	Hexanoic acid, 2-ethyl-, zinc salt, basic	DNEL	Short term Inhalation	208 mg/m ³	Workers
DNEL		Long term Oral	0.83 mg/ kg bw/day	General population	Systemic
DNEL		Long term Inhalation	2.5 mg/m ³	General population	Systemic
DNEL		Long term Dermal	3.21 mg/ kg bw/day	General population	Systemic
DNEL		Long term Inhalation	5 mg/m ³	Workers	Systemic
cumene	DNEL	Long term Dermal	6.41 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	1.2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	15.4 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	16.6 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	100 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	250 mg/m ³	Workers	Local

PNECs

No PNECs available.

8.2 Exposure controls

SECTION 8: Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
- The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
- The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid.
Color	: Green.
Odor	: Characteristic.
Odor threshold	: Not available.
pH	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: Not available.
Flash point	: Closed cup: 28°C
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Upper/lower flammability or explosive limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Highest known value: 4.6 (Air = 1) (2-methoxy-1-methylethyl acetate). Weighted average: 2.74 (Air = 1)
Density	: 1.138 g/cm ³
Solubility(ies)	: Insoluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): 9.67 cm ² /s Kinematic (40°C): 1.01 cm ² /s

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate	LC50 Inhalation Gas.	Rat	390 ppm	4 hours
	LC50 Inhalation Vapor	Mouse	6 g/m ³	2 hours
	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Intraperitoneal	Mouse	1230 mg/kg	-
	LD50 Oral	Guinea pig	4700 mg/kg	-
	LD50 Oral	Mouse	6 g/kg	-
	LD50 Oral	Rabbit	3200 mg/kg	-
	LD50 Oral	Rat	10768 mg/kg	-
Reaction mass of ethylbenzene and xylene	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LD50 Intraperitoneal	Guinea pig	800 mg/kg	-
	LD50 Intraperitoneal	Mouse	268 mg/kg	-
	LD50 Intraperitoneal	Rat	400 mg/kg	-
	LD50 Oral	Guinea pig	1600 mg/kg	-
	LD50 Oral	Mouse	1900 mg/kg	-
	LD50 Oral	Mouse	2850 mg/kg	-
	LD50 Oral	Rat	2080 mg/kg	-
	LD50 Oral	Rat	4600 mg/kg	-
	LD50 Oral	Rat	8500 mg/m ³	4 hours
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LC50 Inhalation Vapor	Rat	8500 mg/m ³	4 hours
	LD50 Oral	Rat	>6 g/kg	-
	LC50 Inhalation Vapor	Mouse	15300 mg/m ³	2 hours
	LC50 Inhalation Vapor	Mouse	10 g/m ³	7 hours
	LC50 Inhalation Vapor	Mouse	10000 mg/m ³	7 hours
	LC50 Inhalation Vapor	Rat	39000 mg/m ³	4 hours
	LD50 Dermal	Rabbit	12300 uL/kg	-
	LD50 Oral	Mouse	12750 mg/kg	-
	LD50 Oral	Rat	2.9 g/kg	-
	LD50 Oral	Rat	1400 mg/kg	-
cumene	LD50 Oral	Rat	>6 g/kg	-
	LC50 Inhalation Vapor	Mouse	15300 mg/m ³	2 hours
	LC50 Inhalation Vapor	Mouse	10 g/m ³	7 hours
	LC50 Inhalation Vapor	Mouse	10000 mg/m ³	7 hours
	LC50 Inhalation Vapor	Rat	39000 mg/m ³	4 hours
	LD50 Dermal	Rabbit	12300 uL/kg	-
	LD50 Oral	Mouse	12750 mg/kg	-
	LD50 Oral	Rat	2.9 g/kg	-
	LD50 Oral	Rat	1400 mg/kg	-

Conclusion/Summary : Not available.**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
n-butyl acetate	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
Reaction mass of ethylbenzene and xylene	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 UI	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
4-methylpentan-2-one	Skin - Moderate irritant	Rabbit	-	100 %	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 UI	-
	Eyes - Severe irritant	Rabbit	-	40 mg	-
cumene	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Mild irritant	Rabbit	-	86 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 10 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 100 mg	-

Date of issue/Date of revision : 1-10-2022

Version : 1

Date of previous issue : No previous validation

12/20

SECTION 11: Toxicological information

				mg	
--	--	--	--	----	--

Conclusion/Summary : Not available.

Sensitization

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2-ethoxy-1-methylethyl acetate	Category 3	-	Narcotic effects
n-butyl acetate	Category 3	-	Narcotic effects
2-methoxy-1-methylethyl acetate	Category 3	-	Narcotic effects
Reaction mass of ethylbenzene and xylene	Category 3	-	Respiratory tract irritation
4-methylpentan-2-one	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Reaction mass of ethylbenzene and xylene	Category 2	-	-

Aspiration hazard

Product/ingredient name	Result
Reaction mass of ethylbenzene and xylene	ASPIRATION HAZARD - Category 1
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Skin contact : May cause an allergic skin reaction.

Ingestion : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:
 nausea or vomiting
 headache
 drowsiness/fatigue
 dizziness/vertigo
 unconsciousness

SECTION 11: Toxicological information

Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Long term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
n-butyl acetate	Acute LC50 32 mg/l Marine water	Crustaceans - Artemia salina	48 hours
	Acute LC50 100000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 18000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 185000 µg/l Marine water	Fish - Menidia beryllina	96 hours
	Acute LC50 62000 µg/l Fresh water	Fish - Danio rerio	96 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
Reaction mass of ethylbenzene and xylene 4-methylpentan-2-one	Acute LC50 505000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 540000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 537000 µg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 78 mg/l Fresh water	Daphnia - Daphnia magna	21 days
cumene	Chronic NOEC 168 mg/l Fresh water	Fish - Pimephales promelas - Embryo	33 days
	Acute EC50 2600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 7.4 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 7.5 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours

Date of issue/Date of revision : 1-10-2022 **Version** : 1

Date of previous issue : No previous validation 14/20

SECTION 12: Ecological information

Acute EC50 10.6 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Acute EC50 10.6 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Acute EC50 11.2 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Acute LC50 7.4 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
Acute LC50 8 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
Acute LC50 20.3 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Acute LC50 20.3 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Acute LC50 6320 µg/l Fresh water	Fish - Pimephales promelas	96 hours
Acute LC50 5100 µg/l Fresh water	Fish - Poecilia reticulata	96 hours
Acute LC50 2700 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2-ethoxy-1-methylethyl acetate	0.76	-	low
n-butyl acetate	2.3	-	low
2-methoxy-1-methylethyl acetate	1.2	-	low
Reaction mass of ethylbenzene and xylene	3.12	8.1 to 25.9	low
4-methylpentan-2-one	1.9	-	low
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	10 to 2500	high
Hexanoic acid, 2-ethyl-, zinc salt, basic	-	60960	high
cumene	3.55	35.48	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances




Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3 	3 	3 
14.4 Packing group	III	III	III

Date of issue/Date of revision : 1-10-2022

Version : 1

Date of previous issue : No previous validation

16/20

AkzoNobel

SECTION 14: Transport information

14.5 Environmental hazards	No.	No.	No.
-------------------------------	-----	-----	-----

Additional information

ADR/RID : **Viscous liquid exception** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.
Tunnel code (D/E)

IMDG : **Emergency schedules** F-E, _S-E_
Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use Mixture : Not applicable.

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Seveso Directive

Date of issue/Date of revision : 1-10-2022 *Version* : 1

Date of previous issue : No previous validation 17/20

SECTION 15: Regulatory information

This product is controlled under the Seveso Directive.

Danger criteria**Category**

P5c

National regulations

Industrial use	: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.	
Social Security Code, Articles L 461-1 to L 461-7	: n-butyl acetate	RG 84
	: Reaction mass of ethylbenzene and xylene	RG 4bis, RG 84
	: 4-methylpentan-2-one	RG 84
	: cumene	RG 84
Reinforced medical surveillance	: Decree n ° 2012-135 of January 30, 2012 relating to the organization of occupational medicine: not applicable	

International regulations**Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Europe : Not determined.

15.2 Chemical Safety Assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

🔍 Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- SGG = Segregation Group
- vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Date of issue/Date of revision : 1-10-2022 **Version** : 1

Date of previous issue : No previous validation 18/20

SECTION 16: Other information

Classification	Justification
Flam. Liq. 3, H226 Skin Sens. 1, H317 STOT SE 3, H336 Aquatic Chronic 3, H412	On basis of test data Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	TOXIC TO REPRODUCTION - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1A	SKIN SENSITIZATION - Category 1A
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

Date of printing : 1 October 2022
Date of issue/ Date of revision : 1 October 2022
Date of previous issue : No previous validation
Version : 1
Unique ID :

Notice to reader

Date of issue/Date of revision : 1-10-2022 **Version** : 1
Date of previous issue : No previous validation 19/20

SECTION 16: Other information

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.