

SAFETY DATA SHEET

FR1-55 HARDENER

Section 1. Identification

Product identifier: FR1-55 HARDENERSDS code: 21055000D

Relevant identified uses of the substance or mixture and uses advised against

	Identified uses			
Paint. Professional use Ind	Paint. Professional use Industrial use			
	Uses advised against			
All other uses				
Product use	: Filler for interior use			
Supplier's details				
MAPAERO SAS 10, Avenue de la 09103 PAMIERS France				
Emergency telephone number (with hours of operation)	: +33 (0)5 34 01 34 01 +33 (0)5 61 60 23 30			
SECTION 2: Haz	ards identification			
Classification of the substance or mixture	: FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3			
GHS label elements				
Hazard pictograms				
Signal word	: Danger			
Hazard statements	 H227 - Combustible liquid. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H332 - Harmful if inhaled. H335 - May cause respiratory irritation. 			

Precautionary statements

SECTION 2: Hazards identification

Prevention	 P280 - Wear protective gloves. Wear eye or face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing vapor.
Response	 P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell. P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not : None known.

result in classification

SECTION 3: Composition/information on ingredients

Substance/mixture

Date of previous issue

: Mixture

Ingredient name	%	CAS number
✓examethylene diisocyanate, oligomers	≥25 - ≤50	28182-81-2
Polyisocyanate, aliphatic	≤10	-
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	≤10	2530-83-8

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

:1-10-2022

SECTION 4: First aid measures

Description of necessary first aid measures

Eye contact	flush eyes with pler Check for and remo	on immediately. Call a poison center or physician. Immediately ity of water, occasionally lifting the upper and lower eyelids. ove any contact lenses. Continue to rinse for at least 10 minutes. Ist be treated promptly by a physician.
Inhalation	victim to fresh air a suspected that fum or self-contained br respiratory arrest o It may be dangerou resuscitation. If un immediately. Main belt or waistband.	on immediately. Call a poison center or physician. Remove nd keep at rest in a position comfortable for breathing. If it is es are still present, the rescuer should wear an appropriate mask reathing apparatus. If not breathing, if breathing is irregular or if ccurs, provide artificial respiration or oxygen by trained personnel. Is to the person providing aid to give mouth-to-mouth conscious, place in recovery position and get medical attention tain an open airway. Loosen tight clothing such as a collar, tie, In case of inhalation of decomposition products in a fire, delayed. The exposed person may need to be kept under e for 48 hours.
Skin contact	plenty of soap and contaminated cloth Continue to rinse fo by a physician. In t	on immediately. Call a poison center or physician. Wash with water. Remove contaminated clothing and shoes. Wash ing thoroughly with water before removing it, or wear gloves. or at least 10 minutes. Chemical burns must be treated promptly he event of any complaints or symptoms, avoid further exposure. or reuse. Clean shoes thoroughly before reuse.
Date of issue/Date of revision	: 9-12-2022	Version : 1.01

2/11

AkzoNobe

SECTION 4: First	aid measures		
Ingestion	: Set medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.		
Most important symptoms/	· · · · · · · · · · · · · · · · · · ·		
Potential acute health effe			
Eye contact Inhalation	: Causes serious eye damage.		
Skin contact	 Harmful if inhaled. May cause respiratory irritation. May cause an allergic skin reaction. 		
Ingestion	: No known significant effects or critical hazards.		
<u>Over-exposure signs/sym</u>			
Eye contact	: Adverse symptoms may include the following:		
_,	pain watering redness		
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing		
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur		
Ingestion	: Adverse symptoms may include the following: stomach pains		
Indication of immediate me	dical attention and special treatment needed, if necessary		
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.		
Specific treatments	: No specific treatment.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.		

See toxicological information (Section 11)

SECTION 5: Firefighting measures

Extinguishing media			
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.		
Unsuitable extinguishing media	: Do not use water jet.		
Specific hazards arising from the chemical		noff to sewer may create fire or explosic crease will occur and the container may	
Date of issue/Date of revision	: 9-12-2022	Version : 1.01	
Date of previous issue	: 1-10-2022	3/11	AkzoNobel

SECTION 5: Firefighting measures

Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for

SECTION 7: Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment.
---------------------	--

emergency contact information and Section 13 for waste disposal.

Date of issue/Date of revision	: 9-12-2022	Version : 1.01
Date of previous issue	: 1-10-2022	4/11



SECTION 7: Handling and storage

	Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

SECTION 8: Exposure controls/personal protection

Control parameters **Occupational exposure limits** None. Appropriate engineering : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne controls contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. Emissions from ventilation or work process equipment should be checked to ensure Environmental exposure controls they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Individual protection measures Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. : Safety eyewear complying with an approved standard should be used when a risk Eye/face protection assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. Skin protection Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

Date of issue/Date of revision	: 9-12-2022	Version : 1.01	
Date of previous issue	: 1-10-2022	5/11	AkzoNobe

estimated.

SECTION 8: Exposure controls/personal protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	: Liquid.
Color	: Colorless.
Odor	: Characteristic.
Odor threshold	: Not available.
рН	∶ <mark>M</mark> ot available. [DIN EN 1262]
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: Not available.
Flash point	: ☑osed cup: 66°C (150.8°F) [Pensky-Martens]
Flammability	: Not available.
Lower and upper explosion limit/flammability limit	: Not available.
Vapor pressure	:

÷

Vapor pressure at 50°C Vapor Pressure at 20°C kPa Method kPa Method Ingredient name mm Hg mm Hg Polyisocyanate, aliphatic <825 <110 DPG-DME 0.93 7 0.0013 hexamethylene-di-isocyanate 0.01 0.0082 0.0011 [3-(2,3-epoxypropoxy)propyl] trimethoxysilane 0.000018 0.0000024 Hexamethylene diisocyanate, EU A.4 oligomers **Relative vapor density** : Not available. : 1.062 g/cm³ [DIN EN ISO 2811-1] Density Solubility(ies) ÷ Media Result cold water Not soluble [OESO (TG 105)] Partition coefficient: n-: Not applicable. octanol/water

Auto-ignition temperature

Ingredient name	°C	°F	Method
₽₽G-DME	165	329	
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	400	752	DIN 51794
hexamethylene-di-isocyanate	454	849.2	

Date of issue/Date of revision	: 9-12-2022	Version : 1.01	5. 5. I
Date of previous issue	: 1-10-2022	6/11	AkzoNobe

FR1-55 HARDENER	
SECTION 9: Physi	cal and chemical properties
Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): 56 mm²/s (56 cSt) [DIN EN ISO 3219] Kinematic (40°C (104°F)): 101 mm²/s (101 cSt) [DIN EN ISO 3219]
Particle characteristics Median particle size	: Not applicable.
SECTION 10: Stab	oility and reactivity
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Hexamethylene diisocyanate, oligomers	LC50 Inhalation Dusts and mists	Rat	18500 mg/m³	1 hours
[3-(2,3-epoxypropoxy)propyl] trimethoxysilane	LD50 Dermal	Rabbit	3970 uL/kg	-
,	LD50 Oral	Rat	7.01 g/kg	-
	LD50 Oral	Rat	22600 uL/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
✓examethylene diisocyanate, oligomers	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	500 mg	-
[3-(2,3-epoxypropoxy)propyl] trimethoxysilane	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

SECTION 11: Toxicological information

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name		Category	Route of exposure	Target organs
Hexamethylene diisocyanate	Category 3	-	Respiratory tract irritation	
Specific target organ toxic Not available.	ity (repeated exposu	re)	•	•
Aspiration hazard Not available.				
Information on the likely routes of exposure	: Not available.			
Potential acute health effect	<u>ts</u>			
Eye contact	: Causes serious e	eye damage.		
Inhalation	: Harmful if inhaled	d. May cause respiratory	irritation.	
Skin contact	: May cause an all	ergic skin reaction.		
Ingestion	: No known signific	cant effects or critical haz	ards.	
Symptoms related to the ph	ysical, chemical and	toxicological character	ristics	
Eye contact	: Adverse sympton pain watering redness	ns may include the follow	ving:	
Inhalation	: Adverse sympton respiratory tract in coughing	ns may include the follow rritation	<i>r</i> ing:	
Skin contact	: Adverse sympton pain or irritation redness blistering may oc	ns may include the follow cur	ring:	
Ingestion		ns may include the follow	ing:	
Delayed and immediate effe	cts and also chronic	effects from short and	long term exposi	ure
Short term exposure				
Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
Long term exposure				
Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
Potential chronic health ef	<u>fects</u>			
Not available.				
General	: Once sensitized, to very low levels	a severe allergic reactior	n may occur when	subsequently exposed
Carcinogenicity	•	cant effects or critical haz	ards.	
Date of issue/Date of revision	: 9-12-2022	Ve	ersion : 1.01	
				AkzoNob

SECTION 11: Toxicological information

Mutagenicity

: No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

SECTION 12: Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
✓examethylene diisocyanate, oligomers	5.54	367.7	low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers

SECTION 14: Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.



SECTION 14: Transport information

	Mexico Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Additional information

IMDG

: MDG Code Segregation group Not applicable

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

SECTION 15: Regulatory information

SECTION 16: Other information

<u>History</u>	
Date of printing	: 9 December 2022
Date of issue/ Date of revision	: 9 December 2022
Date of previous issue	: 1 October 2022
Version	: 1.01
Unique ID	:
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Procedure used to derive the classification

SECTION 16: Other information

Classification	Justification
AMMABLE LIQUIDS - Category 4	On basis of test data
ACUTE TOXICITY (inhalation) - Category 4	Calculation method
SERIOUS EYE DAMAGE - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method

Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision	: 9-12-2022	Version : 1.01	
Date of previous issue	: 1-10-2022	11/11	AkzoNobel