

# SAFETY DATA SHEET

FR4-45 BASE CREAM

## **SECTION 1: Identification of the substance/mixture and of the company/** undertaking

1.1 Product identifier	
Product name	: FR4-45 BASE CREAM
SDS code	: 64000300B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses
Waterborne paint. Profes	ssional use Industrial use
	Uses advised against
All other uses	
Product use	: Filler for interior use
1.3 Details of the supplie	r of the safety data sheet
MAPAERO SAS	
10, Avenue de la 09103 PAMIERS	,
France	Oedex
e-mail address of perso	n : PSRA_PAMIERS@akzonobel.com
responsible for this SD	\$
1.4 Emergency telephone	e number
National advisory body	Poison Center
Telephone number	: 0213183606
<u>Supplier</u>	

Supplier	
Telephone number	: +33 (0)5 34 01 34 01
	+33 (0)5 61 60 23 30
Hours of operation	:

## **SECTION 2: Hazards identification**

.1 Classification of the s	substance or mixture
Product definition	: Mixture
Classification according	g to Regulation (EC) No. 1272/2008 [CLP/GHS]
Skin Sens. 1, H317	
Aquatic Chronic 3, H412	
The product is classified a	as hazardous according to Regulation (EC) 1272/2008 as amended.
See Section 16 for the ful	I text of the H statements declared above.
See Section 11 for more (	detailed information on health effects and symptoms.

Date of issue/Date of revision	: 9-12-2022	Version : 2	
Date of previous issue	: 7-12-2022	1/15	AkzoNobel

FR4-45 BASE CREAM

<b>SECTION 2: Hazards</b>	ic	lentification
2.2 Label elements		
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Wear protective gloves. Avoid release to the environment. Avoid breathing vapor.
Response	:	Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	✓,2-benzisothiazol-3(2H)-one C(M)IT/MIT(3:1)
Supplemental label elements	:	$\overline{W}$ arning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture					
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
√2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5	≤0.1	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
Date of issue/Date of revision	: 9-12-2022		Version : 2		
Date of previous issue	: 7-12-2022		2/15	Akzo	Nobel

EDA AE DASE ODEAM

	F	R4-45 BASE	- CREAM		
SECTION 3: Co	mposition/informat	ion on	ingredients		
C(M)IT/MIT(3:1)	REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5	≤0.1	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Corr. 1C, H314: C $\geq$ 0.6% Skin Irrit. 2, H315: 0.06% $\leq$ C < 0.6% Skin Sens. 1, H317: C $\geq$ 0.0015% M [Acute] = 100 M [Chronic] = 100	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower Eve contact evelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs. Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Skin contact Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. : Wash out mouth with water. Remove dentures if any. If material has been Ingestion swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Date of issue/Date of revision	: 9-12-2022	Version : 2	
Date of previous issue	: 7-12-2022	3/15	AkzoNobel

FR4-45 BASE CREAM

### **SECTION 4: First aid measures**

#### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, C(M)IT/MIT(3:1). May produce an allergic reaction.

#### Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.

### **SECTION 5: Firefighting measures**

<u> </u>		
5.1 Extinguishing media		
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	None known.	
5.2 Special hazards arising	from the substance or mixture	
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.	
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides	
5.3 Advice for firefighters Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	

Date of issue/Date of revision	: 9-12-2022	Version : 2	
Date of previous issue	: 7-12-2022	4/15	AkzoNobel

### **SECTION 5: Firefighting measures**

Special protective equipment for fire-fighters	b n c	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure node. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
---	-------------	---

### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responder	rs : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and materials	for containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and

collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
 6.4 Reference to other sections
 See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	history of skin sensitiza which this product is us Avoid breathing vapor original container or an	sonal protective equipment (see Section 8). Persons v ation problems should not be employed in any process sed. Do not get in eyes or on skin or clothing. Do not or mist. Avoid release to the environment. Keep in the approved alternative made from a compatible materia t in use. Empty containers retain product residue and o use container.	in ingest. e al, kept
Advice on general occupational hygiene	handled, stored and pr eating, drinking and sm	noking should be prohibited in areas where this materia ocessed. Workers should wash hands and face befor noking. Remove contaminated clothing and protective ring eating areas. See also Section 8 for additional e measures.	re
Date of issue/Date of revision	· 0-12-2022	Version :2	

Date of issue/Date of revision	: 9-12-2022	Version : 2
Date of previous issue	: 7-12-2022	5/15



## **SECTION 7: Handling and storage**

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### **Occupational exposure limits**

No exposure limit value known.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient na	ame Type	Exposure	Value	Population	Effects
2-benzisothiazol-3(2H)-on	e DNEL	Long term Dermal	0.345 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.966 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m³	Workers	Systemic
C(M)IT/MIT(3:1)	DNEL	Long term Inhalation	0.02 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	0.02 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	0.04 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	0.04 mg/m <sup>3</sup>		Local
	DNEL	Long term Oral	0.09 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.11 mg/ kg bw/day	General population	Systemic
e of issue/Date of revision	: 9-12-2022		Version	:2	
e of previous issue	: 7-12-2022		6/15		AkzoNob

## **SECTION 8: Exposure controls/personal protection**

#### **PNECs**

No PNECs available.

8.2 Exposure controls	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	ures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

: Liquid.
i Liquiu.
: White.
: Characteristic.

Date of issue/Date of revision	: 9-12-2022	Version : 2	
Date of previous issue	: 7-12-2022	7/15	AkzoNobel

Odor threshold	: Not a	vailable.				
lelting point/freezing poi	nt : Nota	vailable.				
nitial boiling point and oiling range	: Not a	vailable.				
lammability	: Not a	vailable.				
ower and upper explosio mit	n : Nota	vailable.				
lash point	: 🕅	ed cup: 105°0	C (221°F) [Pensky	/-Martens]		
uto-ignition temperature	:					
Ingredient name		°C	°F	ſ	Nethod	
2 <sup>2</sup> butoxyethanol		230	446	[	DIN 51794	
Paraffin waxes and Hydrocarbon	waxes	244.85	472.7			
Ethene, homopolymer		330 to 410	626 to 77	D		
dodecamethylcyclohexasiloxane		368 to 371	694.4 to 6	99.8		
decamethylcyclopentasiloxane		372	701.6		ASTM E 659-78	
N,N'-ethylenedi(stearamide)		380	716	1	DIN 51794	
octamethylcyclotetrasiloxane		384 to 387	723.2 to 7	28.6	ASTM E 659	
ammonia, anhydrous		651	1203.8			
Media pold water	: Res Sol	sult uble [OESO (	201 mm²/s [DIN (TG 105)]		N EN ISO 321 19]	·
Media Pold water artition coefficient: n-oct vater	: Res Sol	sult				·
Media pold water artition coefficient: n-oct vater	: Res Sol anol/ : Not a :	sult uble [OESO (	(TG 105)]			
Media Fold water artition coefficient: n-oct vater apor pressure	: Res Sol anol/ : Not a :	sult uble [OESO ( upplicable.	(TG 105)]		19]	
Media Fold water artition coefficient: n-oct vater apor pressure	: Res Sol anol/ : Not a : Va	sult uble [OESO ( upplicable. por Pressure	(TG 105)] e at 20°C	EN ISO 321	I9] Vapor press	sure at 50°C
Media Fold water artition coefficient: n-oct rater apor pressure Ingredient name	: Res Sol anol/ : Not a : Va mm Hg	sult uble [OESO ( pplicable. por Pressure kPa	(TG 105)] e at 20°C	EN ISO 321	I9] Vapor press	sure at 50°C
Media Fold water artition coefficient: n-oct vater apor pressure Ingredient name Frimonia, anhydrous	: Res Sol anol/ : Not a : Va mm Hg 72.31	sult uble [OESO ( applicable. por Pressure kPa 9.6	(TG 105)] e at 20°C	EN ISO 321	I9] Vapor press	sure at 50°C
Media Fold water artition coefficient: n-oct vater apor pressure Ingredient name primonia, anhydrous octamethylcyclotetrasiloxane	: Res Sol anol/ : Mot a : Va mm Hg 72.31 0.99	sult uble [OESO ( pplicable. por Pressure kPa 9.6 0.13	(TG 105)] e at 20°C	EN ISO 321	I9] Vapor press	sure at 50°C
Media Fold water artition coefficient: n-oct vater apor pressure Ingredient name mmonia, anhydrous octamethylcyclotetrasiloxane 2-butoxyethanol	: Res Sol anol/ : Not a : Va <u>mm Hg</u> 72.31 0.99 0.75	sult uble [OESO ( pplicable. por Pressure kPa 9.6 0.13 0.1	(TG 105)] e at 20°C	EN ISO 321	I9] Vapor press	sure at 50°C
Media Cold water artition coefficient: n-oct vater apor pressure Ingredient name mmonia, anhydrous octamethylcyclotetrasiloxane 2-butoxyethanol Polyether modified siloxane	: Res Sol anol/ : Not a : Va mm Hg 72.31 0.99 0.75 0.75	sult uble [OESO ( pplicable. por Pressure 9.6 0.13 0.1 0.1	(TG 105)] e at 20°C	EN ISO 321	I9] Vapor press	sure at 50°C
Media Cold water Cold water Cartition coefficient: n-oct vater Capor pressure Ingredient name Cartinonia, anhydrous octamethylcyclotetrasiloxane 2-butoxyethanol Polyether modified siloxane decamethylcyclopentasiloxane	: Res Sol anol/ : Not a : Va mm Hg 72.31 0.99 0.75 0.75 0.75 0.25	sult uble [OESO ( pplicable. por Pressure kPa 9.6 0.13 0.1 0.1 0.1 0.1 0.033	(TG 105)] e at 20°C	EN ISO 321	I9] Vapor press	sure at 50°C
Media Cold water Cartition coefficient: n-oct vater Capor pressure Ingredient name Camethylcyclotetrasiloxane 2-butoxyethanol Polyether modified siloxane decamethylcyclopentasiloxane aluminium hydroxide	: Res Sol anol/ : Not a : Va mm Hg 72.31 0.99 0.75 0.75 0.25 <0.075	sult uble [OESO ( pplicable. por Pressure kPa 9.6 0.13 0.1 0.1 0.1 0.1 0.033 <0.01	(TG 105)] e at 20°C	EN ISO 321	I9] Vapor press	sure at 50°C
Media Cold water Partition coefficient: n-oct vater Papor pressure Ingredient name Physical Stress Stress Stress Physical Stress Str	: Res Sol anol/ : Not a : Va mm Hg 72.31 0.99 0.75 0.75 0.75 0.25 <0.075 0.00087	sult uble [OESO ( pplicable. por Pressure 9.6 0.13 0.1 0.1 0.1 0.033 <0.01 0.00012	(TG 105)] e at 20°C Method	EN ISO 321	I9] Vapor press	sure at 50°C
Media Poly of the second seco	: Res Sol anol/ : Not a : Va mm Hg 72.31 0.99 0.75 0.75 0.75 0.25 <0.075 0.25 <0.075 0.00087 <0.0000075 0.0000075 0	sult uble [OESO ( pplicable. por Pressure kPa 9.6 0.13 0.1 0.1 0.1 0.033 <0.01 0.00012 <0.0000001 0 8 g/cm <sup>3</sup> [DIN	(TG 105)] e at 20°C Method	EN ISO 321	I9] Vapor press	sure at 50°C
Media Cold water Cold	: Res Sol anol/ : Not a : Va mm Hg 72.31 0.99 0.75 0.75 0.75 0.25 <0.075 0.25 <0.075 0.00087 <0.0000075 0.0000075 0	sult uble [OESO ( pplicable. por Pressure kPa 9.6 0.13 0.1 0.1 0.1 0.033 <0.01 0.00012 <0.0000001 0	(TG 105)] e at 20°C Method	EN ISO 321	I9] Vapor press	sure at 50°C
Media         Fold water         Partition coefficient: n-oct vater         Papor pressure         Ingredient name         Imgredient name         Immonia, anhydrous         octamethylcyclotetrasiloxane         2-butoxyethanol         Polyether modified siloxane         decamethylcyclopentasiloxane         aluminium hydroxide         N,N'-ethylenedi(stearamide)         1,1'-(ethane-1,2-diyl)bis         [pentabromobenzene]         propylidynetrimethanol         Density         Yapor density	: Res Sol anol/ : Not a : Va mm Hg 72.31 0.99 0.75 0.75 0.75 0.25 <0.075 0.25 <0.075 0.00087 <0.0000075 0.0000075 0	sult uble [OESO ( pplicable. por Pressure kPa 9.6 0.13 0.1 0.1 0.1 0.033 <0.01 0.00012 <0.0000001 0 8 g/cm <sup>3</sup> [DIN	(TG 105)] e at 20°C Method	EN ISO 321	I9] Vapor press	sure at 50°C
Partition coefficient: n-oct water /apor pressure /apor pressure /monia, anhydrous octamethylcyclotetrasiloxane 2-butoxyethanol Polyether modified siloxane decamethylcyclopentasiloxane aluminium hydroxide N,N'-ethylenedi(stearamide) 1,1'-(ethane-1,2-diyl)bis [pentabromobenzene]	: Res Sol anol/ : Not a : Va mm Hg 72.31 0.99 0.75 0.75 0.75 0.25 <0.075 0.25 <0.075 0.00087 <0.0000075 0.0000075 0	sult           uble [OESO (           pplicable.           por Pressure           kPa           9.6           0.13           0.1           0.13           0.1           0.033           <0.01	(TG 105)] e at 20°C Method	EN ISO 321	Vapor press kPa	sure at 50°C

FR4-45 BASE CREAM

SECTION 9: Physical and chemical properties			
Median particle size	: Not applicable.		
SECTION 10: Stabilit	and reactivity		
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	: The product is stable.		
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.		
10.4 Conditions to avoid	: No specific data.		
10.5 Incompatible materials	: No specific data.		

**10.6 Hazardous** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
,2-benzisothiazol-3(2H)-	LD50 Oral	Mouse	1150 mg/kg	-
one	LD50 Oral	Rat	1020 mg/kg	-
Conclusion/Summary	: Not available.			
Irritation/Corrosion				
Conclusion/Summary	: Not available.			
<u>Sensitization</u>				
Conclusion/Summary	: Not available.			
<u>Mutagenicity</u>				
Conclusion/Summary	: Not available.			
<b>Carcinogenicity</b>				
Conclusion/Summary	: Not available.			
Reproductive toxicity				
Conclusion/Summary	: Not available.			
<u>Teratogenicity</u>				
Conclusion/Summary	: Not available.			
Specific target organ toxicity	<u>(single exposure)</u>			
Not available.				
Specific target organ toxicity	(repeated exposure)			
Not available.				

#### Aspiration hazard

Not available.

Date of issue/Date of revision	: 9-12-2022	Version : 2	
Date of previous issue	: 7-12-2022	9/15	AkzoNobel

FR4-45 BASE CREAM

SECTION 11: Toxico	ological information
Information on the likely routes of exposure	: Not available.
Potential acute health effect	<u>s</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph	vsical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Delayed and immediate effe Short term exposure Potential immediate effects	cts and also chronic effects from short and long term exposure : Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	fects
Not available.	
Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

#### 11.2 Information on other hazards

11.2.1 Endocrine disrupting propertiesNot available.11.2.2 Other information

Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Date of issue/Date of revision	: 9-12-2022	Version : 2	
Date of previous issue	: 7-12-2022	10/15	AkzoNobel

## **SECTION 12: Ecological information**

Product/ingredient name	Result	Species	Exposure
,2-benzisothiazol-3(2H)-one	Acute EC50 97 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2.24 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 3.7 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 1.1 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 10 to 20 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 540 ppb Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 167 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 0.75 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.6 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

**Conclusion/Summary** : Not available.

#### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

#### 12.3 Bioaccumulative potential

Not available.

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.

Date of issue/Date of revision	: 9-12-2022	Version : 2	
Date of previous issue	: 7-12-2022	11/15	AkzoNobel

## **SECTION 13: Disposal considerations**

Disposal considerations	: Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no
	longer apply and the appropriate code should be assigned.
	For further information, contact your local waste authority.

#### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation	
EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11	
Packaging		
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.	
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.	

## **SECTION 14: Transport information**

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information         IMDG       : MDG Code Segregation group         Not applicable			
<b>14.6 Special precautions for user</b> : <b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.			

**14.7 Maritime transport in** : Not applicable. **bulk according to IMO instruments** 

SECTION 15: Regula	tory information
15.1 Safety, health and enviro EU Regulation (EC) No. 190	onmental regulations/legislation specific for the substance or mixture 7/2006 (REACH)
Annex XIV - List of substan	nces subject to authorization
Annex XIV	
None of the components a	
Substances of very high	
None of the components a	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Other EU regulations	
VOC	: The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.
VOC for Ready-for-Use Mixture	: Not available.
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed
Ozone depleting substanc Not listed.	<u>es (1005/2009/EU)</u>
Prior Informed Consent (P	IC) (649/2012/EU)
Not listed.	
Persistent Organic Polluta Not listed.	ints
Seveso Directive	
	d under the Seveso Directive.
National regulations	
Industrial use	: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.
International regulations	
-	ion List Schedules I, II & III Chemicals
Not listed.	
Montreal Protocol	
Not listed.	
Stockholm Convention on F Not listed.	Persistent Organic Pollutants
Data of incurs (Data of musician	10.40.2000

Version : 2

13/15

AkzoNobel

Date of issue/Date of revision

Date of previous issue

:9-12-2022

:7-12-2022

FR4-45 BASE CREAM

## **SECTION 15: Regulatory information**

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

### Inventory list

Eurasian Economic Union : Russian Federation inventory: Not determined.

Assessment

## **SECTION 16: Other information**

🔽 Ind	dicates information	that has changed fro	om previously issued version.
-------	---------------------	----------------------	-------------------------------

Abbreviations and acronyms       : ATE = Acute Toxicity Estimate         CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]         DMEL = Derived Minimal Effect Level         DNEL = Derived No Effect Level         EUH statement = CLP-specific Hazard statement         N/A = Not available         DRT = Derivet Disconstruction
1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available
DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available
DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available
EUH statement = CLP-specific Hazard statement N/A = Not available
N/A = Not available
DDT - Deviatent Diseasury dative and Taxia
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

#### Full text of abbreviated H statements

<b>F</b> 301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

#### Full text of classifications [CLP/GHS]

Date of issue/Date of revision	: 9-12-2022	Version : 2 14/15	AkzoNobel
Eye Dam. 1 Skin Corr. 1C Skin Irrit. 2		SERIOUS EYE DAMAGE/ EYE IRRITATION - C SKIN CORROSION/IRRITATION - Category 1C SKIN CORROSION/IRRITATION - Category 2	ategory 1
Aquatic Chronic 3		AQUATIC HAZARD (LONG-TERM) - Category 3	
Aquatic Chronic 2		AQUATIC HAZARD (LONG-TERM) - Category 2	
Aquatic Chronic 1		AQUATIC HAZARD (LONG-TERM) - Category 1	
Aquatic Acute 1		AQUATIC HAZARD (ACUTE) - Category 1	
Acute Tox. 4		ACUTE TOXICITY - Category 4	
Acute Tox. 3		ACUTE TOXICITY - Category 3	
Acute Tox. 2		ACUTE TOXICITY - Category 2	

SECTION 16: Other information				
Skin Sens. 1 Skin Sens. 1A	SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A			
Date of printing	: 9 December 2022			
Date of issue/ Date of revision	: 9 December 2022			
Date of previous issue	: 7 December 2022			
Version	: 2			
Unique ID	:			

#### Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision
Date of previous issue

