

SAFETY DATA SHEET

P65-C BASE BEIGE RAL 1001

In accordance with the Standard for Classification and Labeling of Chemical Substance and Safety Data Sheet, Article 10 Paragraph 1

| l | | | |
|--|--|--|--|
| Section 1. Chemical product and company identification | | | |
| A. Product name | A. Product name : P65-C BASE BEIGE RAL 1001 | | |
| SDS code | : 21165100B | | |
| | | | |
| B. <u>Relevant identified uses</u> | of the substance or mixture and uses advised against | | |
| | Identified uses | | |
| Waterborne paint. Profession | al use Industrial use | | |
| Uses advised against | | | |
| All other uses | | | |
| Product use | : Waterborne primer | | |
| C. Supplier's details | | | |
| MAPAERO SAS | | | |
| 10, Avenue de la Rijo | | | |
| 09103 PAMIERS Ce France | dex | | |
| e-mail address of person responsible for this SDS | : PSRA_PAMIERS@akzonobel.com | | |
| Emergency telephone number (with hours of operation) | : +33 (0)5 34 01 34 01 +33 (0)5 61 60 23 30 | | |

Section 2. Hazards identification

| A. Hazard classification SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 CARCINOGENICITY - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 2 This product is classified in accordance with the Industrial Safety and Health A and the Chemical Control Act. | Act |
|--|-----|
|--|-----|

B. GHS label elements, including precautionary statements



Signal word

: Danger



Section 2. Hazards identification

| Hazard statements | : | H315 - Causes skin irritation. |
|--------------------------|---|--|
| | | H318 - Causes serious eye damage. |
| | | H351 - Suspected of causing cancer. |
| | | H411 - Toxic to aquatic life with long lasting effects. |
| Precautionary statements | 5 | |
| Prevention | : | P201 - Obtain special instructions before use. |
| | | P280 - Wear protective gloves, protective clothing and eye or face protection. |
| | | P273 - Avoid release to the environment. |
| | | P264 - Wash hands thoroughly after handling. |
| Response | : | P391 - Collect spillage. |
| - | | P308 + P313 - IF exposed or concerned: Get medical advice or attention. |
| | | P362 + P364 - Take off contaminated clothing and wash it before reuse. |
| | | P302 + P352 - IF ON SKIN: Wash with plenty of water. |
| | | P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several |
| | | minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| | | Immediately call a POISON CENTER or doctor. |
| Storage | : | Not applicable. |
| Disposal | : | P501 - Dispose of contents and container in accordance with all local, regional, |
| - | | national and international regulations. |
| | | |
| Other hazards which do | : | None known. |
| not result in | | |

```
classification
```

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

| Ingredient name | Identifiers | % |
|--|-----------------|-----------|
| titanium dioxide | CAS: 13463-67-7 | ≥10 - <15 |
| butan-2-ol | CAS: 78-92-2 | ≥10 - <15 |
| Polyaminoamide | - | <10 |
| chromium orthophosphate | CAS: 7789-04-0 | <10 |
| trizinc bis(orthophosphate) | CAS: 7779-90-0 | ≥1 - <5 |
| iron hydroxide oxide | CAS: 20344-49-4 | ≥1 - <5 |
| Amines, polyethylenepoly-, triethylenetetramine fraction | CAS: 90640-67-8 | <10 |
| zinc oxide | CAS: 1314-13-2 | ≥1 - <5 |
| Boric acid, zinc salt | CAS: 1332-07-6 | ≥0.3 - <5 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

| Α. | Eye contact | : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. |
|----|--------------|--|
| В. | Skin contact | : Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse. |



Section 4. First aid measures

| C. | Inhalation | : | Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
|----|----------------------------|---|---|
| D. | Ingestion | : | Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Е. | Notes to physician | : | In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| | Specific treatments | : | No specific treatment. |
| | Protection of first-aiders | : | No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

See toxicological information (Section 11)

Section 5. Fire-fighting measures

| Α. | Extinguishing media | | | | |
|-----|---|---|--|---|-----------|
| | Suitable extinguishing media | : | Use an extinguishing agent suitable for | the surrounding fire. | |
| | Unsuitable extinguishing media | : | None known. | | |
| В. | Specific hazards arising from the chemical | : | In a fire or if heated, a pressure increas This material is toxic to aquatic life with contaminated with this material must be discharged to any waterway, sewer or o | l long lasting effects. Fire we contained and prevented | vater |
| | Hazardous thermal decomposition products | : | Decomposition products may include the carbon dioxide carbon monoxide nitrogen oxides phosphorus oxides metal oxide/oxides | ne following materials: | |
| C. | Special protective equipment for fire- fighters | : | Fire-fighters should wear appropriate p breathing apparatus (SCBA) with a full mode. | | |
| Dat | e of issue/Date of revision | | : 27-10-2022 | Version : 1.03 | |
| Dat | e of previous issue | | : 6-10-2022 | 3/13 | AkzoNobel |
| | | | | | |

Section 5. Fire-fighting measures

| Special precautions for | : Promptly isolate the scene by removing all persons from the vicinity of the incident if |
|-------------------------|---|
| fire-fighters | there is a fire. No action shall be taken involving any personal risk or without |
| | suitable training. |

Section 6. Accidental release measures

| Α. | Personal precautions, | : | No action shall be taken involving any personal risk or without suitable training. |
|----|-----------------------|---|---|
| | protective equipment | | Evacuate surrounding areas. Keep unnecessary and unprotected personnel from |
| | and emergency | | entering. Do not touch or walk through spilled material. Do not breathe vapor or |
| | procedures | | mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is |
| | | | inadequate. Put on appropriate personal protective equipment. |

B. Environmental precautions
 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

C. Methods and materials for containment and cleaning up

| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
|-------------|--|
| Large spill | licensed waste disposal contractor. : Stop leak if without risk. Move containers from spill area. Approach release from |
| | |

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

| Α. | Precautions for safe hand | ling |
|----|--|--|
| | Protective measures | : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
| | Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| В. | Conditions for safe storage, including any incompatibilities | : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |



Section 8. Exposure controls/personal protection

A. <u>Control parameters</u>

Occupational exposure limits

| Ingredient name | Exposure limits |
|-----------------------|---|
| iffanium dioxide | Ministry of Employment and Labor (Republic of Korea, 1/2020). |
| | TWA: 10 mg/m³ 8 hours. Form: total dust |
| | with less than 1% of free SiO2 |
| butan-2-ol | Ministry of Employment and Labor |
| | (Republic of Korea, 1/2020). |
| | STEL: 150 ppm 15 minutes. |
| | TWA: 100 ppm 8 hours. |
| Boric acid, zinc salt | ACGIH TLV (United States, 3/2020). |
| | TWA: 2 mg/m ³ 8 hours. Form: Inhalable |
| | fraction |
| | STEL: 6 mg/m³ 15 minutes. Form: Inhalable fraction |

| В. | Appropriate engineering controls | : | If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. |
|----|------------------------------------|---|---|
| | Environmental exposure controls | : | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |

C. Personal protective equipment

| Respiratory protection | : | Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. |
|------------------------|---|---|
| Eye protection | : | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. |
| Hand protection | : | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Body protection | : | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Hygiene measures | : | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |



Section 9. Physical and chemical properties

| Α. | <u>Appearance</u> | | |
|----|--|---|--|
| | Physical state | : | Liquid. |
| | Color | : | White. |
| В. | Odor | : | Characteristic. |
| C. | Odor threshold | : | Not available. |
| D. | рН | : | Not available. |
| Ε. | Melting/freezing point | : | Not available. |
| F. | Boiling point/boiling range | : | Not available. |
| G. | Flash point | : | Closed cup: 101°C (213.8°F) |
| | Fire point | : | Not available. |
| Н. | Evaporation rate | : | Not available. |
| I. | Flammability (solid, gas) | : | Not available. |
| J. | Lower and upper explosive (flammable) limits | : | Greatest known range: Lower: 1.7% Upper: 9% (butan-2-ol) |
| K. | Vapor pressure | : | Not available. |
| L. | Solubility | : | Insoluble in the following materials: cold water. |
| | Solubility in water | : | Not available. |
| Μ. | Vapor density | : | Highest known value: 2.55 (Air = 1) (butan-2-ol). |
| Ν. | Density | : | 1.259 g/cm³ |
| О. | Partition coefficient: n- octanol/water | : | Not available. |
| Ρ. | Auto-ignition temperature | : | Not available. |
| Q. | Decomposition temperature | : | Not available. |
| R. | Viscosity | : | Kinematic (room temperature): 5.24 cm²/s (524 cSt) Kinematic (40°C (104°F)): 2.01 cm²/s (201 cSt) |
| | Flow time (ISO 2431) | : | Not available. |
| S. | Molecular weight | : | Not applicable. |

Section 10. Stability and reactivity

| Α. | Chemical stability | : | The product is stable. |
|----|---------------------------------------|---|--|
| | Possibility of hazardous reactions | : | Under normal conditions of storage and use, hazardous reactions will not occur. |
| В. | Conditions to avoid | : | No specific data. |
| C. | Incompatible materials | : | No specific data. |
| D. | Hazardous decomposition products | : | Under normal conditions of storage and use, hazardous decomposition products should not be produced. |



Section 11. Toxicological information

A. Information on the likely : Not available. routes of exposure

Potential acute health effects

| <u>CTS</u> |
|--|
| : No known significant effects or critical hazards. |
| : No known significant effects or critical hazards. |
| : Causes skin irritation. |
| : Causes serious eye damage. |
| <u>otoms</u> |
| : No specific data. |
| : Adverse symptoms may include the following: stomach pains |
| : Adverse symptoms may include the following: pain or irritation redness blistering may occur |
| : Adverse symptoms may include the following: pain watering redness |
| |

B. Health hazards

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-----------------------------|-----------------------|------------|-------------------------|----------|
| butan-2-ol | LC50 Inhalation Gas. | Rat | 8000 ppm | 4 hours |
| | LC50 Inhalation Vapor | Rat | 48500 mg/m ³ | 4 hours |
| | LD50 Intraperitoneal | Guinea pig | 1067 mg/kg | - |
| | LD50 Intraperitoneal | Mouse | 771 mg/kg | - |
| | LD50 Intraperitoneal | Rabbit | 277 mg/kg | - |
| | LD50 Intraperitoneal | Rat | 1193 mg/kg | - |
| | LD50 Intravenous | Mouse | 764 mg/kg | - |
| | LD50 Intravenous | Rat | 138 mg/kg | - |
| | LD50 Oral | Rabbit | 4893 mg/kg | - |
| | LD50 Oral | Rabbit | 4890 mg/kg | - |
| | LD50 Oral | Rat | 2193 mg/kg | - |
| | LD50 Oral | Rat | 2054 mg/kg | - |
| trizinc bis(orthophosphate) | LD50 Intraperitoneal | Mouse | 552 mg/kg | - |
| | LD50 Intraperitoneal | Rat | 551 mg/kg | - |
| zinc oxide | LD50 Intraperitoneal | Rat | 240 mg/kg | - |
| | LD50 Oral | Mouse | 7950 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--------------------------|--|------------------|-------|------------------------------|-------------|
| ቓutan-2-ol zinc oxide | Eyes - Severe irritant Eyes - Mild irritant | Rabbit Rabbit | - | 0.1 MI 24 hours | - |
| | Skin - Mild irritant | Rabbit | - | 500 mg 24 hours 500 mg | - |

Sensitization

Not available.

CMR - ISHA Article 42 Occupational Exposure Limits

| Product/ingredient name | Identifiers | Classification |
|-------------------------|-----------------|------------------------------|
| titanium dioxide | CAS: 13463-67-7 | CARCINOGENICITY - Category 2 |

| Date of issue/Date of revision | : 27-10-2022 | Version : 1.03 | |
|--------------------------------|--------------|----------------|-----------|
| Date of previous issue | : 6-10-2022 | 7/13 | AkzoNobel |

Section 11. Toxicological information

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP | ACGIH |
|-------------------------|------|------|-----|-------|
| titanium dioxide | - | 2B | | A4 |
| chromium orthophosphate | - | 3 | | A4 |
| Boric acid, zinc salt | - | - | | A4 |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Name | 0, | Route of exposure | Target organs |
|------------|------------|----------------------|---------------------------------|
| butan-2-ol | Category 3 | | Respiratory tract irritation |
| | Category 3 | | Narcotic effects |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Potential chronic health effects

Chronic toxicity

Not available.

| General | : No known significant effects or critical hazards. |
|-----------------------|--|
| Carcinogenicity | : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Reproductive toxicity | : No known significant effects or critical hazards. |

Section 12. Ecological information

A. Ecotoxicity

| Product/ingredient name | Result | Species | Exposure |
|---------------------------|------------------------------------|---|----------|
| titanium dioxide | Acute EC50 19.3 mg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute EC50 27.8 mg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute EC50 35.306 mg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| | Acute LC50 3 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 13.4 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 11 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 3.6 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| of issue/Date of revision | : 27-10-2022 | Version : 1.03 | |
| of previous issue | : 6-10-2022 | 8/13 | AkzoNobe |

Section 12. Ecological information

| 0 | | | |
|-----------------------------|---------------------------------------|---|----------|
| | Acute LC50 15.9 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 6.5 mg/l Fresh water | Daphnia - Daphnia pulex - | 48 hours |
| | | Neonate | |
| | Acute LC50 13 mg/l Fresh water | Daphnia - Daphnia pulex - Neonate | 48 hours |
| | Acute LC50 >1000 mg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| | Acute LC50 >1000000 µg/l Marine water | Fish - Fundulus heteroclitus | 96 hours |
| butan-2-ol | Acute EC50 4227 mg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 3670000 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| trizinc bis(orthophosphate) | Acute LC50 90 µg/l Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| zinc oxide | Acute EC50 1 mg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| | Acute EC50 0.622 mg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| | Acute EC50 0.481 mg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| | Acute LC50 1.25 mg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| | Acute LC50 98 µg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| | Acute LC50 2246000 µg/l Fresh water | Fish - Pimephales promelas - Neonate | 96 hours |
| | Acute LC50 1.1 ppm Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute LC50 3.969 mg/l Fresh water | Fish - Danio rerio - Adult | 96 hours |
| | Acute LC50 2.525 mg/l Fresh water | Fish - Danio rerio - Adult | 96 hours |

B. Persistence and degradability

Not available.

C. Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|--|--------|-----------------|--------------------|
| butan-2-ol trizinc bis(orthophosphate) Amines, polyethylenepoly-, triethylenetetramine fraction | -2.65 | - 60960 - | low high low |
| zinc oxide | | 28960 | high |

D. Mobility in soil

| Soil/water partition | : Not available. |
|----------------------|------------------|
| coefficient (Koc) | |

E. Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

A. Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.



Section 13. Disposal considerations

B. Disposal precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | - | | | |
|----------------------------------|---|---|---|--|
| | UN | IMDG | ΙΑΤΑ | |
| A. UN number | UN3082 | UN3082 | UN3082 | |
| B. UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis (orthophosphate), zinc oxide) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis (orthophosphate), zinc oxide) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (trizinc bis (orthophosphate), zinc oxide) | |
| C. Transport hazard class(es) | 9 | 9 | 9 | |
| D. Packing group | Ш | | | |
| E. Environmental hazards | Yes. | Marine Pollutant(s): trizinc bis(orthophosphate), zinc oxide | Yes. | |
| Additional informat | ion | - | | |
| UN | | regulated as a dangerous good v the packagings meet the general 1.8. | | |
| IMDG | This product is not or ≤5 kg, provided | Emergency schedules F-A, S-F This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. | | |
| ΙΑΤΑ | or ≤5 kg, provided | : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8. | | |
| F. Special precautio user | upright and secure | : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. | | |
| Transport in bulk ac | cording : Not available. | | | |

to IMO instruments

Section 15. Regulatory information

A. Regulation according to ISHA ISHA article 117 : None of the components are listed. (Harmful substances prohibited from manufacture) ISHA article 118 : None of the components are listed. (Harmful substances requiring permission)



Section 15. Regulatory information

| : Not applicable. |
|--|
| nical Substances and Physical Factors |
| s have an OEL: |
| : None of the components are listed. |
| : The following components are listed: 2-butanol, titanium dioxide, zinc oxide, chromium and its inorganic compounds, iron oxide |
| : The following components are listed: 2-Butanol, Zinc oxide, Chromium and its compounds, Iron oxide |
| Phe following components are listed: 2-butanol, titanium dioxide, zinc and its compounds, zinc and its compounds, zinc and its compounds, iron and its compounds |
| Chemicals Control Act |
| The following components are listed: Zinc and its compounds, Zinc and its compounds, Boron and its compounds, Chromium and its compounds |
| : None of the components are listed. |
| : None of the components are listed. |
| : Not applicable |
| : None of the components are listed. |
| : None of the components are listed. |
| : The following components are listed: Trizinc bis(orthophosphate, Zinc oxide, Boric acid zinc salt, Quartz, Triphenyl phosphite |
| : Class: Specified flammables Item: Combustible liquid Threshold: 2 m ³ Danger category: Not applicable Signal word: Not applicable |
| |



Section 15. Regulatory information

D. Wastes regulation

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

E. Regulation according to other foreign laws

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Section 16. Other information

| A. References | : Not available. |
|--------------------------------|----------------------|
| B. Date of issue/Date revision | of : 27 October 2022 |
| C. Version | : 1.03 |
| Unique ID | : |
| Date of printing | : 31 October 2022 |

D. Other

Indicates information that has changed from previously issued version.

| emicals |
|---------|
| |
| |
| |
| |
| Ships, |
| • |
| |
| |
| |
| |
| |

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

| Date of issue/Date of revision | : 27-10-2022 | Version : 1.03 | |
|--------------------------------|--------------|----------------|-----------|
| Date of previous issue | : 6-10-2022 | 12/13 | AkzoNobel |

Section 16. Other information

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

