

# **SAFETY DATA SHEET**

THINNER P2-2 THINNER .

## **Section 1. Identification**

Product identifier

: THINNER P2-2 THINNER .

SDS code

: 15100200X

### Relevant identified uses of the substance or mixture and uses advised against

	Recomme	nded use	
Thinner. Industrial use			
	Restrictio	ns on use	
All other uses			
Product use	: Thinner		
Supplier's details			
MAPAERO SAS 10, Avenue de la R 09103 PAMIERS C France			
Emergency telephone number (with hours of operation)	: +33 (0)5 34 01 34 01 +33 (0)5 61 60 23 30		
Section 2. Hazard	d identification		
Classification of the substance or mixture	: FLAMMABLE LIQUIDS - ACUTE TOXICITY (oral) ACUTE TOXICITY (inhala SPECIFIC TARGET ORG Category 3	- Category 4	URE) (Narcotic effects) -
GHS label elements			
Hazard pictograms			
Signal word	: Warning		
Hazard statements	: Combustible liquid. Harmful if swallowed or if May cause drowsiness or		
Precautionary statements	<u>s</u>		
Prevention		surfaces, sparks, open flames an ning vapor. Do not eat, drink or s roughly after handling.	
Response	•	ON CENTER or doctor if you feel	unwell.
Storage	: Store in a well-ventilated p	blace. Keep container tightly close	ed.
Date of issue/Date of revision	: 4/28/2023	Version : 1	
Date of previous issue	: No previous validation	1/11	AkzoNobel

### Section 2. Hazard identification

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

## Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

Ingredient name	% (w/w)	CAS number
heptan-2-one	≥80	110-43-0

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-aid measures

Description of necessary first	aid measures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Potential acute health effe	<u>ects</u>	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	Harmful if swallowed. Can cause central nervous system (CNS) depression.
<u>Over-exposure signs/sym</u>	ptom	<u>15</u>
Eye contact	:	No specific data.

Date of issue/Date of revision	: 4/28/2023	Version :1
Date of previous issue	: No previous validation	2/11



### **Section 4. First-aid measures**

Inhalation	: Adverse symptoms may include the following:
	nausea or vomiting
	headache
	drowsiness/fatigue
	dizziness/vertigo
	unconsciousness
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

		<b>o</b>
Extinguishing media		
Suitable extinguishing media		: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishin media	g	: Do not use water jet.
Specific hazards arising from the chemical		: Combustible liquid. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous thermal decomposition product	s	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective action for fire-fighters	S	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighter	rs	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, protec	ve equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Date of issue/Date of revision	: 4/28/2023	Version : 1	
Date of previous issue	: No previous validation	3/11	AkzoNobe

# Section 6. Accidental release measures

Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

Precautions for safe handling		
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

Control parameters

**Occupational exposure limits** 



# Section 8. Exposure controls/personal protection

Ingredient name		Exposure limits
heptan-2-one		<ul> <li>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 233 mg/m<sup>3</sup> 8 hours. 8 hrs OEL: 50 ppm 8 hours.</li> <li>CA British Columbia Provincial (Canada, 3/2022). TWA: 50 ppm 8 hours.</li> <li>CA Ontario Provincial (Canada, 6/2019). TWA: 25 ppm 8 hours. TWA: 115 mg/m<sup>3</sup> 8 hours.</li> <li>CA Quebec Provincial (Canada, 6/2021). TWAEV: 50 ppm 8 hours.</li> <li>TWAEV: 50 ppm 8 hours.</li> <li>TWAEV: 233 mg/m<sup>3</sup> 8 hours.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours.</li> </ul>
Appropriate engineering controls	ventilation or other engine contaminants below any r	entilation. Use process enclosures, local exhaust eering controls to keep worker exposure to airborne ecommended or statutory limits. The engineering controls por or dust concentrations below any lower explosive of ventilation equipment.
Environmental exposure controls	they comply with the requi cases, fume scrubbers, fil	n or work process equipment should be checked to ensure irements of environmental protection legislation. In some lters or engineering modifications to the process ary to reduce emissions to acceptable levels.
Individual protection meas	sures	
Hygiene measures	eating, smoking and using Appropriate techniques sh Wash contaminated clothi	nd face thoroughly after handling chemical products, before g the lavatory and at the end of the working period. nould be used to remove potentially contaminated clothing. ing before reusing. Ensure that eyewash stations and to the workstation location.
Eye/face protection	assessment indicates this gases or dusts. If contact	g with an approved standard should be used when a risk is necessary to avoid exposure to liquid splashes, mists, t is possible, the following protection should be worn, dicates a higher degree of protection: safety glasses with
Skin protection		
	: Chemical-resistant, imper	vious gloves complying with an approved standard should
Hand protection	be worn at all times when this is necessary. Consid check during use that the should be noted that the ti different for different glove	handling chemical products if a risk assessment indicates ering the parameters specified by the glove manufacturer, gloves are still retaining their protective properties. It ime to breakthrough for any glove material may be e manufacturers. In the case of mixtures, consisting of rotection time of the gloves cannot be accurately
Hand protection	<ul> <li>be worn at all times when this is necessary. Consid check during use that the should be noted that the ti different for different glove several substances, the p estimated.</li> <li>Personal protective equiption</li> </ul>	ering the parameters specified by the glove manufacturer, gloves are still retaining their protective properties. It ime to breakthrough for any glove material may be e manufacturers. In the case of mixtures, consisting of rotection time of the gloves cannot be accurately ment for the body should be selected based on the task risks involved and should be approved by a specialist



## Section 8. Exposure controls/personal protection

```
Respiratory protection
```

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state	: Liquid.
Color	: Colorless.
Odor	: Characteristic.
Odor threshold	: Not available.
рН	: Not applicable. [DIN EN 1262]
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: Not available.
Flash point	: Closed cup: 62°C (143.6°F) [Pensky-Martens]
Flammability	: Not available.
Lower and upper explosion limit/flammability limit	: Not available.

#### Vapor pressure

	V	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
heptan-2-one	6.88	0.92					
Relative vapor density	: Not ava	ailable.	Į				
Density	: 0.816 g	: 0.816 g/cm³ [DIN EN ISO 2811-1]					

: 0.816 g/cm<sup>3</sup> [DIN EN ISO 2811-1]

÷

2

2

#### Solubility(ies)

Ī	Media	Result
	cold water	Not soluble [OESO (TG 105)]

#### Partition coefficient: n-: Not applicable.

#### octanol/water

#### Auto-ignition temperature

Ing	gredient name			°C	°F	Method
hep	tan-2-one			393	739.4	
Deco	mposition temperature	:	Not availab	le.	ł	ł
Visco	osity	:	Kinematic ( Kinematic (	room temperature) 40°C (104°F)): 6 m	): 12 mm²/s (12 cSt nm²/s (6 cSt) [DIN I	:) [DIN EN ISO 3219] EN ISO 3219]
	<u>cle characteristics</u> ian particle size	:	Not applica	ble.		



# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

#### Information on toxicological effects

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
heptan-2-one	LD50 Dermal	Rabbit	12600 uL/kg	-
	LD50 Intraperitoneal	Mouse	400 mg/kg	-
	LD50 Intraperitoneal	Rat	800 mg/kg	-
	LD50 Oral	Mouse	730 mg/kg	-
	LD50 Oral	Rat	1670 mg/kg	-
	LD50 Oral	Rat	1600 mg/kg	-

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
heptan-2-one	Skin - Mild irritant	Rabbit	-	24 hours 14 mg	-

### Sensitization

Not available.

### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
heptan-2-one	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Not available.

Date of issue/Date of revision	: 4/28/2023	Version : 1	
Date of previous issue	: No previous validation	7/11	AkzoNobel

# Section 11. Toxicological information

### Aspiration hazard

Not available.

Information on the likely routes of exposure	: Not available.
Potential acute health effects	
Eye contact	: No known significant effects or critical hazards.
Inhalation	: Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: Harmful if swallowed. Can cause central nervous system (CNS) depression.
Symptoms related to the phy	sical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate effect	ts and also chronic effects from short and long term exposure
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
Numerical measures of toxic	ity
Acute toxicity estimates	

N/A



# Section 12. Ecological information

#### <u>Toxicity</u>

Product/ingredient name	Result	Species	Exposure
heptan-2-one	Acute LC50 131000 μg/l Fresh water	Fish - Pimephales promelas	96 hours

### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
heptan-2-one	2.26	-	low

### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	TDG Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Date of issue/Date of revision	: 4/28/2023	Version :1	
Date of previous issue	: No previous validation	9/11	AkzoN

obe

# Section 14. Transport information

Additional information IMDG	:	IMDG Code Segregation group Not applicable
Special precautions for user	:	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according to IMO instruments	:	Not available.

### Section 15. Regulatory information

Canadian lists	
Canadian NPRI	: None of the components are listed.
CEPA Toxic substances	: None of the components are listed.
Inventory list	
Canada	: All components are listed or exempted.
United States	: All components are active or exempted.

# Section 16. Other information

<u>History</u>	
Date of printing	: 28 April 2023
Date of issue/ Date of revision	: 28 April 2023
Date of previous issue	: No previous validation
Version	: 1
Unique ID	:
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals HPR = Hazardous Products Regulations IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

### Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	On basis of test data Calculation method Calculation method Calculation method

#### ✓ Indicates information that has changed from previously issued version.

Notice to reader



# Section 16. Other information

### FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

