

SAFETY DATA SHEET

FR2-55 SEMI-GLOSS BASE SMOKE WHITE AIC 12.5

Section 1. Identification

GHS product identifier : FR2-55 SEMI-GLOSS BASE SMOKE WHITE AIC 12.5

SDS code : 55981205B

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Waterborne paint. Professional use Industrial use

Uses advised against

All other uses

Product use : Waterborne coating for interior use.

Supplier's details

MAPAERO SAS

10, Avenue de la Rijole CS30098

09103 PAMIERS Cedex

France

Emergency telephone number (with hours of

number (with hoperation)

: +33 (0)5 34 01 34 01

+33 (0)5 61 60 23 30

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture

: CARCINOGENICITY - Category 2

GHS label elements
Hazard pictograms

Signal word : Warning

Hazard statements: Suspected of causing cancer.

Precautionary statements

Prevention : Øbtain special instructions before use. Wear protective gloves, protective clothing and

eye or face protection.

Response: F exposed or concerned: Get medical advice or attention.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Date of issue/Date of revision :10/31/2022 Version :2

Date of previous issue : 10/21/2022 1/11 AkzoNobel

Section 2. Hazards identification

Hazards not otherwise

classified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Manium dioxide	≥10 - ≤25	13463-67-7
silicon dioxide	≤3	7631-86-9
Talc , not containing asbestiform fibres	≤3	14807-96-6
Chlorite-group minerals	≤3	1318-59-8
Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether	≤3	9038-95-3
aluminium hydroxide	≤3	21645-51-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower Eye contact

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If

not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact : Fush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing

before reuse. Clean shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and

the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing

such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. : No known significant effects or critical hazards. Ingestion

Over-exposure signs/symptoms

Eye contact : No specific data. Inhalation : No specific data. Skin contact : No specific data.

Date of issue/Date of revision Version : 2 : 10/31/2022

AkzoNobel Date of previous issue :10/21/2022 2/11

Section 4. First aid measures

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective :

equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 10/31/2022 Version : 2

Date of previous issue : 10/21/2022 3/11 AkzoNobel

Section 6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

• Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
iranium dioxide	OSHA PEL (United States, 5/2018).
	TWA: 15 mg/m³ 8 hours. Form: Total dust
	OSHA PEL 1989 (United States, 3/1989).
	TWA: 10 mg/m³ 8 hours. Form: Total dust
	ACGIH TLV (United States, 3/2020). Notes:
	Substance identified by other sources as a
	suspected or confirmed human carcinogen.
	1996 Adoption Substances for which the
	TLV is higher than the OSHA Permissible
	Exposure Limit (PEL) and/or the NIOSH
	Recommended Exposure Limit (REL). See
	CFR 58(124) :36338-33351, June 30, 1993,
	for revised OSHA PEL. Refers to Appendix
	A Carcinogens.
	TWA: 10 mg/m³ 8 hours.
silicon dioxide	None.
Talc , not containing asbestiform fibres	None.
Chlorite-group minerals	None.
Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether	None.
aluminium hydroxide	None.

 Date of issue/Date of revision
 : 10/31/2022
 Version
 : 2

 Date of previous issue
 : 10/21/2022
 4/11
 AkzoNobel

Section 8. Exposure controls/personal protection

Appropriate engineering controls

: Wuser operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing.

Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-

shields.

Skin protection

Hand protection : **⊘**hemical-resistant, impervious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the

protection time of the gloves cannot be accurately estimated.

Body protection: Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before

handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

Respiratory protection: Based on the hazard and potential for exposure, select a respirator that meets the

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.
Color : White.

Odor : Characteristic.
Odor threshold : Not available.

8 : Hq

Melting point: Not available.Boiling point: Not available.

Flash point : Closed cup: 105°C (221°F)

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Upper/lower flammability or : Not available.

explosive limits

Vapor pressure : Not available.

Date of issue/Date of revision : 10/31/2022 Version : 2

Date of previous issue : 10/21/2022 5/11 AkzoNobel

Section 9. Physical and chemical properties

Vapor density : Highest known value: (Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether).

Density : 1.465 g/cm³

Solubility(ies) : Easily soluble in the following materials: cold water.

Partition coefficient: n-

octanol/water

: Not available.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether	LC50 Inhalation Vapor	Guinea pig	293 mg/m³	4 hours
,	LC50 Inhalation Vapor	Mouse	174 mg/m³	4 hours
	LC50 Inhalation Vapor	Rat	4770 mg/m ³	4 hours
	LC50 Inhalation Vapor	Rat	4670 mg/m ³	4 hours
	LC50 Inhalation Vapor	Rat	147 mg/m³	4 hours
	LC50 Inhalation Vapor	Rat	330 mg/m ³	4 hours
	LD50 Dermal	Rabbit	>20 g/kg	-
	LD50 Dermal	Rabbit	20 mL/kg	-
	LD50 Dermal	Rabbit	14100 uL/kg	-
	LD50 Intraperitoneal	Rat	2600 mg/kg	-
	LD50 Oral	Mouse	49 g/kg	-
	LD50 Oral	Mouse	7460 mg/kg	-
	LD50 Oral	Rabbit	16 g/kg	-
	LD50 Oral	Rabbit	1770 mg/kg	-
	LD50 Oral	Rat	5 g/kg	-
	LD50 Oral	Rat	45 g/kg	-
	LD50 Oral	Rat	4 mL/kg	-
	LD50 Oral	Rat	6130 mg/kg	-
	LD50 Oral	Rat	5370 mg/kg	-
	LD50 Oral	Rat	9610 mg/kg	-
	LD50 Oral	Rat	12300 uL/kg	-
	LD50 Oral	Rat	9170 uL/kg	-
	LD50 Oral	Rat	38400 uL/kg	-
	LD50 Oral	Rat	8530 uL/kg	-
	LD50 Oral	Rat	18300 uL/kg	-
	LD50 Oral	Rat	20600 uL/kg	-

Irritation/Corrosion

Date of issue/Date of revision: 10/31/2022Version: 2Date of previous issue: 10/21/20226/11AkzoNobel

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
silicon dioxide	Eyes - Mild irritant	Rabbit	-	24 hours 25	-
				mg	
Oxirane, 2-methyl-, polymer	Eyes - Severe irritant	Rabbit	-	50 mg	-
with oxirane, monobutyl ether					
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-
silicon dioxide	-	3	-
Talc , not containing asbestiform fibres	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure

: Not available.

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Date of issue/Date of revision : 10/31/2022 Version : 2

Date of previous issue : 10/21/2022 7/11 AkzoNobel

Section 11. Toxicological information

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

effects

: Not available.

Potential delayed effects

: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General: No known significant effects or critical hazards.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity : No known significant effects or critical hazards.Reproductive toxicity : No known significant effects or critical hazards.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
iitanium dioxide	Acute EC50 19.3 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 27.8 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 35.306 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 13.4 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3.6 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 15.9 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 13 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000 mg/l Fresh water Acute LC50 >1000000 µg/l Marine wate	Fish - Pimephales promelas Fish - Fundulus heteroclitus	96 hours 96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Date of issue/Date of revision : 10/31/2022 Version : 2

Date of previous issue : 10/21/2022 8/11 AkzoNobel

Section 12. Ecological information

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	DOT Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according: Not available. to IMO instruments

Date of issue/Date of revision Version : 2 : 10/31/2022

AkzoNobel Date of previous issue : 10/21/2022 9/11

Section 15. Regulatory information

U.S. Federal regulations

: United States inventory

(TSCA 8b):

Not determined.

State regulations

Massachusetts : The following components are listed: TITANIUM DIOXIDE; TIN DIOXIDE DUST; TALC;

SOAPSTONE; DIATOMACEOUS EARTH; AMORPHOUS SILICA

New York: None of the components are listed.

New Jersey : The following components are listed: TITANIUM DIOXIDE; TITANIUM OXIDE (TiO2);

SOAPSTONE

Pennsylvania : The following components are listed: TITANIUM OXIDE; TALC; SOAPSTONE DUST;

SILICA

California Prop. 65

MARNING: Cancer - www.P65Warnings.ca.gov.

Ingredient name	•	Maximum acceptable dosage level
titanium dioxide crystalline silica, respirable powder	-	-

Inventory list

Canada : At least one component is not listed.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
☑ARCINOGENICITY - Category 2	Calculation method

History

Date of printing : 31 October 2022

Date of issue/ Date of : 31 October 2022

revision

Date of previous issue : 21 October 2022

Version : 2 Unique ID :

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

✓ Indicates information that has changed from previously issued version.

Notice to reader

Date of issue/Date of revision : 10/31/2022 Version : 2

Date of previous issue : 10/21/2022 10/11 AkzoNobel

Section 16. Other information

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision : 10/31/2022 Version : 2

Date of previous issue :10/21/2022 11/11 AkzoNobel