

SAFETY DATA SHEET

FR2-55-SG-TINT SEMI-GLOSS BASE GREEN SF3090

In accordance with the Standard for Classification and Labeling of Chemical Substance and Safety Data Sheet,
Article 10 Paragraph 1

Section 1. Chemical product and company identification

A. Product name : FR2-55-SG-TINT SEMI-GLOSS BASE GREEN SF3090

SDS code : 55993090B

B. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Waterborne paint. Professional use Industrial use

Uses advised against

All other uses

Product use : Waterborne coating for interior use.

C. Supplier's details

MAPAERO SAS

10, Avenue de la Rijole CS30098

09103 PAMIERS Cedex

France

e-mail address of

person responsible for

this SDS

Emergency telephone

number (with hours of

operation)

: PSRA_PAMIERS@akzonobel.com

: +33 (0)5 34 01 34 01 +33 (0)5 61 60 23 30

Section 2. Hazards identification

A. Hazard classification : Not classified.

This product was evaluated in accordance with the Industrial Safety and Health Act

and the Chemical Control Act, and determined to be 'not classified'.

B. GHS label elements, including precautionary statements

Signal word : No signal word.

Hazard statements: No known significant effects or critical hazards.

Precautionary statements

Prevention: P262 - Do not get in eyes, on skin, or on clothing.

Response : Not applicable.

Storage : Not applicable.

Disposal: P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Date of previous issue : 6-10-2022 1/11 AkzoNobel

FR2-55-SG-TINT SEMI-GLOSS BASE GREEN SF3090

Section 2. Hazards identification

C. Other hazards which do : None known. not result in

classification

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

| Ingredient name | Identifiers | % |
|--|-----------------|-----------|
| polychloro copper phthalocyanine | CAS: 1328-53-6 | ≥5 - <10 |
| Talc , not containing asbestiform fibres | CAS: 14807-96-6 | <10 |
| silicon dioxide | CAS: 7631-86-9 | <10 |
| 2-butoxyethanol | CAS: 111-76-2 | ≥0.1 - <5 |
| C(M)IT/MIT(3:1) | CAS: 55965-84-9 | <10 |
| ammonia, anhydrous | CAS: 7664-41-7 | <1 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

A. Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

B. Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

C. Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention if symptoms occur.

D. Ingestion : Wash out mouth with water. Remove victim to fresh air and keep at rest in a

> position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms

occur.

E. Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

A. Extinguishing media

Suitable extinguishing

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable

media

extinguishing media

: None known.

from the chemical

B. Specific hazards arising : In a fire or if heated, a pressure increase will occur and the container may burst.

Date of issue/Date of revision : 19-10-2022 Version: 1.02

AkzoNobel Date of previous issue : 6-10-2022 2/11

Section 5. Fire-fighting measures

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides

- C. Special protective equipment for fire-fighters
- : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode

Special precautions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures
- : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
- B. Environmental precautions
- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- C. Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

A. Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene

- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- B. Conditions for safe storage, including any incompatibilities
- : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of issue/Date of revision : 19-10-2022 Version : 1.02

Date of previous issue : 6-10-2022 3/11 AkzoNobel

Section 8. Exposure controls/personal protection

A. Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|-------------------------|---|
| 2 -butoxyethanol | Ministry of Employment and Labor |
| | (Republic of Korea, 1/2020). Absorbed |
| | through skin. |
| | TWA: 20 ppm 8 hours. |
| C(M)IT/MIT(3:1) | Ministry of Employment and Labor |
| | (Republic of Korea, 1/2020). |
| | TWA: 0.1 mg/m ³ 8 hours. Form: inhalable |
| | fraction |
| ammonia, anhydrous | Ministry of Employment and Labor |
| | (Republic of Korea, 1/2020). |
| | STEL: 35 ppm 15 minutes. |
| | TWA: 25 ppm 8 hours. |

B. Appropriate engineering

controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

C. Personal protective equipment

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Eye protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9. Physical and chemical properties

A. Appearance

Physical state : Liquid.
Color : Green.

B. Odor : Characteristic.C. Odor threshold : Not available.

D. **pH** : 8

E. Melting/freezing point : Not available.

Date of issue/Date of revision : 19-10-2022 Version : 1.02

Date of previous issue : 6-10-2022 4/11 AkzoNobel

FR2-55-SG-TINT SEMI-GLOSS BASE GREEN SF3090

Section 9. Physical and chemical properties

F. Boiling point/boiling

range

: Not available.

G. Flash point : Closed cup: 105°C (221°F)

Fire point : Not available. H. Evaporation rate : Not available. Flammability (solid, gas) : Not available. J. Lower and upper : Not available.

explosive (flammable)

limits

K. Vapor pressure : Not available.

L. Solubility : Easily soluble in the following materials: cold water.

Solubility in water : Not available.

M. Vapor density : Highest known value: (Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether).

N. Density : 1.203 g/cm³ O. Partition coefficient: n-: Not available.

octanol/water

P. Auto-ignition

: Not available.

temperature

Q. Decomposition temperature

: Not available.

R. Viscosity : Kinematic (room temperature): 4.82 cm²/s (482 cSt)

Kinematic (40°C (104°F)): 2.01 cm²/s (201 cSt)

Flow time (ISO 2431) : Not available.

S. Molecular weight : Not applicable.

Section 10. Stability and reactivity

A. Chemical stability : The product is stable.

reactions

Possibility of hazardous: Under normal conditions of storage and use, hazardous reactions will not occur.

B. Conditions to avoid : No specific data.

C. Incompatible materials : No specific data.

D. Hazardous : Under normal conditions of storage and use, hazardous decomposition products

decomposition products should not be produced.

Section 11. Toxicological information

A. Information on the likely : Not available.

routes of exposure

Potential acute health effects

Inhalation : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards. Skin contact No known significant effects or critical hazards. Eye contact : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation : No specific data.

Date of issue/Date of revision : 19-10-2022 Version: 1.02

AkzoNobel Date of previous issue : 6-10-2022 5/11

Section 11. Toxicological information

Ingestion: No specific data.Skin contact: No specific data.Eye contact: No specific data.

B. Health hazards

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|------------------------|------------|-------------------------|------------|
| 2-butoxyethanol | LC50 Inhalation Gas. | Mouse | 700 ppm | 7 hours |
| • | LC50 Inhalation Gas. | Rat | 450 ppm | 4 hours |
| | LC50 Inhalation Vapor | Mouse | 3380 mg/m ³ | 7 hours |
| | LC50 Inhalation Vapor | Rat | 2900 mg/m ³ | 7 hours |
| | LD50 Dermal | Guinea pig | 230 uL/kg | - |
| | LD50 Dermal | Rabbit | 220 mg/kg | - |
| | LD50 Intraperitoneal | Mouse | 536 mg/kg | - |
| | LD50 Intraperitoneal | Rabbit | 220 mg/kg | - |
| | LD50 Intraperitoneal | Rat | 220 mg/kg | - |
| | LD50 Intravenous | Mouse | 1130 mg/kg | - |
| | LD50 Intravenous | Rabbit | 252 mg/kg | - |
| | LD50 Intravenous | Rat | 307 mg/kg | - |
| | LD50 Oral | Guinea pig | 1200 mg/kg | - |
| | LD50 Oral | Mouse | 1230 mg/kg | - |
| | LD50 Oral | Mouse | 1167 mg/kg | - |
| | LD50 Oral | Rabbit | 300 mg/kg | - |
| | LD50 Oral | Rabbit | 320 mg/kg | - |
| | LD50 Oral | Rat | 917 mg/kg | - |
| | LD50 Oral | Rat | 250 mg/kg | - |
| | LD50 Route of exposure | Mouse | 1050 mg/kg | - |
| | unreported | | | |
| | LD50 Route of exposure | Rat | 917 mg/kg | - |
| | unreported | | | |
| ammonia, anhydrous | LC50 Inhalation Gas. | Mouse | 4230 ppm | 1 hours |
| • | LC50 Inhalation Gas. | Mouse | 4500 ppm | 1 hours |
| | LC50 Inhalation Gas. | Mouse | 21430 ppm | 30 minutes |
| | LC50 Inhalation Gas. | Rat | 9500 ppm | 1 hours |
| | LC50 Inhalation Gas. | Rat | 17401 ppm | 15 minutes |
| | LC50 Inhalation Gas. | Rat | 2000 ppm | 4 hours |
| | LC50 Inhalation Vapor | Mouse | 4600 mg/m ³ | 2 hours |
| | LC50 Inhalation Vapor | Rabbit | 7 g/m³ | 1 hours |
| | LC50 Inhalation Vapor | Rat | 7040 mg/m ³ | 30 minutes |
| | LC50 Inhalation Vapor | Rat | 4673 mg/kg | 4 hours |
| | LC50 Inhalation Vapor | Rat | 4673 mg/kg | 4 hours |
| | LC50 Inhalation Vapor | Rat | 18600 mg/m ³ | 5 minutes |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--|------------------|-------|--------------------------|-------------|
| sílicon dioxide | Eyes - Mild irritant | Rabbit | - | 24 hours 25 | - |
| 2-butoxyethanol | Eyes - Moderate irritant | Rabbit | - | mg 24 hours 100 mg | - |
| | Eyes - Severe irritant Skin - Mild irritant | Rabbit Rabbit | - | 100 mg 500 mg | - |

Sensitization

Not available.

CMR - ISHA Article 42 Occupational Exposure Limits

Date of previous issue : 6-10-2022 6/11 AkzoNobel

Section 11. Toxicological information

| Product/ingredient name | Identifiers | Classification |
|-------------------------|---------------|------------------------------|
| 2 -butoxyethanol | CAS: 111-76-2 | CARCINOGENICITY - Category 2 |

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP | ACGIH |
|--|---------|------|-----|---------|
| ralc , not containing asbestiform fibres | - | 3 | - | A4 |
| silicon dioxide 2-butoxyethanol | - - | 3 | - | - A3 |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Potential chronic health effects

Chronic toxicity

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Section 12. Ecological information

A. Ecotoxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--------------------------------------|--|----------|
| 2-butoxyethanol | Acute EC50 >1000 mg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 800000 μg/l Marine water | Crustaceans - Crangon crangon | 48 hours |
| | Acute LC50 1490000 µg/l Fresh water | Fish - Lepomis macrochirus | 96 hours |
| | Acute LC50 1250000 μg/l Marine water | Fish - Menidia beryllina | 96 hours |
| ammonia, anhydrous | Acute EC50 29.2 mg/l Marine water | Algae - Ulva fasciata - Zoea | 96 hours |
| | Acute LC50 2500 μg/l Fresh water | Crustaceans - Asellus aquaticus | 48 hours |
| | Acute LC50 4980 μg/l Marine water | Crustaceans - Penaeus japonicus - Nauplii | 48 hours |
| | Acute LC50 5210 μg/l Marine water | Crustaceans - Fenneropenaeus penicillatus - | 48 hours |

Date of issue/Date of revision : 19-10-2022 Version : 1.02

Date of previous issue :6-10-2022 7/11 AkzoNobel

Section 12. Ecological information

| | Zoea | |
|-----------------------------------|---------------------------------|----------|
| Acute LC50 2080 µg/l Fresh water | Crustaceans - Gammarus | 48 hours |
| | pulex | |
| Acute LC50 2710 μg/l Fresh water | Crustaceans - Ceriodaphnia | 48 hours |
| , 5 | reticulata | |
| Acute LC50 0.53 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| Acute LC50 25400 µg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| Acute LC50 4180 μg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| Acute LC50 4130 µg/l Fresh water | Daphnia - Daphnia pulex | 48 hours |
| Acute LC50 300 µg/l Fresh water | Fish - Hypophthalmichthys | 96 hours |
| · · | nobilis | |
| Acute LC50 450 µg/l Fresh water | Fish - Oncorhynchus | 96 hours |
| | tshawytscha - Underyearling | |
| Acute LC50 380 µg/l Fresh water | Fish - Hypophthalmichthys | 96 hours |
| | molitrix - Fingerling | |
| Acute LC50 660 µg/l Fresh water | Fish - Cyprinus carpio | 96 hours |
| Acute LC50 440 µg/l Fresh water | Fish - Cyprinus carpio | 96 hours |
| Chronic NOEC 550 µg/l Fresh water | Fish - Rutilus rutilus - Embryo | 31 days |
| Chronic NOEC 0.204 mg/l Marine | Fish - Dicentrarchus labrax | 62 days |
| water | | - |
| | | |

B. Persistence and degradability

Not available.

C. Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| 2 -butoxyethanol | 0.81 | - | low |

D. Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

E. Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

A. Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

B. Disposal precautions

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of previous issue : 6-10-2022 8/11 AkzoNobel

Section 14. Transport information

| | UN | IMDG | IATA |
|-------------------------------|----------------|----------------|----------------|
| A. UN number | Not regulated. | Not regulated. | Not regulated. |
| B. UN proper shipping name | - | - | - |
| C. Transport hazard class(es) | - | - | - |
| D. Packing group | - | - | - |
| E. Environmental hazards | No. | No. | No. |

F. Special precautions for user

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

Section 15. Regulatory information

A. Regulation according to ISHA

ISHA article 117

: None of the components are listed.

(Harmful substances prohibited from manufacture)

ISHA article 118 (Harmful substances : None of the components are listed.

requiring permission) **Article 2 of Youth**

: Not applicable.

Protection Act on Substances Hazardous

to Youth

Exposure Limits of Chemical Substances and Physical Factors

The following components have an OEL:

2-butoxyethanol C(M)IT/MIT(3:1) ammonia, anhydrous

ISHA Enforcement Regs Annex 19 (Exposure

: The following components are listed: ammonia

standards established for harmful factors)

ISHA Enforcement Regs Annex 21 (Harmful

: The following components are listed: talc; soapstone, silica

factors subject to Work **Environment**

Measurement)

ISHA Enforcement Regs: None of the components are listed.

Annex 22 (Harmful **Factors Subject to** Special Health Check-

up)

Date of issue/Date of revision : 19-10-2022 Version: 1.02

AkzoNobel Date of previous issue : 6-10-2022 9/11

Section 15. Regulatory information

Standard of Industrial Safety and Health **Annex 12 (Hazardous** substances subject to control)

: The following components are listed: copper and its compounds

B. Regulation according to Chemicals Control Act

CCA Article 11 (TRI)

: The following components are listed: Copper and its compounds

CCA Article 18 Prohibited (K-Reach : None of the components are listed.

Article 27)

CCA Article 19 Subject

: None of the components are listed.

to authorization (K-Reach Article 25)

CCA Article 20 Toxic Chemicals (K-Reach

: Not applicable

Article 20)

CCA Article 20

Restricted (K-Reach

: None of the components are listed.

Article 27)

CCA Article 39

(Accident Precaution

Chemicals)

: None of the components are listed.

Existing Chemical Substances Subject to

Registration

: The following components are listed: Quartz, 5-Chloro-2-methyl-3(2H)-isothiazolone,

mixt. With 2-methyl-3(2H)-isothiazolone, Ammonia

C. Dangerous Materials **Safety Management Act** : Class: Specified flammables Item: Combustible liquid

Threshold: 2 m3

Danger category: Not applicable Signal word: Not applicable

D. Wastes regulation

Dispose of contents and container in accordance with all local, regional, national

and international regulations.

E. Regulation according to other foreign laws

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Date of issue/Date of revision : 19-10-2022 Version: 1.02

AkzoNobel Date of previous issue : 6-10-2022 10/11

Section 16. Other information

A. References : Not available.B. Date of issue/Date of : 19 October 2022

revision

C. Version : 1.02

Unique ID :

Date of printing : 28 October 2022

D. Other

▼ Indicates information that has changed from previously issued version.

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision : 19-10-2022 Version : 1.02

Date of previous issue : 6-10-2022 11//11 AkzoNobel