

SAFETY DATA SHEET

THINNER 713 THINNER

Section 1. Identification

GHS product identifier SDS code

: THINNER 713 THINNER : 51713000X

Relevant identified uses of the substance or mixture and uses advised against

	Identified uses	
Thinner. Professional use Indu	ustrial use	
	Uses advised against	
All other uses		
Product use	: Thinner	
Supplier's details		
MAPAERO SAS 10, Avenue de la Rijo 09103 PAMIERS Ceo France		
e-mail address of person responsible for this SDS	: PSRA_PAMIERS@akzonobel.com	
Emergency telephone number (with hours of operation)	: +33 (0)5 34 01 34 01 +33 (0)5 61 60 23 30	

Section 2. Hazards identification

Classification of the	: FLAMMABLE LIQUIDS - Category 3
substance or mixture	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -
	Category 3

GHS label elements

Hazard pictograms



Signal word	: Warning
Hazard statements	: Flammable liquid and vapor. May cause drowsiness or dizziness.
Precautionary statements	
Prevention	: Keep away from heat, sparks and hot surfaces. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapor.
Response	: IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
Storage	: Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Date of issue/Date of revision	: 9-12-2022	Version : 2.01	
Date of previous issue	: 5-10-2022	1/11	AkzoNobel

Section 2. Hazards identification

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Clasificación de: peligro NCh382	:	
Distintivo Según NCh2190	:	Not applicable.
Señal de seguridad según NCh1411/4	:	

Other hazards which do not : None known. result in classification

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

Ingredient name	%	CAS number
r butyl acetate	≥90	123-86-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Becomption of neocoodiy me	
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Date of issue/Date of revision	: 9-12-2022	Version : 2.01	
Date of previous issue	: 5-10-2022	2/11	AkzoNobel

Section 4. First aid measures

Potential acute health	<u>effects</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness o dizziness.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: Can cause central nervous system (CNS) depression.
Over-exposure signs/s	symptoms
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: No specific data.
Ingestion	: No specific data.

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	 Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.



Section 6. Accidental release measures

Personal precautions, protec	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ontainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	Ĺ			
Protective measures		Put on appropriate personal protective of Avoid contact with eyes, skin and clothin with adequate ventilation. Wear appropriate inadequate. Do not enter storage areas ventilated. Keep in the original container compatible material, kept tightly closed heat, sparks, open flame or any other ig (ventilating, lighting and material handlin Take precautionary measures against e retain product residue and can be haza	ing. Avoid breathing vapor of priate respirator when ventil s and confined spaces unle er or an approved alternativ when not in use. Store and gnition source. Use explosi ng) equipment. Use only no electrostatic discharges. Er	or mist. Use only lation is iss adequately re made from a d use away from ion-proof electrical on-sparking tools. mpty containers
Advice on general occupational hygiene		Eating, drinking and smoking should be handled, stored and processed. Worke eating, drinking and smoking. Remove equipment before entering eating areas information on hygiene measures.	ers should wash hands and contaminated clothing and	face before protective
Conditions for safe storage, including any incompatibilities		Store in accordance with local regulatio area. Store in original container protect ventilated area, away from incompatible drink. Store locked up. Eliminate all ign materials. Keep container tightly closed that have been opened must be careful leakage. Do not store in unlabeled con- avoid environmental contamination. Se before handling or use.	ted from direct sunlight in a e materials (see Section 10) nition sources. Separate fro d and sealed until ready for lly resealed and kept uprigh tainers. Use appropriate co	dry, cool and well-) and food and om oxidizing use. Containers it to prevent ontainment to
Date of issue/Date of revision		: 9-12-2022	Version : 2.01	
Date of previous issue		: 5-10-2022	4/11	AkzoNobel

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
n-butyl acetate	Ministry of Health (Chile, 2/2018). STEL: 950 mg/m ³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 624 mg/m ³ 8 hours. TWA: 131 ppm 8 hours.

Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measu	res	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the



Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

	Closed cup	Open cup			
Flash point	: Øosed cup: 24°C (75.2°F) [Pensky-Marte	ens]			
Boiling point, initial boiling point, and boiling range	: Not available.				
Melting point/freezing point	Not available.				
рН	: <mark>M</mark> ot applicable. [DIN EN 1262]				
Odor threshold	: Not available.				
Odor	Characteristic.				
Color	: Colorless.				
Physical state	: Liquid.				

		Closed c	up	Open cup		
Ingredient name	°C	°F	Method	°C	°F	Method

Flammability

: Not available. Lower and upper explosion : Not available.

limit/flammability limit

Vapor pressure

	v	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
p-butyl acetate	11.25	1.5	DIN EN 13016-2				

Relative vapor density : Not available.

	:	Ø.881 g/cm ³ [DIN EN ISO 2811-1]
--	---	---

2

2

Solubility(ies)

Density

	Media	Result
	₽old water	Not soluble [OESO (TG 105)]
Ρ	artition coefficient: n- : Not	t applicable.

octanol/water

Auto-ignition temperature

Ingredient name		°C	°F	Method	
p≁butyl acetate		415	779	EU A.15	
Decomposition temperature	: Not ava	ailable.	I	I	
Viscosity				(11 cSt) [DIN EN ISO 3219] t) [DIN EN ISO 3219]	
Particle characteristics		•		-	
Median particle size	: Not app	olicable			

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.

Section 10. Stability and reactivity

Possibility of hazardous	: Under normal conditions of storage and use, hazardous reactions will not occur.
reactions	
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
p-butyl acetate	LC50 Inhalation Gas. LC50 Inhalation Vapor LD50 Dermal LD50 Intraperitoneal LD50 Oral LD50 Oral	Rat Mouse Rabbit Mouse Guinea pig Mouse	390 ppm 6 g/m ³ >17600 mg/kg 1230 mg/kg 4700 mg/kg 6 g/kg	4 hours 2 hours - - -
	LD50 Oral LD50 Oral	Rabbit Rat	3200 mg/kg 10768 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
p -butyl acetate	Eyes - Moderate irritant Skin - Moderate irritant	Rabbit Rabbit	-	100 mg 24 hours 500 mg	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
n-butyl acetate	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.



Ingestion

Section 11. Toxicological information

Information on the likely routes of exposure	: Not av	ailable.
Potential acute health effect		
Eye contact	: No kno	wn significant effects or critical hazards.
Inhalation	: Can ca dizzine	use central nervous system (CNS) depression. May cause drowsiness or ss.
Skin contact	: No kno	wn significant effects or critical hazards.
Ingestion	: Can ca	use central nervous system (CNS) depression.
Symptoms related to the ph	<u>sical, che</u>	nical and toxicological characteristics
Eye contact	: No spe	cific data.
Inhalation	nause heada drowsi dizzine	e symptoms may include the following: a or vomiting che ness/fatigue ss/vertigo sciousness
Skin contact	: No spe	cific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

: No specific data.

Section 12. Ecological information

Toxicity				
Product/ingredient name	Result	Species	Exposure	
<mark>∳-</mark> butyl acetate	Acute LC50 32 mg/l Marine water Acute LC50 62000 µg/l Fresh water Acute LC50 100000 µg/l Fresh water Acute LC50 185000 µg/l Marine water Acute LC50 18000 µg/l Fresh water	Crustaceans - Artemia salina Fish - Danio rerio Fish - Lepomis macrochirus Fish - Menidia beryllina Fish - Pimephales promelas	48 hours 96 hours 96 hours 96 hours 96 hours	

Persistence/degradability

Date of issue/Date of revision	: 9-12-2022	Version : 2.01	
Date of previous issue	: 5-10-2022	8/11	AkzoNobel

Section 12. Ecological information

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
p -butyl acetate	2.3	-	low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	NCh382/NCh2190	IMDG	IATA
UN number	UN1263	UN1263	UN1263
UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
Transport hazard class(es)	3	3	3
Packing group	III	III	
Environmental hazards	No.	No.	No.
Additional informat	tion		
Brazil IMDG	: <u>Risk number</u> 30 : <u>Emergency sched</u> MDG Code Segre	l <u>ules</u> F-E, _S-E_ gation group Not applicable	
Special precautions	-	user's premises: always transpo . Ensure that persons transporting	

the event of an accident or spillage.

Section 14. Transport information

Transport in bulk according : Not available. to IMO instruments

Section 15. Regulatory information

U		5
Local Regulations:	:	The recipient should verify the possible existence of local regulations applicable to the chemical.
DS 43: Reglamento de Almace DS 148: Reglamento Sanitario DS 298: Reglamenta el Transp DS 594: Reglamento sobre Co NCh 382: Mercancías Peligros NCh 2190: Transporte Terrestr NCh 2245: Hoja de Datos de S	enar sol oorte ondi as - re d Segu	ción de Riesgos Profesionales. miento de Sustancias Peligrosas. ore Manejo de Residuos Peligrosos. e de Cargas Peligrosas por Calles y Caminos. ciones Sanitarias y Ambientales Basicas en los Lugares de Trabajo. - Clasificación. e Mercancías Peligrosas - Distintivos para Identificación de Peligros. uridad para Productos Químicos - Contenido y Orden de las Secciones. s - Parte 4: Señales de Seguridad para la Identificación de Riesgos de Materiales.
Inventory list	0	
Australia	:	All components are listed or exempted.
Canada	:	All components are listed or exempted.
China	:	All components are listed or exempted.
Eurasian Economic Union	:	Russian Federation inventory : All components are listed or exempted.
Japan	:	Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): All components are listed or exempted.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Thailand	:	KI components are listed or exempted.
Turkey	:	All components are listed or exempted.
United States	:	All components are active or exempted.
Viet Nam		All components are listed or exempted.

Section 16. Other information

<u>History</u>	
Date of printing	: 9 December 2022
Date of issue/ Date of revision	: 9 December 2022
Date of previous issue	: 5 October 2022
Version	: 2.01
Unique ID	:
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Procedure used to derive the classification

Date of issue/Date of revision	: 9-12-2022	Version : 2.01	
Date of previous issue	: 5-10-2022	10/11	AkzoNobel

Section 16. Other information

Classification	Justification
	On basis of test data Calculation method

Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision	: 9-12-2022	Version : 2.01	
Date of previous issue	: 5-10-2022	11/11	AkzoNobel